

# Chapter 5: Performance and Optimization of the Everglades Stormwater Treatment Areas

Kathleen Pietro, Ron Bearzotti,  
Guy Germain and Nenad Iricanin

Contributors: Hongjun Chen, Michael Chimney,  
Stephen Colon, Tom DeBusk<sup>1</sup>, Michelle Ferree,  
Brian Garrett, Gary Goforth<sup>2</sup>, Delia Ivanoff, Bijaya  
Kattel, Christopher King, Mike Korvela, Jerry Krenz,  
Jim Galloway, Neil Larson, Jeremy McBryan, Lou Toth  
and Shi Kui Xue

---

## SUMMARY

---

As part of the ongoing efforts to restore the Everglades, the construction and operation of six large freshwater treatment wetlands was mandated by the Everglades Forever Act (Chapter 373.4592, Florida Statutes) and the Everglades Settlement Agreement. The overall efforts to improve water quality in the Everglades watershed and throughout the South Florida ecosystem involve the cooperation of the South Florida Water Management District (District or SFWMD), the U.S. Army Corps of Engineers, the Florida Department of Environmental Protection, and other agencies and private landowners. The mandates specifically required the construction of treatment wetlands, referred to as the Everglades Stormwater Treatment Areas (STAs). Over 65,000 acres of STAs (approximately 45,000 acres of effective treatment area) have been constructed south of Lake Okeechobee to remove excess phosphorus from surface waters prior to entering the Everglades Protection Area. Stormwater Treatment Areas 1 East, 1 West, 2, 3/4, 5, and 6 (STA-1E, STA-1W, STA-2, STA-3/4, STA-5, and STA-6, respectively) are operated under the Everglades Forever Act and National Pollutant Discharge Elimination System permits. This chapter serves as the reporting mechanism for STA performance, status, and condition during Water Year 2009 (WY2009) (May 1, 2008–April 30, 2009).

Since 1994, the STAs combined have retained more than 1,200 metric tons of total phosphorus that would have otherwise entered the Everglades. Despite the challenges of operating under regional drought conditions for the third consecutive water year, the six STAs together removed about 82 percent of the inflow total phosphorus load. During the dry season, the District implemented proactive operational strategies to protect the STAs, in accordance with the

---

<sup>1</sup> DB Environmental, Inc. Rockledge, FL

<sup>2</sup> Gary Goforth, Inc., Stuart, FL

33 STA Drought Contingency Strategy Document (SFWMD, 2007). During the WY2009 drought  
34 period, the water levels in most of the interior cells dominated by submerged aquatic vegetation  
35 (SAV) were maintained at about six inches above minimum target stage levels. During the  
36 WY2009 drought period, the water levels in many of the interior cells dominated by SAV were  
37 maintained at about six inches above minimum target stage levels. In some STAs, alternative  
38 means of water delivery were utilized to hydrate cells. For example, water was pumped from cells  
39 vegetated with emergent plants into SAV cells; construction dewatering water during the  
40 rehabilitation activities at STA-5, Cell 1A, was pumped into Cell 1B; construction and related  
41 dewatering activities at STA-1E provided supplemental water to STA-1W; and STA-1W, STA-2,  
42 STA-3/4, and STA-5 received about 20,676 acre-feet of supplemental water from Lake  
43 Okeechobee. Despite these efforts, parts of or entire SAV cells experienced dryouts and  
44 consequently SAV loss.

45 Agency staff and consultants continue to work together to maintain and further optimize STA  
46 performance. During WY2009, weekly operational meetings included making decisions on water  
47 flows and structure operation in the STAs based on near real-time data. Field assessments to  
48 monitor hydrologic conditions, water quality in cell inflows and outflows, soil condition, and  
49 vegetation continued. Rehabilitation efforts conducted in STA-1W in 2006–2007 continue to  
50 yield positive results in establishing desired plant communities and improving phosphorus  
51 removal performance. Research studies aimed at achieving better understanding STA  
52 performance and finding ways to improve sustainability also continued. Among these studies is  
53 mesocosm-scale research to determine cattail (*Typha* spp.) tolerance and stress patterns as  
54 affected by extreme water conditions, vegetation management studies, and internal water quality  
55 and soil transect studies to determine treatment gradient.

56 Detailed analysis of STA data also continued in WY2009. Notably, in STA-5, Cell 1A,  
57 results showed short-circuiting, resulting from a preexisting deep slough area, as one of the  
58 potential causes of this STA's poor performance. In response, the District completed earthwork to  
59 fill a large portion of this slough as part of the overall larger effort to rehabilitate this STA. For  
60 STA-6, analysis of historical data indicated that its declining performance was likely due to  
61 frequent cycles and extended periods of dryout.

62 SAV conversion of STA-3/4, Cell 1B, continued while SAV conversion in STA-1W, Cell 3,  
63 has been completed. Also, a partial conversion of STA-2, Cell 2, from emergent to submerged  
64 aquatic vegetation also began in this year.

65 In WY2009, there were large numbers of migratory birds that nested within the treatment  
66 cells. The presence of migratory bird nests within treatment cells restricts the ability to operate  
67 those cells due to protections set forth in the Migratory Bird Treaty Act. In accordance with the  
68 Avian Protection Plan for black-necked stilts (*Himantopus mexicanus*) and burrowing owls  
69 (*Athene cunicularia*) nesting in the STAs (Pandion Systems, Inc., 2008), nesting surveys were  
70 conducted through the nesting season, starting in mid-April 2009. Survey results were used in  
71 operational meetings during which water flow into the STAs was prioritized based on nest  
72 locations. A total of 873 nests were observed during levee surveys through July 2009.

73 Over the past year, several STAs had recreational facilities open for public access. These  
74 facilities include boardwalks, informational kiosks, and designated areas for bird watching and  
75 alligator and duck hunting. In late 2008, a customized boardwalk with a duck blind was  
76 constructed at STA-5 to provide hunting opportunities for the public, including access for  
77 disabled residents.

78

## INTRODUCTION


79

Major problems facing the Everglades are loss of habitat, disruption of hydroperiods and hydroperiod (i.e., duration, timing, volume, and distribution of water), coastal saltwater intrusion, degradation of water quality, and invasion of exotic plants. The 1994 Everglades Forever Act (EFA) addressed some of these issues through the implementation of the Everglades Agricultural Area (EAA) Best Management Practices (BMPs) and the Everglades Stormwater Treatment Areas (STAs). The STAs are a major component of the South Florida Water Management District's (District) Everglades restoration efforts. These are constructed wetlands that remove and store nutrients through several mechanisms including plant growth, accumulation of dead plant material in a layer of peat, settling and sorption, and microbial activities.

88

This chapter reports on the performance and condition of the six STAs (STA-1E, STA-1W, STA-2, STA-3/4, STA-5, and STA-6) (Figure 5-1 and Appendix 5-2). The STAs operate under the Everglades Forever Act and National Pollutant Discharge Elimination System (NPDES) permits and Administrative Orders (AOs). Varying in size, configuration, and period of operation, the STAs are shallow freshwater marshes divided into treatment cells by interior levees. Water flows through these systems via water control structures, such as pump stations, gates, or culverts. The dominant plant communities in the treatment cells are broadly classified into the following general categories: (1) emergent aquatic vegetation (EAV), (2) submerged aquatic vegetation (SAV), and (3) floating aquatic vegetation (FAV). This chapter includes permit-mandated reporting requirements, analysis of STA conditions and performance, highlights of key research and optimization activities, highlights of STA operation and maintenance activities, and a report on recreational and wildlife-related activities. *[Note: The STA-6 flow data is currently under review. The final chapter will be revised to include the updated flow data for all inflow and outflow structures, as well as the load estimates. The revisions will affect both WY2008 and WY2009 performance estimates for STA-6 and the overall POR estimates for all the STAs.]*

103



**Figure 5-1.** Location of the six Everglades Stormwater Treatment Areas (STAs) – STA-1E, STA-1W, STA-2, STA-3/4, STA-5, and STA-6).

104 STA treatment performance, which varies temporally and among STAs, depends on several  
 105 factors, such as antecedent land use, nutrient and hydraulic loading, vegetation composition and  
 106 condition, soil type, cell topography, cell size and shape, extreme weather conditions,  
 107 construction activities to improve performance (enhancement activities), and regional operations.  
 108 This chapter summarizes STA performance, construction, operation and maintenance, research,  
 109 and optimization efforts during Water Year 2009 (WY2009) (May 1, 2008– April 30, 2009). The  
 110 chapter serves to fulfill various permit reporting mandates (see the *Permit Status and Reporting*  
 111 *Mandates* section of this chapter and Appendix 5-1) and provides an evaluation of phosphorus (P)  
 112 target compliance and other water quality parameters, including dissolved oxygen (DO), mercury  
 113 (Hg), and other nutrients and major ions. An evaluation of long-term performance for each STA  
 114 and by individual flow-ways is also presented.

115 Additionally, WY2009 results from the research and monitoring conducted in areas receiving  
 116 STA discharges, i.e., Arthur R. Marshall Loxahatchee National Wildlife Refuge (Refuge), Water  
 117 Conservation Area 2A (WCA-2A), and the Rotenberger Wildlife Management Area (RWMA),  
 118 are summarized in this chapter. Summaries of STA research, the status of rehabilitation,  
 119 optimization activities, vegetation conversions, wildlife issues, recreational opportunities, and the  
 120 impact of the extreme events (storm and drought) on the STAs are also covered.

121 Appendices 5-1 through 5-14 provide supplementation information for the chapter (see  
 122 **Table 5-1**). Further details about individual STA performance are provided in Appendix 5-2,  
 123 which contains period of record (POR) time series graphs for inflow and outflow volume, total  
 124 phosphorus (TP) load, TP flow-weighted mean concentration (FWMC), and hydraulic and TP  
 125 loading rates. Other appendices contain a timeline of major operational activities in the STAs  
 126 from 2004 to present (Appendix 5-3), black-necked stilt nest survey results (Appendix 5-14),  
 127 compliance monitoring for mercury in the STAs (Appendix 5-6), information about herbicide  
 128 application in the STAs (Appendix 5-13), and raw data for other water quality parameters  
 129 (Appendices 5-4 and 5-5).

130

131

132

**Table 5-1.** Volume I, Chapter 5, appendix list.

Appendix Number	Appendix Title
5-1	Cross-Reference List for Everglades Forever Act Permit Reporting Requirements
5-2	Calculation Methodology for Estimating Flow and Total Phosphorus Loads and for Determining Effective Treatment Areas for the STAs
5-3	Individual Performance Time Series Plots and Period of Record Flow and Total Phosphorus Load Estimates for the STAs
5-4	Water Year 2009 Water Quality Data for STA-1E, STA-1W, STA-2, STA-3/4, STA-5 and STA-6
5-5	Water Year 2009 Dissolved Oxygen Data for STA-1E, STA-1W, STA-2, STA-3/4 and STA-5 and Site-Specific Alternative Criteria Estimates
5-6	Annual Permit Compliance Monitoring Report for Mercury in the STAs
5-7	Monthly Water Quality Data for Marsh Transect Stations at STA-1W, STA-1E, STA-2 and STA-5
5-8	Downstream Monitoring Station Database Codes
5-9	2008 Rotenberger Wildlife Management Area Topographic Map
5-10	Water Budgets, Total Phosphorus Budgets and Treatment Performance in STA Treatment Cells and Flow-ways
5-11	Summary Statistics for Water Quality Variables Monitored in the STA-3/4 PSTA Implementation Project
5-12	STA-3/4 PSTA Implementation Project Submerged Aquatic Vegetation Coverage Maps
5-13	STA Herbicide Application Summary for Water Year 2009
5-14	STA Black-Necked Stilt Nesting Summary for Water Year 2009
5-15	Supporting Information on Water Quality Data for the Everglades Stormwater Treatment Areas for Water Year 2009

133

134


135 **WATER YEAR 2009 HIGHLIGHTS**

- 136 • STA-1E, STA-1W, STA-2, STA-3/4, STA-5, and STA-6 are in compliance with the  
137 EFA and NPDES operating permits and AOs for WY2009 (**Figures 5-1** and **5-2**).  
138 New operating permits were issued in 2009 for STA-2, STA-5, and STA-6.
- 139 • Since 1994, the ECP STAs have retained 1,209 metric tons (mt) of TP that would  
140 have otherwise entered the EPA, reducing TP loads by 72 percent and concentrations  
141 from an overall annual TP FWMC of 144 to 40 parts per billion (ppb) (**Figure 5-3**,  
142 **Table 5-2**<sup>3</sup>, and Appendix 5-3).
- 143 • During WY2009, the six STAs received a total of 1,135,554 acre-feet (ac-ft) of  
144 water, equating to an average hydraulic loading rate of 2.24 centimeters per day  
145 (cm/day). The TP load received was 214.308 mt, equating to an average TP loading  
146 rate of 1.37 grams per square meter per year (g/m<sup>2</sup>/yr). An estimated 82 percent load  
147 reduction was achieved, with the STAs retaining 176 mt of TP and reducing inflow  
148 TP FWMC from 153 ppb to 25 ppb (**Table 5-2** and **Figure 5-4**). Lake Okeechobee  
149 releases and diversions are listed in **Table 5-4**.
- 150 • For the third consecutive year, drought conditions impacted the region. The STA  
151 Drought Contingency Strategy Document (SFWMD, 2007) was again implemented  
152 in an attempt to maintain minimum water levels in many STA cells. STA-1W,  
153 STA-2, STA-3/4, and STA-5 received about 20,676 ac-ft of supplemental water from  
154 Lake Okeechobee. While supplemental water was delivered to some STA cells  
155 during WY2009, there were still several cells that experienced dry-out conditions.
- 156 • Further refinements were made in the STA performance tool that is used to  
157 generate weekly reports. The tool was enhanced to include additional information to  
158 evaluate STA performance as it relates to the permit compliance limits. It utilizes  
159 near real-time data in comparing long-term performance estimates for operational  
160 decision making.
- 161 • The Avian Protection Plan for black-necked stilts (*Himantopus mexicanus*) and  
162 burrowing owls (*Athene cunicularia*) nesting in the STAs (APP) (Pandion Systems,  
163 Inc., 2008) was accepted by the U.S. Fish and Wildlife Service (USFWS) in  
164 September 2008. The APP is intended to minimize impacts to migratory birds nesting  
165 in the STAs while acknowledging that the STAs are operated for water quality  
166 treatment and flood control purposes. The plan provides an avian risk assessment  
167 methodology, mortality reduction measures, and reporting protocols.
- 168 • STA operations were affected with migratory birds nesting during the dry period.  
169 In accordance with the APP, surveys were conducted during the nesting season (April  
170 to June) to monitor for the presence of nests and eggs; information collected helped  
171 guide STA operations for water quality treatment while minimizing impacts to nests  
172 (see the *Wildlife and Avian Protection* section of this chapter).

---


<sup>3</sup> **Note:** The STA-6 flow data is currently under review. The final chapter will be revised to include the updated flow data for all inflow and outflow structures, as well as the load estimates. The revisions will affect both WY2008 and WY2009 performance estimates for STA-6 and the overall POR estimates for all the STAs.

- 173 • The phased vegetation conversion from EAV to SAV in STA-3/4, Cell 1B, continued  
 174 with positive results while the STA-1W, Cell 3, conversion was considered complete  
 175 (see the *Vegetation Conversion Status Updates* section of this chapter).
- 176 • STA-5 Southern Flow-way (Cells 3A and 3B) passed start-up criteria for TP and Hg  
 177 and began flow-through operations in August 2008. However, by January 2009, the  
 178 Southern Flow-way was dried out and supplemental water was not available to keep  
 179 the cells hydrated.
- 180 • While the STA-5 Southern Flow-way and STA-6 Section 2 became flow-capable in  
 181 December 2006, flow-through conditions did not occur until WY2009.
- 182 • Rehabilitation construction occurred in STA-5, Cell 1A, to help improve water  
 183 flow and treatment (see the *STA-5 Performance Analysis and Rehabilitation* section  
 184 of this chapter).
- 185 • Many of the STA recreational areas remained open for public access. In response to  
 186 a public request, a customized boardwalk with a duck blind was constructed in  
 187 STA-5 to provide hunting opportunities for the public, including access for the  
 188 disabled (see the *Recreational Facilities and Activities* section of this chapter).
- 189



**Figure 5-2.** Schematics of the STAs showing orientation of the treatment cells and locations of the permitted inflow and outflow stations.


190



191

**Figure 5-3.** (A) Overall annual inflow and outflow total phosphorus (TP) flow-weighted mean concentration (FWMC) and inflow volume, and (B) overall annual inflow and outflow TP loads and percent TP load retained by all the STAs. The amount of effective treatment area in the STAs varies as more treatment cells are built or as existing treatment cells undergo temporary restrictions during maintenance activities.

192



**Figure 5-4.** Water Year WY2009 (WY2009) (May 1, 2008–April 30, 2009) hydraulic and phosphorus loading rates and outflow TP FWMC for the STAs.



**Table 5-2. STA Performance for Water Year 2009 (WY2009)**  
(May 1, 2008–April 30, 2009) and period of record (POR) 1994–2009.

	STA-1E	STA-1W	STA-2	STA-3/4	STA-5	STA-6 <sup>f</sup>	All STAs
Average Effective Treatment Area (acres) <sup>a</sup>	5,011	6,670	8,240	16,543	4,505	2,257	43,226
<b>Rainfall</b>							
Total Annual Rainfall (inches)	51.3	51.3	49.1	48.0	42.8	44.4	47.8 <sup>g</sup>
SFWM Simulation Rainfall Range	39.8 - 77.5	36.6 - 77.4	35.4 - 71.6	32.3 - 70.7	38.6 - 61.4	46.8 - 57.6	---
<b>Inflow</b>							
Total Inflow Volume (ac-ft)	145,192	164,425	250,382	445,610	99,285	32,552	1,137,446
Total Inflow TP Load (mt)	32.612	49.917	37.604	52.515	31.155	10.595	214.398
Flow-weighted Mean Inflow TP (µg/L)	182	246	122	96	254	264	153
Hydraulic Loading Rate (HLR) (cm/d)	2.42	2.06	2.54	2.25	1.84	1.20	2.24
TP Loading Rate (PLR) (g/m <sup>2</sup> /yr)	1.61	1.85	1.13	0.78	1.71	1.16	1.37
<b>Outflow</b>							
Total Outflow Volume (ac-ft)	148,532	187,208	291,408	459,427	106,217	44,169	1,236,961
Total Outflow TP Load (mt)	3.874	8.208	6.503	7.357	7.315	5.068	38.325
Flow-weighted Mean Outflow TP (µg/L)	21	36	18	13	56	93	25
Hydraulic Residence Time (d)	23	14	19	21	12	5	---
TP Retained (mt)	28.738	41.709	31.101	45.158	23.840	5.527	176.073
TP Removal Rate (g/m <sup>2</sup> /yr)	1.42	1.55	0.93	0.67	1.31	0.61	1.01
Load Reduction (%)	88%	84%	83%	86%	77%	52%	82%
<b>Period of Record Performance</b>							
Start date	Sep-04	Oct-93	Jun-99	Oct-03	Oct-99	Oct-97	<b>1994 - 2008</b>
Inflow Volume (ac-ft)	407,026	2,832,614	2,197,055	2,520,635	1,049,406	478,121	9,484,857
TP Retained to Date (mt)	44.475	399.189	231.952	307.991	184.039	41.821	1,209.467
TP Outflow to Date (µg/L)	58	54	21	18	101	30	40
<b>Permit Mandated Reporting for WY2009 for the permits: Everglades Forever Act (EFA), National Pollutant Discharge Elimination System (NPDES), Administrative Order (AO)</b>							
	STA-1E	STA-1W	STA-2	STA-3/4	STA-5	STA-6	
Operational Permit Phase <sup>h</sup>	Stabilization	Stabilization	Stabilization	Post	Stabilization	Stabilization	
In compliance with Permits?	Yes	Yes	Yes	Yes	Yes	Yes	
Within Operational Envelope (Flow/Load)?	Yes/Yes	Yes/No	Yes/Yes	Yes/Yes	Yes/No	Yes/No	
Was EFA TBEL Achieved?	Yes	No <sup>b</sup>	Yes	Yes <sup>c</sup>	No <sup>b</sup>	No <sup>b</sup>	
Was NPDES/AO TBEL Achieved?	Yes	Yes	Yes	Yes	Yes	No <sup>b,d</sup>	
Was Dissolved Oxygen (DO SSAC) achieved? <sup>e</sup>	Yes	No	Yes	Yes	No	No	
Were there any Water Quality (other than phosphorus) excursions? <sup>e</sup>	No	No	No	No	No	No	
<b>Permit Limits</b>							
<b>Operational Envelope:</b>							
Avg. Inflow volume (ac-ft)	199,395	207,014	339,630	576,021	117,557	78,572	
Max. Inflow volume (ac-ft)	290,661	329,169	530,641	977,270	154,674	94,234	
Avg. Inflow TP load (mt)	33.441	44.510	42.823	64.821	28.912	8.290	
Max. Inflow TP load (mt)	48.870	72.273	70.367	117.668	47.252	10.714	
<b>Outflow EFA and NPDES/AO Limits:</b>							
Outflow EFA TBEL TP (ppb) Limit	30	32	24	76	52	22	
Outflow NPDES/AO TBEL TP (ppb) Limit	68	76	24	76	52	22	

**Comments:**

<sup>a</sup> Average effective treatment areas reflect treatment cells temporarily off-line for plant rehabilitation or LTP enhancements. Refer to Appendix 5-7 for details on how the effective treatment areas were estimated.

<sup>b</sup> Because the STA is in the stabilization phase of the permit, excursions to the TBEL limit are allowed. Details found in "ECP STA Performance" section of this chapter.

<sup>c</sup> STA-3/4 is operated under permits issued in 2004 and is considered to be in the post-stabilization phase and the TBEL limit is set at 76 ppb as defined in those permits.

<sup>d</sup> The total annual rainfall received by the STA was below the range of values used to develop the TBELs.

<sup>e</sup> See "Dissolved Oxygen", "STA Performance Water Year Synopsis" and "Water Quality" sections of this chapter for details.

<sup>f</sup> Flows recorded at STA-6 structures are questionable; surveying of structures being performed to correct flow data. Values associated with this STA will be revised.

<sup>g</sup> Average Annual Rainfall

<sup>h</sup> See "Permit Status and Reporting Mandates" section of this chapter for details.

**Notes:**

Flow-proportional autosamplers samples are used to calculate TP loads and concentrations, if available.

Period of record calculations include start-up data.

Concentrations expressed as parts per billion (ppb) are equal to µg/L.

The STA-6 flow data is currently under review. The final chapter will be revised to include the updated flow data for all inflow and outflow structures, as well as the load estimates. The revisions will affect both WY2008 and WY2009 performance estimates for STA-6 and the overall POR estimates for all of the STAs

**Table 5-3.** Current permit status and reporting criteria used during WY2009 to assess the STA phosphorus removal performance for the Everglades Forever Act (EFA) and National Pollutant Discharge Elimination System (NPDES) permits, and Administrative Orders (AOs). The AO, issued in conjunction with each of the STA permits, establishes a schedule for achieving compliance with the permit effluent limit.

<b>STA-1E Permit Phase: Eastern Flow-way Restricted Operations; Central and Western flow-ways in Extended Stabilization Phase</b>	
EFA permit 0279499-001-EM (issued 11/16/07) is in effect.	The TBEL criterion is applied to assess the phosphorus removal and for the reporting requirements.
NPDES permit FL0304549 (issued 8/30/05) and AO AO-009-EV (issued 8/30/08) are in effect.	These permits have the annual limit of 68 ppb and three-year target of 50 ppb, in lieu of the newer TBEL.
<b>STA-1W Permit Phase: All Treatment Cells in Extended Stabilization Phase</b>	
EFA permit 0279499-001-EM (issued 11/16/07) is in effect.	The TBEL criterion is applied to assess the phosphorus removal and for the reporting requirements.
NPDES permit FL0177962-001 (issued 5/11/99) and AO (issued 5/11/99) are in effect.	The NPDES and AO permits have the annual limit of 76 ppb and three-year target of 50 ppb, in lieu of the newer TBEL, for the STA when it is in the Post-stabilization Phase.
<b>STA-2 Permit Phase: Cells 1–4 in Stabilization Phase</b>	
EFA permit 0126704-008-EM (issued 3/17/09), NPDES permit FL0177946 (issued 9/4/07), and AO AO-010-EV (issued 3/17/09) are in effect.	The TBEL criterion is applied to assess the phosphorus removal and for the reporting requirements.
Note: AO authorizes continued operation of STA-2 and conditional authorization of the construction of Compartment B.	
<b>STA-3/4 Permit Phase: Post-Stabilization Phase (according to 2004 Issued Permit)</b>	
EFA permit 0192895 (issued 1/9/04), NPDES permit FL0300195 (issued 1/9/04), and AO (issued 1/9/04) are in effect.	These permits have the annual limit of 76 ppb and three-year target of 50 ppb, in lieu of the newer TBEL, for the STA when it is in the Post-stabilization Phase.
<b>STA-5 Permit Phase: North and Central Flow-way in Stabilization Phase, Southern Flow-way in Start-up Phase</b>	
EFA permit 0131842-009-EM (issued 1/29/09), NPDES permit FL0177954 (issued 9/4/07), and AO AO-011-EV (issued 1/29/09) are in effect.	The TBEL criterion is applied to assess the phosphorus removal and for the reporting requirements.
Note: AO authorizes continued operation of STA-5 and STA-6 and conditional authorization of the construction of Compartment C.	
<b>STA-6 Permit Phase: Section 1 and 2 in Stabilization Phase</b>	
EFA permit 0131842-009-EM (issued 1/29/09), NPDES permit FL0473804-001 (issued 9/4/07), and AO AO-011-EV (issued 1/29/09) are in effect.	The TBEL criterion is applied to assess the phosphorus removal and for the reporting requirements.

197  
198  
199

**Table 5-4.** Information fulfilling the permit-related reporting requirement for the amount of water diverted around the STAs and received by the STAs from Lake Okeechobee as regulatory inflows in WY2009.

STA	STA Diversion Structure Flow							Inflows from Lake Okeechobee <sup>c</sup>						
	STA Diversion <sup>a</sup>				Water Supply, Gate Maintenance, etc. <sup>b</sup>			Regulatory Release				Water Supply Release		
	Structure	Volume (ac-ft)	TP Load (mt)	FWM TP (ppb) <sup>d</sup>	Volume (ac-ft)	TP Load (mt)	FWM TP (ppb)	Structure	Volume (ac-ft)	TP Load (mt)	FWM TP (ppb)	Volume (ac-ft)	TP Load (mt)	FWM TP (ppb)
STA-1E	G300	----	----	----	12.4	0.005	304	G311	988	0.124	102	5,243	0.455	70
								S319	26,418	5.151	158	----	----	----
	<b>Total</b>	----	----	----	<b>12.4</b>	<b>0.005</b>	<b>304</b>	<b>Total</b>	<b>27,406</b>	<b>5.275</b>	<b>156</b>	<b>5,243</b>	<b>0.455</b>	<b>70</b>
STA-1W	G301	----	----	----	1.5	0.001	326	G302	2,556	0.326	103	13,568	1.793	107
	<b>Total</b>	----	----	----	<b>1.5</b>	<b>0.001</b>	<b>326</b>	<b>Total</b>	<b>2,556</b>	<b>0.326</b>	<b>103</b>	<b>13,568</b>	<b>1.793</b>	<b>107</b>
STA-2	G338	----	----	----	0	0	----	S6	501	0.012	19	5,587	0.286	42
	G339	----	----	----	4.5	0.0002	40							
	<b>Total</b>				<b>4.5</b>	<b>0.0002</b>	<b>40</b>	<b>Total</b>	<b>501</b>	<b>0.012</b>	<b>19</b>	<b>5,587</b>	<b>0.286</b>	<b>42</b>
STA-3/4	G371	3,963	0.660	135	20,124	1.512	61	G370	----	----	----	3,248	0.338	84
	G373	----	----	----	24,219	2.085	70	G372	----	----	----	5,250	0.455	70
	<b>Total</b>	<b>3,963</b>	<b>0.660</b>	<b>135</b>	<b>44,343</b>	<b>3.597</b>	<b>66</b>	<b>Total</b>	----	----	----	<b>8,498</b>	<b>0.793</b>	<b>76</b>
STA-5		----	----	----	----	----	----							
	<b>Total</b>	----	----	----	----	----	----	<b>Total</b>	----	----	----	----	----	----
STA-6	G407	----	----	----	28.8	0.007	192							
	<b>Total</b>	----	----	----	<b>28.8</b>	<b>0.007</b>	<b>192</b>	<b>Total</b>	----	----	----	----	----	----

**Operational Notes:**

- <sup>a</sup> The G-371 structure discharged approximately 650 ac-ft on September 5, 2008, approximately 2,600 ac-ft on September 6, 2008, and approximately 707 ac-ft on September 7, 2008. As a result of these actions, inflows to STA-3/4 were reduced, but the ability to divert stormwater through G-371 was limited due to the need to keep water levels in the North New River Canal lower in order to accommodate high EAA basin runoff.
- <sup>b</sup> Water was delivered via the G-373 structure to WCA-3A from January 15 to April 30 2009 and via G-371 to WCA-2A from February 5 to March 18th, 2009 for water supply deliveries during dry times. Some water delivered via G373 was delivered to Big Cypress Seminole Indian Reservation.
- <sup>c</sup> Water was delivered via the G-311, G-302, S-6, G-370 and G-372 structures from January 15 to April 30 2009 for water supply deliveries during dry times.
- <sup>d</sup> Concentrations expressed as parts per billion (ppb) are equal to µg/L.

## 200 **INDIVIDUAL STA HIGHLIGHTS**

### 201 **STA-1E**

- 202 • In WY2009, the Central and Western Flow-ways were operational. Discharges began  
203 in the Eastern Flow-way on June 10, 2008, but flow restrictions remained due to the  
204 U.S. Army Corps of Engineers (USACE) Periphyton-based Stormwater Treatment  
205 Area (PSTA) Demonstration Project in Cell 2.
- 206 • Structure S-375 was taken offline in March 2008 due to structural failure of the  
207 culverts. It is expected that the structure will remain offline for repairs during  
208 WY2010 and be operational by June 2010.
- 209 • Installation of a temporary structure (G-707) was completed in March 2009 to  
210 partially replace part of the conveyance through the failed S-375 structure. In  
211 addition, four 100 cubic feet per second (cfs) temporary pumps, installed in May  
212 2008, are also available to move water from the East Distribution Cell to the West  
213 Distribution Cell until S-375 is repaired.
- 214 • As part of damage assessment activities after Tropical Storm Fay in August 2008,  
215 some settlement and joint separation was identified at S-365A and S-365B. In April  
216 2009, S-365A was taken offline for inspection and repair activities, which are  
217 anticipated to be complete by August 2009. An assessment of S-365B is planned to  
218 occur after S-365A repairs are complete.
- 219 • Improved rating equations, based on revised flow ratings were developed for G-311,  
220 S-319, S-361, and S-362 flow data. The current ratings at these stations are effective  
221 since November 17, 2008, for S-319; August 25, 2008, for S-316; August 26, 2008,  
222 for S-362; and October 5–7, 2008, for G-311.
- 223 • In December 2008, the target stages in the SAV cells (Cells 4N, 4S and 6) were  
224 increased by six inches to help maintain water levels during the dry months and  
225 protect the vegetation from dry-out conditions. Due to the construction of structure  
226 G-707, supplemental water was not delivered, and as a result, Cells 1, 2, 3, 4N, and 5  
227 reached dry-out conditions as early as April 2009.

### 228 **STA-1W**

- 229 • In WY2009, all three flow-ways (Eastern, Western, and Northern) were operational.
- 230 • In December 2008, in accordance with the Drought Contingency Plan, target stages  
231 in the SAV cells (Cells 1B, 2B, 3, 4, and 5B) were increased by six inches to help  
232 maintain water levels during the dry months and protect the vegetation from dry-out  
233 conditions. Starting in January 2009, supplemental water was delivered, including  
234 water that was redirected from STA-1E as a result of dewatering activities related to  
235 installation of G-707. This action allowed the SAV cells in this STA stayed hydrated  
236 through the dry season.

### 237 **STA-2**

- 238 • In WY2009, all four flow-ways (Cells 1–4) were operational.
- 239 • Improved rating equations were developed for G-328I and G-337A, resulting in  
240 changes to the preferred flow record for G-328I from April 28, 2005 to August 10,  
241 2009 and for G-337A from July 18, 2008 to August 10, 2009.
- 242 • In anticipation of drought conditions, in December 2008 the between-storm target  
243 stages in the SAV cells were increased by six inches to maintain water levels and

244 protect the vegetation from dry-out conditions. Starting in January 2009,  
245 supplemental water was delivered to the SAV cells.

- 246 • The vegetation conversion from EAV to SAV in Cell 2 was initiated.

#### 247 **STA-3/4**

- 248 • In WY2009, all three flow-ways (Eastern, Central, and Western) were operational.
- 249 • The vegetation conversion from EAV to SAV in STA-3/4, Cell 1B, continued with  
250 positive results (see the *Vegetation Conversion Status Updates* section of this  
251 chapter).
- 252 • In anticipation of drought conditions, in December 2008 the between-storm target  
253 stages in the SAV cells (Cells 1B, 2B, and 3B) were increased by six inches to  
254 maintain water levels and protect the vegetation from dry-out conditions. Starting in  
255 January 2009, supplemental water was delivered and pumping from the EAV cells to  
256 the SAV cells was also initiated.

#### 257 **STA-5**

- 258 • In WY2009, the Central Flow-way (Cells 2A and 2B) was operational. The Northern  
259 Flow-way (Cells 1A and 1B) was offline starting in December 2008 for the Cell 1A  
260 Rehabilitation Project. The Southern Flow-way (Cells 3A and 3B) passed start-up  
261 criteria for TP and Hg and discharge operations in August 2008; however, it was  
262 offline again starting in April 2009 for activities related to the Cell 1A Rehabilitation  
263 Project.
- 264 • Rehabilitation construction for Cell 1A started in December 2009 (see the *STA-5*  
265 *Data Analysis and Rehabilitation* section of this chapter).
- 266 • In anticipation of drought conditions, in December 2008 the between-storm target  
267 stages in the SAV cells were increased by six in. to maintain water levels and protect  
268 the vegetation from dry-out conditions. Water that was pumped out of Cell 1A during  
269 construction was redirected into Cells 1B and 2A. However, no other sources of  
270 supplemental water was available to be delivered to the Southern Flow-way and, as a  
271 result, it dried out by January 2009. Starting in February 2009, supplemental water  
272 was delivered to Cell 1B through the G-507 pump (1.28 mt of TP; 10,643 ac-ft;  
273 annual TP FWMC 98 ppb), and Cell 2B received water from Cell 1B via the internal  
274 G-345 culvert.
- 275 • A new survey was conducted during WY2009 at the Cell 3A and Cell 3B structures  
276 to improve stage measurements and flow estimates.

#### 277 **STA-6**

- 278 • IN WY2009, all three flow-ways (Cell 3, Cell 5, and Section 2) were operational.
  - 279 • In anticipation of drought conditions, in December 2008 the between-storm target  
280 stage in the SAV cell (Section 2) was increased by six inches to maintain water levels  
281 and protect the vegetation from dry-out conditions, however, no supplemental  
282 water was available to be delivered. As a result, all three flow-ways dried out by  
283 January 2009.
  - 284 • A new elevation survey was conducted during WY2009 at all inflow and outflow  
285 structures and is intended to improve stage measurements and flow estimates.
- 286

---

## STA PERFORMANCE

---

287

### PERMIT STATUS AND REPORTING MANDATES

#### Permit Phases and Phosphorus Loading Requirements

290 In calendar year 2007 (CY2007), new operating permits (EFA, NPDES, and AOs) were  
291 issued for all STAs, except for STA-3/4, requiring Technology Based Effluent Limits (TBELs)  
292 for total phosphorus (TP) as well as comparisons of actual TP loads to the operational envelopes  
293 (**Table 5-3**). STA-3/4 is still operating under permits issued in CY2004. The new STA-3/4 permit  
294 is currently being developed and, in the interim, the existing permit has been extended to allow  
295 time to complete processing of the new permit. The Technical Support Documents for the TBELs  
296 explain the derivation of the TBEL limits and identify factors that may impact flows and loads  
297 associated with the treatment system. The Operational Envelope criterion was added to account  
298 for the variable inflows the STAs receive. The original conceptual design of the STAs was based  
299 on a first-order phosphorus removal model and annual-average data. Because this design  
300 approach did not consider the temporal/seasonal characteristics of the inflows, there was little  
301 reference against which actual inflows and resulting STA performance could be assessed. By  
302 contrast, the design of the STA enhancements and projections of performance were based on a  
303 dynamic model utilizing a 31-year set of simulated daily flows and TP loads, also referred to as  
304 the Operational Envelope. This design approach captures the variability of inflows and provides a  
305 reference against which actual inflows can be compared to the predicted inflows. Weekly  
306 summaries comparing the actual inflows to the Operational Envelopes are used to assist in  
307 operational decision making to try to ensure that the STAs are not subject to overload of either  
308 flow or nutrients.

309 The operating permits recognize that the natural systems undergo maturity changes and the  
310 STAs are categorized into phases, depending on the developmental and performance phase of the  
311 system. The permits describe three phases with regard to application of the TBEL: Start-up Phase,  
312 Stabilization Phase, and Routine Operations Phase. The TBEL does not apply until the STA is in  
313 the Routine Operations Phase. STA-1E, STA-1W, STA-2, STA-5, and STA-6 operations are in  
314 the Stabilization Phase, which ends when the STA achieves the annual TP limits as defined in the  
315 TBEL. Because STA-3/4 is operating under permits issued in CY2004, it is considered to be in  
316 the Post-stabilization Phase and the TBEL identified in that permit applies. As defined in the EFA  
317 permit issued in CY2007, during the Stabilization Phase, the vegetation will be maturing and the  
318 STA performance will generally be improving toward achieving the TBEL. It is anticipated that  
319 the vegetation may require one to three years after flow-through operations begin for the  
320 treatment cells to achieve optimal treatment performance. During the stabilization phase, the  
321 TBEL applies, and it is also acknowledged that exceedances of the TBEL may occur. An STA or  
322 flow-way may enter the Stabilization Phase after one of four antecedent conditions occurs (1)  
323 once flow-through operations begin following the initial start-up of a new treatment cell, (2)  
324 when a treatment cell is taken offline for implementation of Long-Term Plan enhancements that  
325 may have adverse impacts on STA performance, (3) when a treatment cell is taken offline for  
326 recovery activities associated with a major event that compromises the structural integrity or  
327 performance of the STA, or (4) when planned or unplanned maintenance activities would cause  
328 adverse impacts to the STA treatment capabilities.

329 The STA flow volumes are based on daily average surface water flow, and the TP loads are  
330 calculated using weekly flow or time-proportional auto-sampler data. If auto-sampler data are not  
331 available, then TP data from grab samples collected during flow events are used instead. The TP  
332 loads in surface water inflow and outflow were calculated using a Microsoft Excel VBA  
333 application that accessed the District's hydrometeorologic database DBHYDRO (Reardon and

334 Germain, 2005). Both positive and negative (i.e., reverse) flows at water control structures were  
335 used in these calculations.

## 336 WATER YEAR 2009 PERFORMANCE

### 337 STA Hydraulic and Phosphorus Loading

338 In WY2009, about 176 metric tons (mt) of TP that would have entered the Everglades was  
339 instead retained in the STAs. The percent of TP retained (i.e., a comparison of outflow to inflow)  
340 for the year ranged from 52 percent for STA-6 to 88 percent for STA-1E. The STAs reduced the  
341 inflow TP load by 82 percent, decreasing total inflow TP flow-weighted mean concentration  
342 (FWMC) from 153 to 25 parts per billion (ppb). Since 1994, the total amount of TP retained in  
343 the STAs is about 1,200 mt (**Table 5-2**, **Figure 5-3**, and Appendix 5-2 of this volume).  
344 The annual STA TP mass removal rates (also referred to as the effective settling rate) for  
345 WY2009 increased for all the STAs compared to WY2008, and ranged from 5 to 19 meters per  
346 year (STA-6 and STA-1E, respectively) (Appendix 5-2 of this volume).

347 During WY2009, the flows and TP loads into the STAs were not constant, which is consistent  
348 with the seasonality effects of weather anticipated in the design of the STAs. Inflows occurred  
349 from June through October 2008, and were small to non-existent during the remaining months of  
350 the water year. Peak inflows occurred in all the STAs in August 2008 due to Tropical Storm Fay  
351 (details about the storm are presented in Chapter 2 of this volume and impacts on the STAs are  
352 presented in the *Tropical Storm Fay Impacts on the STAs* section of this chapter). Ironically,  
353 Tropical Storm Fay arrived in the midst of the third consecutive year of the regional drought  
354 conditions. The 2006 –2009 drought in South Florida is considered to be one of the most severe  
355 droughts in the region. For WY2009, the STAs received about 20 to 30 percent less inflow  
356 volume compared to the Operational Envelope long-term average annual volumes (**Table 5-2**).  
357 For TP loads, STA-1E, STA-2, and STA-3/4 received less than the long-term average annual  
358 Operational Envelope TP loads, while STA-1W, STA-5, and STA-6 received more than the  
359 long-term average annual Operational Envelope TP loads. All six of the STAs loadings were  
360 below the maximum Operational Envelope TP loads. *[Note: The STA-6 flow data is currently  
361 under review. The final chapter will be revised to include the updated flow data for all inflow and  
362 outflow structures, as well as the load estimates. The revisions will affect both WY2008 and  
363 WY2009 performance estimates for STA-6 and the overall POR estimates for all the STAs.]*

364 All the STAs demonstrated a reduction in outflow TP concentrations as compared to inflows.  
365 Inflow TP FWMC ranged from 96 ppb for STA-3/4 up to 264 ppb for STA-6. Outflow TP  
366 FWMC were below 25 ppb for STA-1E, STA-2, and STA-3/4 (21 ppb, 18 ppb, and 13 ppb  
367 respectively); slightly higher for STA-1W and STA-6 (26 ppb and 56 ppb, respectively); and  
368 highest for STA-6 (93 ppb).

369 STA-3/4 and STA-6 had some apparent negative flow events. The negative flows at STA-3/4  
370 occurred at the outflow structures, indicating reverse flow from the discharge canal into the  
371 treatment cell. Because the flows went into the STA, these negative flows are not a permit-related  
372 issue. The apparent negative flows at the STA-6 inflow structures are currently under  
373 investigation and the Florida Department of Environmental Protection (FDEP) has been notified  
374 via the monthly Discharge Monitoring Reports.

375

376

### 377 **Permit Compliance for Phosphorus**

378 In WY2009, STA-1E, STA-2, and STA-3/4 outflows met the permit TBEL limits, while  
379 STA-1W, STA-5, and STA-6 did not meet their limits (**Table 5-2**). For STA-1W and STA-5,  
380 outflow TP FWMC was 4 ppb above the TBEL limit and, for STA-6, the outflow was about 71  
381 ppb above the TBEL limit. Although the STA-6 flow data is still under review, it appears that this  
382 STA received inflow loads nearly at the annual maximum Operational Envelope TP load. All the  
383 STAs received large TP loads in August 2008 due to Tropical Storm Fay (see the *Tropical Storm*  
384 *Fay Impacts on the STAs* section of this chapter for additional details). In August 2008, STA-1W  
385 received 29 mt of TP, which is over half of the anticipated average annual TP load. Under the  
386 permit, it is recognized that STA-1W may receive flows and TP loads higher than anticipated  
387 until regional improvements are completed. At STA-5, Cell 1A was taken off-line in December  
388 2008 for rehabilitation activities which temporarily decreased the amount of effective treatment  
389 area in the STA (see the *STA-5 Performance Analysis and Rehabilitation* section of this chapter).

390 With the completion of STA-6 Section 2 and the modifications to the STA-6 Section 1 inflow  
391 structures, STA-6 began accepting runoff from the C-139 basin, a new inflow source for this  
392 STA. C-139 basin runoff has had higher TP concentrations compared to the runoff that previously  
393 was treated by STA-6; therefore, this appears to be a reason for the increase in TP loading. Both  
394 STA-5 and STA-6 had treatment cells that were dry in WY2009 because of the drought  
395 conditions (see the *Drought Impacts on the STAs* section of this chapter for more details).  
396 According to the STA permits issued in 2007 and 2009 for all the STAs (except for STA-3/4,  
397 which is still operating under the 2004 permit), the STAs are considered to be in the Stabilization  
398 Phase (**Table 5-3**) and the permits recognize that the TBEL may not be met during this phase.

### 399 **Other Water Quality Parameters**

400 Water quality parameters with Florida Class III standards are identified in **Table 5-5**.  
401 Compliance with the EFA permit is determined based on the following three-part assessment:

- 402 1. If the annual average outflow concentration does not cause or contribute to violations of  
403 applicable Class III water quality standards, then the STA shall be deemed in compliance.
- 404 2. If the annual average concentration at the outflow causes or contributes to violations of  
405 applicable Class III water quality standards, but does not exceed or is equal to the annual  
406 average concentration at the inflow stations, then the STA shall be deemed in compliance.
- 407 3. If the annual average concentration at the outflow causes or contributes to violations of  
408 applicable Class III water quality standards and also exceeds the annual average  
409 concentration at the inflow station, then the STA shall be deemed out of compliance.

410 The determination as to whether or not an STA is contributing to a violation for a specific  
411 parameter is a comparison of the average annual inflow concentration to the average annual  
412 outflow concentration relative to the three-part assessment. The District has performed all  
413 sampling and analysis in compliance with Chapter 62-160, Florida Administrative Code (F.A.C.),  
414 and the District's Laboratory Quality Manual (SFWMD, 2009b) and Field Sampling Quality  
415 Manual (SFWMD, 2009c). The Annual Permit Compliance Monitoring Report for Mercury in the  
416 STAs is located in Appendix 5-6. Each STA has different permit reporting requirements for  
417 annual water quality constituents. The required parameters are shown in **Table 5-6**. For WY2009,  
418 the ECP STAs are in compliance with all requirements of the EFA and NPDES operating permits.

419



**Table 5-5.** Water quality parameters with Florida Class III criteria specified in Section 62-302.530, Florida Administrative Code. Because the STAs are freshwater systems, background concentration for specific conductivity is assumed to be less than 1,275 micromhos per centimeter ( $\mu\text{mhos/cm}$ ), and background concentration for turbidity cannot exceed 29 nephelometric turbidity units (NTUs).

Parameter	Units	Class III Criteria
Dissolved Oxygen <sup>a</sup>	mg/L	Greater than (>) or equal to (=) 5.0 mg/L
Conductivity	$\mu\text{mhos/cm}$	Not > 50 percent of background or > 1,275 $\mu\text{mhos/cm}$ , whichever is greater
pH	SU	Not less than (<) 6.0 or > 8.5
Turbidity	NTU	< or = 29 NTU above background conditions
Unionized Ammonia	mg/L	< or = 0.02 mg/L
Alkalinity	mg $\text{CaCO}_3/\text{L}$	Not < 20 mg/L

<sup>a</sup> Permits for all STAs, except STA-3/4, require compliance with the Site-Specific Alternative Criteria (SSAC) for dissolved oxygen (Weaver, 2004).

mg/L – milligrams per liter

$\mu\text{mhos/cm}$  – micromhos per centimeter

SU – standard units

NTU – nephelometric turbidity unit

$\text{CaCO}_3$  – calcium carbonate

421

**Table 5-6.** Summary of annual flow-weighted mean concentrations (FWMC) for parameters other than total phosphorus (TP) at inflow and outflow of STAs to the Everglades Protection Area (EPA) during WY2009. Excursions occurred when FWMC at outflows are greater than those at inflows. There were no excursions in WY2009.

Stormwater Treatment Area	Data Classification	Flow-Weighted Mean Concentrations							
		Alkalinity (mg CaCO <sub>3</sub> /L)	Chloride (mg/L)	Sulfate (mg/L)	Un-ionized Ammonia (mg NH <sub>3</sub> /L)	Nitrate+Nitrite (mg N/L)	Total Dissolved Nitrogen (mg/L)	Total Nitrogen (mg/L)	Total Dissolved Phosphorus (mg/L)
STA-1E	Inflow	174	----	42.5	----	1.296	----	3.26	----
	Outflow	139	----	29.4	----	0.068	----	1.25	----
	Excursions	No	----	No	----	No	----	No	----
STA-1W	Inflow	275	----	81.0	----	0.596	----	3.67	----
	Outflow	201	----	61.6	----	0.044	----	2.19	----
	Excursions	No	----	No	----	No	----	No	----
STA-2	Inflow	333	----	77.5	----	0.605	----	3.40	----
	Outflow	265	----	58.3	----	0.137	----	2.32	----
	Excursions	No	----	No	----	No	----	No	----
STA-3/4	Inflow	263	88	61.5	0.004	1.931	4.22	4.41	0.069
	Outflow	207	87	49.3	0.001	0.009	1.78	1.81	0.007
	Excursions	No	No	No	No	No	No	No	No
STA-5	Inflow	----	----	6.1	----	0.037	----	1.74	----
	Outflow	----	----	4.7	----	0.009	----	1.36	----
	Excursions	----	----	No	----	No	----	No	----
STA-6	Inflow	143	----	8.6	----	0.096	----	1.67	----
	Outflow	140	----	3.7	----	0.011	----	1.31	----
	Excursions	No	----	No	----	No	----	No	----

## 422 **Water Year 2009 Performance for Water Quality Parameters** 423 **Other Than Phosphorus**

424 Water quality parameters with Florida Class III standards applicable to the STAs are provided  
425 in **Table 5-5**. Compliance with EFA permits is determined based on the three-part assessment  
426 presented in the *Water Quality Permit Requirements* section of this chapter. The description of  
427 background for specific conductance criteria is described as follows: For conductivity, the value  
428 “shall not be increased more than 50 percent above background or to 1,275, whichever is  
429 greater”. Because the standards are for fresh water, background conductivities are typically lower  
430 than 1,275 microsiemens per centimeter ( $\mu\text{S}/\text{cm}$ ). The description of background for turbidity is  
431 described as follows: “For turbidity, the measured value shall be “< 29 above natural background  
432 conditions.” Under Chapter 62-303, F.A.C., natural background is defined as “...the condition of  
433 waters in the absence of man-induced alterations based on the best scientific information  
434 available to the Department. The establishment of natural background for an altered water body  
435 may be based upon a similar unaltered water body or on historical pre-alteration data.” Since the  
436 Florida Department of Environmental Protection (FDEP) has not compiled any information on  
437 what it considers natural background, the District determines that any measured value that is  
438 greater than 29 nephelometric turbidity units (NTUs) is considered to exceed the turbidity  
439 criterion. For the other water quality parameters that do not have Class III standard, excursions  
440 are noted when the outflow FWMCs are higher than the inflow. An STA may have excursions  
441 and still be considered to be in compliance with the permit.

442 WY2009 monitoring data for permitted water quality parameters at the STA inflows and  
443 outflows are presented in Appendix 5-5. Annual FWMC at inflows and outflows of the STAs,  
444 including excursion analysis, is summarized in **Table 5-6**. In addition, the annual permit  
445 compliance monitoring report for mercury in the STAs is included as Appendix 5-4.

446 Pursuant to EFA permits for each of the STAs (except STA-3/4), dissolved oxygen  
447 compliance shall be evaluated annually using a statistical analysis to compare DO levels within  
448 facility as set forth in the Everglades Marsh Dissolved Oxygen Site-Specific Alternative Criteria  
449 (DO SSAC). Additional details regarding compliance with the DO SSAC is presented in the  
450 *Dissolved Oxygen* section.

451 Based on water quality data (excluding TP and DO) collected during WY2009 at inflows and  
452 outflow to the STAs, all of the annual mean FWMCs measured at outflows of a specific STA did  
453 not exceed the Class III criteria and were lower than annual mean FWMC at the inflows to that  
454 STA (**Tables 5-5** and **5-6**). Therefore, all STAs were within permit compliance requirements for  
455 parameters other than phosphorus.

456 As part of the performance evaluation specified by permit for each STA, a statistical  
457 comparison of inflow and outflow FWMC is required to be reported at a significance level ( $\alpha$ ) of  
458 0.05. The test (i.e., Student’s t-test) specified in the permits to statistically compare the parameter  
459 concentrations may not be the most appropriate based on distributional assumptions of the data.  
460 When datasets to be compared are not significantly different from a normal distribution, then the  
461 Student’s t-test can be applied. However, when data are significantly different from normality, the  
462 Student’s t-test is not appropriate and can result in incorrect significance. For the purpose of this  
463 report, distribution of the datasets was determined using the Shapiro-Wilks test of normality at  
464  $\alpha = 0.05$ . Those datasets exhibiting probability values (p-values) greater than 0.05 do not deviate  
465 significantly from a normal distribution and could be tested using the Student’s t-test. However,  
466 datasets with distributions deviating significantly from normality (p-value < 0.05), will be tested  
467 using the Mann-Whitney U test (a non-parametric equivalent of the Student’s t-test).

468 During WY2009, inflow and outflow datasets for the six STAs exhibited deviations from  
469 normal distributions. **Table 5-7** summarizes these statistical comparisons for parameter FWMC at

470 STA inflows and outflow. Of the 33 datasets evaluated, nine comparisons exhibited statistically  
 471 higher concentrations at the inflows than outflows.

472

**Table 5-7.** Statistical comparison flow-weighted mean concentrations at inflows and outflows of STAs that discharge to the EPA during WY2009. Highlighted probability values (p-values) indicate a statistically significant difference between inflows and outflows for a parameter.

Parameter Name	Variable	Storm Water Treatment Areas					
		STA-1E	STA-1W	STA-2	STA-3/4	STA-5	STA-6
Specific Conductivity	P-Value <sup>a</sup>	0.750	0.440	0.460	0.720	0.850	0.160
	Structure <sup>b</sup>	Inflow	Inflow	Inflow	Inflow	Inflow	Inflow
	Statistical Test <sup>c</sup>	Mann-Whitney	Mann-Whitney	Mann-Whitney	Mann-Whitney	Mann-Whitney	Mann-Whitney
Turbidity	P-Value <sup>a</sup>	NA	NA	NA	<b>&lt;0.01</b>	NA	NA
	Structure <sup>b</sup>	NA	NA	NA	<b>Inflow</b>	NA	NA
	Statistical Test <sup>c</sup>	NA	NA	NA	<b>Mann-Whitney</b>	NA	NA
Dissolved Chloride	P-Value <sup>a</sup>	NA	NA	NA	0.890	NA	NA
	Structure <sup>b</sup>	NA	NA	NA	Inflow	NA	NA
	Statistical Test <sup>c</sup>	NA	NA	NA	Mann-Whitney	NA	NA
Alkalinity	P-Value <sup>a</sup>	0.310	0.710	0.240	0.060	0.600	<b>0.030</b>
	Structure <sup>b</sup>	Inflow	Outflow	Inflow	Inflow	Inflow	<b>Inflow</b>
	Statistical Test <sup>c</sup>	Mann-Whitney	Mann-Whitney	Mann-Whitney	Mann-Whitney	Mann-Whitney	<b>Mann-Whitney</b>
Sulfate	P-Value <sup>a</sup>	0.430	0.100	0.600	0.150	0.070	<b>0.020</b>
	Structure <sup>b</sup>	Outflow	Inflow	Outflow	Inflow	Inflow	<b>Inflow</b>
	Statistical Test <sup>c</sup>	Mann-Whitney	Mann-Whitney	Mann-Whitney	Mann-Whitney	Mann-Whitney	<b>Mann-Whitney</b>
Total Dissolved Phosphorus	P-Value <sup>a</sup>	NA	NA	NA	<b>&lt;0.01</b>	NA	NA
	Structure <sup>b</sup>	NA	NA	NA	<b>Inflow</b>	NA	NA
	Statistical Test <sup>c</sup>	NA	NA	NA	<b>Mann-Whitney</b>	NA	NA
Unionized Ammonia	P-Value <sup>a</sup>	NA	NA	NA	0.200	NA	NA
	Structure <sup>b</sup>	NA	NA	NA	Inflow	NA	NA
	Statistical Test <sup>c</sup>	NA	NA	NA	Mann-Whitney	NA	NA
Nitrate + Nitrite	P-Value <sup>a</sup>	0.270	<b>&lt;0.01</b>	<b>&lt;0.01</b>	<b>&lt;0.01</b>	<b>&lt;0.01</b>	0.060
	Structure <sup>b</sup>	Inflow	<b>Inflow</b>	<b>Inflow</b>	<b>Inflow</b>	<b>Inflow</b>	Inflow
	Statistical Test <sup>c</sup>	Mann-Whitney	<b>Mann-Whitney</b>	<b>Mann-Whitney</b>	<b>Mann-Whitney</b>	<b>Mann-Whitney</b>	Mann-Whitney
Total Dissolved Nitrogen	P-Value <sup>a</sup>	NA	NA	NA	0.090	NA	NA
	Structure <sup>b</sup>	NA	NA	NA	Inflow	NA	NA
	Statistical Test <sup>c</sup>	NA	NA	NA	Mann-Whitney	NA	NA
Total Nitrogen	P-Value <sup>a</sup>	0.220	0.430	0.190	0.090	<b>&lt;0.01</b>	0.170
	Structure <sup>b</sup>	Inflow	Inflow	Inflow	Inflow	<b>Inflow</b>	Inflow
	Statistical Test <sup>c</sup>	Mann-Whitney	Mann-Whitney	Mann-Whitney	Mann-Whitney	<b>Mann-Whitney</b>	Mann-Whitney

Notes:

NA - indicates that data was not collected or there were insufficient data to perform the statistical analyses.

<sup>a</sup> Probability level (p-value) computed using appropriate comparison test. A significance level ( $\alpha$ ) of 0.05 was used. When p-value was less than 0.05, the parameter concentrations were significantly different between the inflow and outflow. Significant p-values are identified by shading and are presented in the table as italicized and bolded values.

<sup>b</sup> STA structure(s) exhibiting higher parameter concentrations during the water year.

<sup>c</sup> Statistical test used to compare inflow and outflow water quality data. Choice of test was based on distributional assumptions. If the distribution of the data did not significantly deviate from normality, the Student t-test was used. When the distribution of the data did deviate significantly from normality, the Mann-Whitney test (non-parametric equivalent) was used.

## 473 Dissolved Oxygen

474 Dissolved oxygen (DO) concentrations below 5.0 milligrams per liter (mg/L) occur  
475 commonly throughout the EPA, including interior marsh sites minimally impacted by nutrient  
476 enrichment or cattail invasion. Frequent DO levels below 5.0 mg/L are typical in macrophytic  
477 dominated wetlands where marsh processes of photosynthesis and respiration result in wide diel  
478 cycle swings in DO levels. Since low DO concentrations often measured in the EPA represent  
479 natural variability in this type of ecosystem, the FDEP, pursuant to Chapter 62-302.800(1),  
480 F.A.C., has promulgated a Site-Specific Alternative Criterion (SSAC) for DO in the Everglades.  
481 This SSAC addresses the wide-ranging natural daily (diel) fluctuations that influence natural  
482 background DO levels. In the *2008 South Florida Environmental Report (SFER) – Volume I*,  
483 Chapter 3A explains the SSAC and its development and application in assessing DO excursions  
484 (Weaver, 2008). The specific methods for determining compliance are set forth in the DO  
485 SSAC (Weaver, 2004), which was adopted by Secretarial Order on January 26, 2004, and  
486 approved by the U.S. Environmental Protection Agency (USEPA) as a revision to the state of  
487 Florida's water quality standards on June 16, 2004.

488 Previous reports (Jorge et al, 2002; Goforth et al., 2003; Goforth et al., 2004; Goforth et al.,  
489 2005; Pietro et al., 2006; Pietro et al., 2007) provide monitoring results, comparisons and  
490 evaluations with regard to diel DO for the STAs. These reports were used to assess the impact of  
491 STA discharges on the downstream Everglades ecological system or downstream water quality  
492 with respect to DO and pursuant to the STA-1E, STA-1W, STA-2, STA-3/4, and STA-5 EFA  
493 permits and associated AOs. This also provided data to the FDEP for developing the DO SSAC.

494 In the 2008 SFER – Volume I, Chapter 5, DO levels measured at outflow stations from the  
495 five STAs (STA-1E, STA-1W, STA-2, STA-3/4, and STA-5) were assessed using the developed  
496 SSAC rather than diel DO evaluation as performed in previous reports. This change was agreed to  
497 by the FDEP and the District. Since the STA-6 permit did not have diel requirements, no SSAC  
498 comparison was performed for this STA for WY2007.

499 The SSAC is presently included in EFA permits and associated AOs of five STAs (STA-1E,  
500 STA-1W, STA-2, STA-5, and STA-6) as permit compliance criterion. The SSAC is also expected  
501 to be included in future STA permits for STA-3/4. The NPDES permit issued on January 9, 2004,  
502 for this STA stipulates that it shall be revised in the event the state of Florida establishes a DO  
503 SSAC in the EPA. A map showing the permitted outflow points for each STA is provided in  
504 Figure 5-2.

505 Permits issued for the six STAs require that the District provides the FDEP with an annual  
506 report consisting of an analysis demonstrating that DO levels in STA discharges do not adversely  
507 change the downstream Everglades ecology or the downstream water quality. Since the SSAC has  
508 been adopted by the FDEP and formally approved by the USEPA, assessment on possible  
509 downstream impacts by the outflows from STAs during WY2009 were performed by applying  
510 the SSAC limit with respect to DO at the outflow stations.

511 Biweekly DO concentrations measured at STA discharge stations during WY2009 were used  
512 to summarize annual DO levels (Appendix 5-5). A summary of these annual DO levels for  
513 permitted outflows at each STA and calculated SSAC DO limits are provided in **Table 5-8**. By  
514 comparing the measured mean annual DO for an outflow station with the calculated mean annual  
515 SSAC limit, a determination can be made if the station complies with the permitted limit. When  
516 mean annual DO concentrations measured at the effluent compliance points (outflow stations) are  
517 greater than the calculated mean annual lower limit utilizing the SSAC equation, then the outflow  
518 values are above the SSAC limit or comply with the permitted limit. During WY2009, one  
519 outflow station at STA-1W (G-251), two new outflow stations at STA-5 (G-344E and G-344F),  
520 and two outflow stations at STA-6 (G-354C and G-393B) had mean annual DO levels that were

521 lower than the SSAC limit (**Table 5-8**). These deviations from the SSAC limit probably resulted  
522 from a combination of low-flow conditions at these discharge locations and drought conditions  
523 during part of WY2009.

524 More than 96 percent of the total flow from STA-1W was directed through G-310 during  
525 WY2009 with less than four percent of the total flow being released at G-251. The low flow at  
526 G-251 contributed to the mean annual DO level being 1.2 mg/L due to more frequent periods of  
527 stagnation. The combined flow at the two new outflow structures from STA-5 (G-344E and  
528 G-344F) accounted for less than three percent of the total outflow from this STA. Mean annual  
529 DO levels at both structures were less than 0.5 mg/L below the SSAC limit (**Table 5-8**). During  
530 WY2009, STA-6 had three outflow structures in operation. Two of the structures (G-354C and G-  
531 393B) had a combined flow that was less 17 percent of the total flow from the STA. In addition,  
532 both outflow stations had mean annual DO levels that deviated approximately 2.0 mg/L from the  
533 SSAC limit. In all cases, outflow structures that had limited flow during WY2009 did not meet  
534 the SSAC limit for DO.

535 In addition to determining STA performance to the SSAC for WY2009, a comparison of STA  
536 performance with the SSAC for the past three years was performed. **Figure 5-5** presents the mean  
537 annual residual DO levels for STA outflow for WY2007–WY2009. When mean annual DO levels  
538 are greater than the SSAC, the mean annual residuals (difference between mean annual DO levels  
539 and SSAC limit) are positive (or greater than zero). All outflow stations at STA-3/4 had positive  
540 residuals with four structures (G-376B, G-379B, G-379C, and G-381E) exhibiting continued  
541 improvement in DO (**Figure 5-5**). Only G-344C in STA-5 exhibited a three-year improvement in  
542 DO levels.

543

544

545

546

**Table 5-8.** Summary of annual dissolved oxygen (DO) levels at outflow stations for each STA and their comparison with Site-Specific Alternative Criteria (SSAC) in WY2009.

STA	Outflow Station	No. of Samples	Mean <sup>a</sup>	Standard Deviation	Minimum	Maximum	Mean Annual SSAC Limit <sup>b</sup>	SSAC Limit Classification <sup>c</sup>
STA-1E	S362	53	5.93	1.82	2.47	8.81	4.14	Above
STA-1W	<b>G251</b>	<b>53</b>	<b>1.99</b>	<b>1.31</b>	<b>0.16</b>	<b>6.97</b>	<b>3.19</b>	<b>Below</b>
	G310	53	4.51	1.58	1.07	7.76	2.96	Above
STA-2	G335	52	5.70	1.42	2.55	9.18	4.21	Above
STA-3/4	G376B	52	4.64	1.67	1.46	7.78	3.07	Above
	G376E	52	4.14	2.09	0.88	9.60	3.14	Above
	G379B	52	4.49	2.19	1.81	10.10	3.35	Above
	G379D	52	3.87	1.85	0.57	8.76	3.62	Above
	G381B	52	4.90	1.88	1.21	10.40	3.73	Above
	G381E	52	5.81	2.14	0.37	10.60	4.05	Above
STA-5	G344A	53	4.26	2.32	0.31	9.69	3.37	Above
	G344B	53	4.39	2.10	0.95	8.71	3.59	Above
	G344C	53	5.02	2.05	1.48	9.78	3.63	Above
	G344D	53	5.44	2.33	1.48	10.20	3.80	Above
	<b>G344E</b>	<b>25</b>	<b>3.26</b>	<b>1.30</b>	<b>1.25</b>	<b>5.11</b>	<b>3.69</b>	<b>Below</b>
	<b>G344F</b>	<b>25</b>	<b>3.40</b>	<b>1.45</b>	<b>0.85</b>	<b>5.89</b>	<b>3.86</b>	<b>Below</b>
STA-6	G352B	37	3.93	2.02	0.25	7.27	3.76	Above
	<b>G354C</b>	<b>32</b>	<b>1.71</b>	<b>1.20</b>	<b>0.18</b>	<b>5.19</b>	<b>3.71</b>	<b>Below</b>
	<b>G393B</b>	<b>32</b>	<b>1.72</b>	<b>1.23</b>	<b>0.29</b>	<b>5.44</b>	<b>3.55</b>	<b>Below</b>

Note: <sup>a</sup> Arithmetic mean


<sup>b</sup> SSAC limit derived using the equation derived by Weaver (2004) which calculates the limit using water temperature and time of day data recorded at each monitoring location during each monitoring event.

<sup>c</sup> SSAC limit indicates whether the mean annual DO level measured at an outflow station was above or below the SSAC limit. To be above the SSAC limit, mean annual DO must be equal to or greater than the mean annual SSAC limit.

STA-1E and STA-1W EFA Permit No. 0279499-001-EM; STA-2 EFA Permit No. 0126704-005-EM; STA-3/4 EFA Permit No. 0192895 and NPDES Permit No. FL0300195; STA-5 EFA Permit No. 0131842-006-GL; and STA-6 EFA Permit No. 0236905-001 (PATS No. 262918309)

547

548



**Figure 5-5.** The mean annual residual DO plots at STA outflow stations for WY2007, WY2008, and WY2009. Mean annual residuals were computed as the difference between the mean annual DO and mean annual SSAC. Negative residuals indicate that an outflow station was below the SSAC limit, while positive residuals indicate that an outflow station was above the SSAC limit.



## 550 Mercury

551 In WY2009, there were no violations of the Florida Class III numerical water quality standard  
552 of 12 nanograms of total mercury per liter (THg/L) during the reporting year at any STAs.  
553 Currently, surface water samples are collected in STA-1E, STA-2, STA-5, and STA-6 for THg  
554 and methylmercury (MeHg) analysis. Surface water mercury monitoring within STA-3/4 and  
555 STA-1W has been terminated in accordance with guidelines listed the mercury monitoring  
556 protocol. During WY2009, average annual outflow loading of THg and MeHg from STA-1E  
557 were lower than inflow. For STA-2, outflow loading of MeHg was lower than inflow; however,  
558 outflow loading of THg was greater than inflow. Higher outflow loading for THg in STA-2 is  
559 likely related to the start-up of Cell 4 in 2008. Due to a large number of surface water THg and  
560 MeHg quality assurance/quality control failures during WY2009, loadings estimates could not be  
561 calculated for STA-5 and STA-6.

562 For calendar year 2008, mercury concentrations in mosquitofish (*Gambusia holbrooki*) from  
563 all interior STA locations showed an average 48 percent increase since 2007. The only STA that  
564 showed a decrease was STA-1E. Sunfish (*Lepomis* spp.) showed an average 10 percent reduction  
565 across all STAs and largemouth bass (*Micropterus salmoides*) (age and length-standardized)  
566 showed a 63 percent reduction. [Note that the reduction in largemouth bass only relies on data  
567 from two STAs due to age standardization restrictions.] The large increase in mosquitofish  
568 mercury concentrations for 2008 was highly influenced by increases within STA-5, STA-6, and  
569 STA-2 from the start-up of Flow-way 3, Section 2 and Cell 4. A common occurrence during and  
570 after cell/operating unit start-up is a temporary increase in fish-related mercury concentrations  
571 particularly for low trophic levels fish species, in this case, mosquitofish. However, even with  
572 these increases, there was no exceedance of any action criterion listed in the mercury monitoring  
573 protocol related to fish mercury monitoring.

574 Based on the U.S. Fish and Wildlife Service (USFWS) and U.S. Environmental Protection  
575 Agency (USEPA) predator protection criteria, fish-eating wildlife foraging within all STAs  
576 appear to be at an overall moderate risk to mercury exposure. STA mercury performance criteria  
577 are evaluated on an annual basis. If respective actions levels are exceeded, then corrective  
578 measures are taken in accordance with the FDEP-approved monitoring plans. Additional  
579 information on fish mercury concentrations, including spatial and temporal trends within and  
580 downstream of each STA, is presented in Appendix 5-6.

## 581 **HYDROPATTERN RESTORATION AND STA DISCHARGE** 582 **MONITORING ON THE DOWNSTREAM AREAS**

583 This section presents results from the research and monitoring conducted in the areas  
584 downstream of the STAs including the Arthur R. Marshall Loxahatchee National Wildlife Refuge  
585 (WCA-1), Water Conservation Area 2 (WCA-2A), and the Rotenberger Wildlife Management  
586 Area (RWMA). Part of the EFA permit requirements for STA-1W, STA-1E, STA-2, and STA-5  
587 is characterizing the effects of STA discharges on adjacent marsh areas. This characterization is  
588 based on monthly samples collected for specific conductance (conductivity) and TP. Water  
589 quality monitoring stations in the marsh areas have been chosen along a transect from the  
590 discharge points and are categorized as “impacted” or “unimpacted” based on sediment TP levels.  
591 Those transect stations in areas where sediment TP levels are greater than 500 milligrams per  
592 kilogram (mg/kg) are identified as impacted. Monitoring data for each transect are provided in  
593 Appendix 5-9. A summary of conductivity and TP collected for these transects is provided in  
594 **Tables 5-9** and **5-10**, respectively. These water quality data are also graphically presented as  
595 notched box-and-whisker plots along with the results of the monitoring conducted as part of the  
596 hydropattern restoration monitoring, which includes vegetation, water level, and soil monitoring.

597

598 **Arthur R. Marshall Loxahatchee National Wildlife Refuge**

599 Discharges from STA-1W and STA-1E are released into the rim canal surrounding the Arthur  
 600 R. Marshall Loxahatchee National Wildlife Refuge. These discharges enter the rim canal from the  
 601 northwestern (STA-1W) and northeastern (STA-1E) quadrats of the Refuge. Marsh transects  
 602 downstream from both discharges extend approximately 4 kilometers (km) into the Refuge  
 603 (Figure 5-6). Impacted stations extend approximately 2 km (downstream of STA-1W) and 1 km  
 604 (downstream of STA-1E) into the marsh (Tables 5-9 and 5-10). A total of 12 stations are  
 605 monitored in the Refuge, with seven stations along the western transect and five stations along the  
 606 eastern transect. One station from each transect is monitored in the rim canal.

607 Transects in the Refuge exhibited a substantial decrease in both conductivity and TP  
 608 concentrations within 1 km from the rim canal (Figure 5-7). TP concentrations measured in the  
 609 western transect (downstream of STA-1W outflows) decreased by approximately 19 micrograms  
 610 per liter [(µg/L), or parts per billion (ppb)], and conductivity decreased by approximately 370  
 611 µS/cm within 1 km from the rim canal station. The eastern transect (downstream of the STA-1E  
 612 outflow) exhibited a decrease of approximately 280 µS/cm in conductivity and 20 ppb in TP  
 613 within the first kilometer from the rim canal. Stations on both transects located at a distance  
 614 greater than 1 km from the rim canal had median TP concentrations ranging from 6 to 8 ppb.  
 615 Median conductivity values for these stations ranged from 99 to 274 µS/cm. All conductivity  
 616 levels measured at Refuge transect stations were below the Class III criterion of 1,275 µS/cm. A  
 617 Kruskal-Wallis test was used to determine if TP and conductivity levels between stations along  
 618 both transects were statistically different. Both parameters exhibited a statistically significant  
 619 (p < 0.01) decrease in both TP concentrations and conductivity levels across each transect.

620

621


622 **Table 5-9.** Summary statistics for conductivity (in microsiemens  
 623 per centimeter, or µS/cm) measurements collected during WY2009 at  
 624 transect stations from STA outflows.

STA Transects	Station Information		Distance from Canal (km)	Number of Samples	Mean	Standard Deviation	Minimum	Percentiles			Maximum
	Name	Category <sup>1</sup>						25th	50th (Median)	75th	
STA-1W	LOXA135	Rim Canal	0.0	12	710.2	126.4	512	625	680	810	908
	LOXA136	Impacted	0.6	9	547.8	163.0	206	480	562	679	735
	LOXA137	Impacted	1.1	9	367.0	202.9	104	173	402	492	743
	LOXA138	Impacted	2.1	9	279.0	119.2	114	194	274	375	460
	LOXA139	Impacted	4.0	8	97.7	31.5	43	79	99	127	130
	LOXA104	Unimpacted	0.0	12	652.0	167.5	303	521	716	748	900
	LOXA104.5	Unimpacted	0.4	9	607.7	197.5	306	427	639	783	804
STA-1E	LOXA105	Rim Canal	0.8	9	510.3	229.0	220	332	484	693	866
	LOXA106	Impacted	1.1	9	378.2	189.8	180	239	347	463	792
	LOXA107	Impacted	2.2	8	203.2	134.4	111	126	172	198	524
	LOXA107U	Unimpacted	3.4	8	119.0	25.4	80	98	126	137	152
	LOXA108	Unimpacted	4.1	8	111.0	21.2	75	96	117	126	138
STA-2 Transect 1	N <sub>0.25</sub>	Impacted	0.2	6	1,122.5	75.6	1,018	1,042	1,150	1,170	1,206
	N <sub>1.0</sub>	Impacted	0.9	6	1,081.0	91.2	914	1,054	1,105	1,131	1,177
	N <sub>2.0</sub>	Impacted	1.9	4	1,053.9	88.8	960	979	1,054	1,129	1,147
	N <sub>4.0</sub>	Impacted	3.7	4	1,053.7	105.9	940	967	1,050	1,140	1,174
	C <sub>4.0</sub>	Unimpacted	6.8	4	1,013.8	107.5	869	932	1,044	1,096	1,099
STA-2 Transect 2	FS <sub>0.25</sub>	Impacted	0.4	6	1,111.5	70.0	1,040	1,059	1,091	1,186	1,203
	FS <sub>1.0</sub>	Impacted	1.0	5	1,063.6	56.6	1,023	1,025	1,053	1,082	1,161
	FS <sub>3.0</sub>	Impacted	3.1	6	1,037.2	139.2	817	960	1,065	1,143	1,173
	CA29	Unimpacted	5.6	15	898.7	153.3	621	768	890	1,009	1,181
STA-5	RC1	Impacted	0.2	11	606.8	198.6	290	503	583	715	1,009
	RC2	Impacted	2.3	9	500.3	179.9	186	396	527	660	724
	RC3	Impacted	4.2	8	467.0	206.4	142	315	473	655	709

625  
626  
627**Table 5-10.** Summary statistics for TP (in micrograms per liter, or  $\mu\text{g/L}$ ) measurements collected during WY2009 at transect stations from STA outflows.

STA Transects	Station Information		Distance from Canal (km)	Number of Samples	Mean	Standard Deviation	Minimum	Percentiles			Maximum
	Name	Category <sup>1</sup>						25th	50th (Median)	75th	
STA-1W	LOXA104	Rim Canal	0.0	12	32.2	12.7	20	24	27	40	55
	LOXA104.5	Impacted	0.4	9	39.0	54.0	15	17	22	26	182
	LOXA105	Impacted	0.8	9	12.4	5.7	6	9	12	15	25
	LOXA106	Impacted	1.1	9	9.9	5.5	6	7	8	10	24
	LOXA107	Impacted	2.2	8	7.1	1.7	5	6	8	8	10
	LOXA107U	Unimpacted	3.4	8	6.3	1.4	4	6	6	8	8
	LOXA108	Unimpacted	4.1	8	9.6	2.8	6	8	9	12	14
STA-1E	LOXA135	Rim Canal	0.0	12	35.5	19.3	13	21	29	48	77
	LOXA136	Impacted	0.6	9	21.1	21.5	9	10	14	20	77
	LOXA137	Impacted	1.1	9	12.0	10.8	5	7	9	11	40
	LOXA138	Unimpacted	2.1	9	7.0	2.4	5	6	6	7	13
	LOXA139	Unimpacted	4.0	8	7.0	1.9	5	6	6	8	11
STA-2 (Transect 1)	N <sub>0.25</sub>	Impacted	0.2	7	23.6	12.0	7	17	17	35	39
	N <sub>1.0</sub>	Impacted	0.9	7	15.4	7.5	6	11	15	18	30
	N <sub>2.0</sub>	Impacted	1.9	5	10.2	3.3	6	8	10	12	15
	N <sub>4.0</sub>	Impacted	3.7	5	6.8	1.5	5	6	7	8	9
	C <sub>4.0</sub>	Unimpacted	6.8	5	4.8	1.3	3	4	5	6	6
STA-2 (Transect 2)	FS <sub>0.25</sub>	Impacted	0.4	7	17.6	5.0	7	17	20	21	21
	FS <sub>1.0</sub>	Impacted	1.0	6	13.8	2.6	10	13	14	15	18
	FS <sub>3.0</sub>	Impacted	3.1	7	7.4	2.6	4	5	8	10	11
	CA29	Unimpacted	5.6	16	4.9	1.1	3	4	5	6	7
STA-5	RC1	Impacted	0.2	11	26.0	9.0	13	18	28	30	44
	RC2	Impacted	2.3	9	11.9	3.1	7	10	12	14	17
	RC3	Impacted	4.2	8	14.3	6.7	8	9	13	19	26


<sup>1</sup>Categories of "impacted" and "unimpacted" refer to station identification based on sediment phosphorus concentrations. Impacted stations have sediment phosphorus levels greater than 500 mg/kg.



628  
 629  
 630  
 631

**Figure 5-6.** Locations of marsh transect stations in the Arthur R. Marshall Loxahatchee National Wildlife Refuge (Refuge) and outflow structures from STA-1W and STA-1E.

632  
 633  
 634  
 635  
 636  
 637  
 638  
 639  
 640  
 641  
 642  
 643  
 644  
 645  
 646  
 647  
 648  
 649  
 650  
 651  
 652  
 653  
 654  
 655  
 656  
 657  
 658  
 659  
 660  
 661



**Figure 5-7.** Notched box and whisker plots of conductivity and total phosphorus levels measured at transect stations during WY2009 for STA-1W and STA-1E. The notch on a box represents the 95% C.I. about the median, which is represented by the narrowest part of the notch. The top and bottom of the box represent the 75<sup>th</sup> and 25<sup>th</sup> percentiles, respectively. The whiskers represent the highest and lowest data values that are within two standard deviations of the median. Values above and below the whiskers are greater than two standard deviations from the median. Notches that do not overlap indicate that the data represented by the boxes being compared are significantly different at the 95% C.I.

662

**663 Northwestern Water Conservation Area 2A****664 WCA-2A Monitoring Objectives**

665 In accordance with the EFA, the District has been monitoring the effect of water discharged  
666 from STA-2 into the northwestern region of Water Conservation Area 2A (WCA-2A). These  
667 releases are intended to restore the hydropattern and ecological functionality of the marshes  
668 downstream of STA-2. The STA-2 EFA permit requires that the District implement a monitoring  
669 and assessment program to monitor and evaluate ecological changes associated with STA-2  
670 discharges into the area. The annual report addresses the following issues: (1) what are the  
671 beneficial environmental effects, including changes in water quality, soil, vegetative conditions,  
672 inundation and timing of discharges; and (2) are there any adverse environmental effects,  
673 including imbalances in natural populations of flora or fauna, changes in periphyton communities,  
674 increased P accumulation rates in soil, expansion of cattail (*Typha* spp.) or other undesirable or  
675 exotic vegetation, or other undesirable consequences of the hydropattern restoration.

**676 WCA-2A Configuration**


677 STA-2 primarily discharges into WCA-2A through six culverts (G-336A–F structures)  
678 (Figure 5-8). Additional STA-2 effluent is released through G-336G into the discharge canal  
679 south of STA-2. Approximately 1 km northeast of the S-7 pump station, the levee separating this  
680 discharge canal from WCA-2A is degraded, allowing discharge passing through G-336G to  
681 passively enter WCA-2A. Monitoring transects (N-, C-, and S-transects) were established in 1998  
682 to monitor environmental and ecological changes in the area. In 2005, a new transect  
683 (FS-transect) was established to monitor the additional STA-2 discharge. Monitoring data for the  
684 stations downstream of STA-2 can be located within two District databases, ERDP and  
685 DBHYDRO (Appendix 5-8).

**686 WCA-2A Hydropattern Restoration**

687 Hydropattern improvements resulting from STA-2 discharges are presented in the 2009 SFER  
688 – Volume I, Chapter 5 (Pietro et al., 2009) and Hydropattern Restoration in Water Conservation  
689 Area 2A Report (Garrett and Ivanoff, 2008). To monitor water levels, water depth recorders were  
690 set up at eight stations between 2004 and 2006. The accuracy of these depth recorder  
691 measurements was assessed during 2006 and 2007 by comparing them with periodic water depth  
692 measurements collected manually in the field. These accuracy measurements were reported in the  
693 2009 SFER – Volume I, Chapter 5. Water depths at these stations during WY2009 are presented  
694 in Figure 5-9. Unfortunately, the data record for only four of the eight depth recorders (N<sub>0.25</sub>,  
695 N<sub>4.0</sub>, C<sub>0.25</sub>, and C<sub>1.0</sub>) was uninterrupted due to equipment malfunctions in WY2009. The mean  
696 inundation periods at these four stations ranged from 245 days at N<sub>0.25</sub> to 251 days at N<sub>4.0</sub>. Mean  
697 water depth ranged from 42 cm at N<sub>0.25</sub> to 26 cm at N<sub>4.0</sub>. Due to repairs, the S<sub>1.0</sub> depth recorder  
698 was only active for only 64 days during WY2009. The recorder at the C<sub>4.0</sub> station began to fail  
699 during the last month of WY2009. The FS<sub>0.25</sub> and FS<sub>3.0</sub> depth recorders were also non-operational,  
700 so the inundation period could not be estimated for the southern portion of the monitoring area.  
701 Water depths increased throughout in the entire area during August and early September due to  
702 Tropical Storm Fay.


703 Permanent stage recorders were installed at the N<sub>1.0</sub> (WC2AN1) and S<sub>1.0</sub> (WC2AS1) stations  
704 in WY2009 and both gauges began to record data in June 2009. Future hydropattern restoration  
705 reports in relation to this portion of WCA-2A will be based on measurements from these two  
706 instruments.

707



708  
709  
710

**Figure 5-8.** Location of STA-2 discharge structures, including the G-336A–G discharge culverts in relation to sampling stations along transects in the northwestern section of Water Conservation Area 2A (WCA-2A).



711

712 **Figure 5-9.** Daily mean water depths (cm) obtained from depth recorders  
 713 deployed at eight stations in the northwestern region of WCA-2A during WY2009.  
 714 See **Figure 5-8** for location of these stations.

715

716



717 ***WCA-2A Surface Water Quality***

718 Surface water samples were collected monthly at 17 sites when sufficient water (depth  $\geq 10$   
719 cm) was available for representative sampling. During WY2009, surface water TP gradients  
720 existed along the N-, C-, and FS-transects with stations nearest to the L-6 levee demonstrating  
721 higher P concentrations and those locations downstream demonstrating lower concentrations  
722 (**Table 5-11**). The S-transect displayed near background level concentrations along the entire  
723 transect. Mean TP concentrations were highest at N<sub>0.25</sub> and FS<sub>0.25</sub>, at 24 ppb and 18 ppb,  
724 respectively. The C<sub>4.0</sub>, S<sub>4.0</sub>, and CA29 stations had the lowest mean TP concentration, all at 5 ppb.  
725 Annual mean surface water TP concentrations decreased at 14 stations compared to WY2008  
726 levels. Mean TP concentrations at N<sub>0.25</sub>, C<sub>2.0</sub>, and S<sub>1.0</sub> remained at similar levels as in WY2008.

727 Mean specific conductivity ranged from 899  $\mu\text{S}/\text{cm}$  (CA29) to 1140  $\mu\text{S}/\text{cm}$  (C<sub>0.25</sub>) in  
728 WY2009 (**Table 5-12**). These ranges are comparable to WY2008 values. In general, stations  
729 along the L-6 levee had greater annual mean specific conductivity than those located farther into  
730 the marsh.

731 Mean WY2009 total Kjeldahl nitrogen (TKN) concentrations ranged from 1.88 mg/L (S<sub>4.0</sub>) to  
732 2.19 mg/L (N<sub>0.25</sub>) (**Table 5-13**). Annual mean TKN concentrations were comparable among all  
733 stations, and were similar to mean concentrations observed in WY2008.

734 WY2009 mean sulfate (SO<sub>4</sub>) concentrations were highest at FS<sub>1.0</sub> (62 mg/L), and lowest at  
735 CA29 (39 mg/L) (**Table 5-14**). SO<sub>4</sub> concentrations at all stations except for FS<sub>3.0</sub> increased from  
736 WY2008 to WY2009. However, these concentrations were generally lower than the mean  
737 concentrations observed from 2001 to 2006 (Garrett and Ivanoff, 2008). The exception was at  
738 FS<sub>2.0</sub>, with similar mean SO<sub>4</sub> concentrations during both periods.

739 ***EFA Permit Compliance Transect Total Phosphorus and Conductivity at***  
740 ***STA-2 Downstream Area (WCA-2A)***

741 The EFA permit compliance transects to characterize the effects of STA-2 discharges on the  
742 marsh are located in the western portion of the WCA, with one transect located in the northern  
743 portion and the other in the southern portion of WCA-2A (**Figure 5-8**). The northern transect  
744 comprises five monitoring stations extending approximately 7 km. The southern transect extends  
745 approximately 6 km into WCA-2A and contains four monitoring stations.

746 Conductivity and TP levels changed more gradually at the two transects located in  
747 WCA-2A with median conductivity ranging from 890 to 1150  $\mu\text{S}/\text{cm}$  (**Table 5-9**). Conductivity  
748 levels along the northern transect were not statistically different (p-value  $\sim 0.35$  based on the  
749 Kruskal-Wallis test). However, a statistically significant (p = 0.01) decrease in conductivity levels  
750 was observed for the southern transect. A decrease in median conductivity levels of  
751 approximately 175  $\mu\text{S}/\text{cm}$  occurred between 3 and 6 km from the canal along this transect  
752 (**Figure 5-10**). No conductivity measured along the northern or southern transect exceeded the  
753 Class III criterion of 1,275  $\mu\text{S}/\text{cm}$ . Median TP concentrations were  $\leq 10$  ppb at a distance of more  
754 than 3 km from the canal (**Figure 5-10; Table 5-10**). Both transects exhibited a statistically  
755 significant (p < 0.001) decrease in median TP concentrations.

756

757  
758  
759  
760  
761

**Table 5-11.** Summary statistics for surface water TP concentrations ( $\pm$  standard deviations) measured at WCA-2A transect locations during WY2009. Asterisk (\*) indicates permit compliance location.

Station	Mean TP (ppb)	N	Min	Median	Max
N <sub>0.25</sub> *	24 $\pm$ 12	7	7	17	39
N <sub>1.0</sub> *	15 $\pm$ 8	7	6	15	30
N <sub>2.0</sub> *	10 $\pm$ 3	5	6	10	15
N <sub>4.0</sub> *	7 $\pm$ 2	7	5	7	10
C <sub>0.25</sub>	16 $\pm$ 4	7	11	15	22
C <sub>1.0</sub>	9 $\pm$ 3	6	6	10	14
C <sub>2.0</sub>	9 $\pm$ 3	7	5	8	15
C <sub>4.0</sub> *	5 $\pm$ 1	5	3	5	6
S <sub>0.25</sub>	7 $\pm$ 2	5	4	8	9
S <sub>1.0</sub>	6 $\pm$ 2	5	4	6	8
S <sub>2.0</sub>	6 $\pm$ 1	5	5	6	7
S <sub>4.0</sub>	5 $\pm$ 1	6	3	5	6
FS <sub>0.25</sub> *	18 $\pm$ 5	7	7	20	21
FS <sub>1.0</sub> *	14 $\pm$ 3	6	10	14	18
FS <sub>2.0</sub>	9 $\pm$ 2	7	6	9	13
FS <sub>3.0</sub> *	7 $\pm$ 3	7	4	8	11
CA29*	5 $\pm$ 1	17	3	5	7

762  
763  
764  
765  
766  
767

**Table 5-12.** Summary statistics for surface water specific conductivity ( $\pm$  standard deviations) measured at WCA-2A transect locations during WY2009. Asterisk (\*) indicates permit compliance location.

Station	Mean Sp Cond ( $\mu$ S/cm)	N	Min	Median	Max
N <sub>0.25</sub> *	1123 $\pm$ 76	6	1018	1150	1206
N <sub>1.0</sub> *	1081 $\pm$ 91	6	914	1105	1177
N <sub>2.0</sub> *	1054 $\pm$ 89	4	960	1054	1147
N <sub>4.0</sub> *	1054 $\pm$ 106	4	940	1051	1174
C <sub>0.25</sub>	1140 $\pm$ 64	6	1063	1132	1245
C <sub>1.0</sub>	1093 $\pm$ 78	5	1013	1093	1194
C <sub>2.0</sub>	1122 $\pm$ 147	6	958	1145	1345
C <sub>4.0</sub> *	1014 $\pm$ 108	4	869	1044	1099
S <sub>0.25</sub>	1037 $\pm$ 128	4	845	1094	1114
S <sub>1.0</sub>	1019 $\pm$ 144	4	810	1070	1126
S <sub>2.0</sub>	958 $\pm$ 125	4	798	986	1063
S <sub>4.0</sub>	926 $\pm$ 138	5	747	966	1105
FS <sub>0.25</sub> *	1112 $\pm$ 70	6	1040	1091	1203
FS <sub>1.0</sub> *	1064 $\pm$ 57	5	1023	1053	1161
FS <sub>2.0</sub>	1044 $\pm$ 114	6	858	1038	1181
FS <sub>3.0</sub> *	1037 $\pm$ 139	6	817	1065	1173
CA29*	899 $\pm$ 150	16	621	853	1181

768

769

770

771

772

**Table 5-13.** Summary statistics for surface water total Kjeldahl nitrogen (TKN) concentrations ( $\pm$  standard deviations) measured at WCA-2A transect locations during WY2009. Asterisk (\*) indicates permit compliance location.

Station	Mean TKN (mg/L)	N	Min	Median	Max
N <sub>0.25</sub> *	2.19 $\pm$ 0.13	6	2.04	2.15	2.39
N <sub>1.0</sub> *	2.10 $\pm$ 0.30	6	1.61	2.11	2.55
N <sub>2.0</sub> *	2.10 $\pm$ 0.12	5	2.00	2.08	2.30
N <sub>4.0</sub> *	2.09 $\pm$ 0.16	5	1.85	2.08	2.28
C <sub>0.25</sub>	2.14 $\pm$ 0.12	6	1.96	2.11	2.29
C <sub>1.0</sub>	2.13 $\pm$ 0.13	5	2.01	2.10	2.35
C <sub>2.0</sub>	2.11 $\pm$ 0.17	6	1.95	2.05	2.40
C <sub>4.0</sub> *	2.05 $\pm$ 0.19	5	1.82	2.01	2.33
S <sub>0.25</sub>	2.09 $\pm$ 0.12	5	1.94	2.06	2.25
S <sub>1.0</sub>	2.02 $\pm$ 0.16	5	1.86	1.94	2.27
S <sub>2.0</sub>	1.93 $\pm$ 0.19	5	1.73	1.86	2.20
S <sub>4.0</sub>	1.88 $\pm$ 0.23	5	1.50	1.95	2.12
FS <sub>0.25</sub> *	2.13 $\pm$ 0.09	6	2.03	2.12	2.25
FS <sub>1.0</sub> *	2.11 $\pm$ 0.17	5	1.90	2.08	2.37
FS <sub>2.0</sub>	2.05 $\pm$ 0.11	5	1.88	2.08	2.17
FS <sub>3.0</sub> *	1.99 $\pm$ 0.16	6	1.76	2.04	2.16
CA29*	1.91 $\pm$ 0.26	12	1.56	1.99	2.23

773

774

775

776

777

778

**Table 5-14.** Summary statistics for surface water sulfate (SO<sub>4</sub>) concentrations ( $\pm$  standard deviations) measured at WCA-2A transect locations during WY2009. Asterisk (\*) indicates permit compliance location.

Station	Mean SO <sub>4</sub> (mg/L)	N	Min	Median	Max
N <sub>0.25</sub> *	58 $\pm$ 17	6	29	59	82
N <sub>1.0</sub> *	55 $\pm$ 16	6	28	57	73
N <sub>2.0</sub> *	56 $\pm$ 10	5	47	53	72
N <sub>4.0</sub> *	55 $\pm$ 8	5	46	52	65
C <sub>0.25</sub>	60 $\pm$ 11	6	49	58	79
C <sub>1.0</sub>	57 $\pm$ 9	5	52	53	72
C <sub>2.0</sub>	50 $\pm$ 11	6	33	49	66
C <sub>4.0</sub> *	53 $\pm$ 8	5	43	55	62
S <sub>0.25</sub>	54 $\pm$ 9	5	43	56	65
S <sub>1.0</sub>	52 $\pm$ 9	5	41	54	62
S <sub>2.0</sub>	50 $\pm$ 9	5	42	44	60
S <sub>4.0</sub>	45 $\pm$ 10	5	28	46	53
FS <sub>0.25</sub> *	58 $\pm$ 18	6	30	57	85
FS <sub>1.0</sub> *	62 $\pm$ 10	5	52	60	79
FS <sub>2.0</sub>	56 $\pm$ 11	5	44	54	72
FS <sub>3.0</sub> *	51 $\pm$ 15	6	28	51	67
CA29*	39 $\pm$ 14	12	7	40	63

779

780

781

782

783

784

785

**Table 5-15.** Summary statistics for surface water TP, specific conductivity, TKN, and SO<sub>4</sub> concentrations ( $\pm$  standard deviations) measured at WCA-2A transect locations during WY2008. WY2009 data for these parameters is shown in **Tables 5-11 through 5-14**. Asterisk (\*) indicates permit compliance location.


Station	WY 2008 Mean TP (ppb)	WY 2008 Mean Sp Cond ( $\mu$ S/cm)	WY 2008 Mean TKN (mg/L)	WY 2008 Mean SO <sub>4</sub> (mg/L)
N <sub>0.25</sub> *	23 $\pm$ 6	1131 $\pm$ 126	2.17 $\pm$ 0.26	52 $\pm$ 8
N <sub>1.0</sub> *	19 $\pm$ 5	1098 $\pm$ 146	2.03 $\pm$ 0.31	50 $\pm$ 9
N <sub>2.0</sub> *	15 $\pm$ 5	1004 $\pm$ 247	1.80 $\pm$ 0.37	44 $\pm$ 15
N <sub>4.0</sub> *	8 $\pm$ 3	966 $\pm$ 244	1.75 $\pm$ 0.45	41 $\pm$ 16
C <sub>0.25</sub>	25 $\pm$ 15	1113 $\pm$ 135	2.15 $\pm$ 0.31	51 $\pm$ 9
C <sub>1.0</sub>	11 $\pm$ 2	1024 $\pm$ 189	1.92 $\pm$ 0.35	45 $\pm$ 13
C <sub>2.0</sub>	9 $\pm$ 2	991 $\pm$ 237	1.85 $\pm$ 0.45	42 $\pm$ 15
C <sub>4.0</sub> *	7 $\pm$ 2	917 $\pm$ 262	1.72 $\pm$ 0.48	42 $\pm$ 17
S <sub>0.25</sub>	9 $\pm$ 2	997 $\pm$ 208	1.85 $\pm$ 0.41	45 $\pm$ 12
S <sub>1.0</sub>	6 $\pm$ 1	960 $\pm$ 253	1.73 $\pm$ 0.47	44 $\pm$ 15
S <sub>2.0</sub>	7 $\pm$ 2	837 $\pm$ 264	1.92 $\pm$ 0.55	37 $\pm$ 15
S <sub>4.0</sub>	6 $\pm$ 1	945 $\pm$ 242	1.97 $\pm$ 0.56	37 $\pm$ 23
FS <sub>0.25</sub> *	20 $\pm$ 6	1088 $\pm$ 266	2.05 $\pm$ 0.52	44 $\pm$ 17
FS <sub>1.0</sub> *	19 $\pm$ 9	1066 $\pm$ 272	2.01 $\pm$ 0.52	45 $\pm$ 17
FS <sub>2.0</sub>	12 $\pm$ 4	1114 $\pm$ 254	2.21 $\pm$ 0.64	53 $\pm$ 32
FS <sub>3.0</sub> *	9 $\pm$ 2	1094 $\pm$ 271	2.19 $\pm$ 0.63	57 $\pm$ 56
CA29*	7 $\pm$ 2	1009 $\pm$ 220	2.11 $\pm$ 0.43	29 $\pm$ 11

786

787

788

789



**Figure 5-10.** Notched box and whisker plots of conductivity and total phosphorus levels measured at transect stations during WY2009 for STA-2. The notch on a box plot represents the 95% C.I. about the median, which is represented by the narrowest part of the notch. The top and bottom of the box represent the 75th and 25th percentiles, respectively. The whiskers represent the highest and lowest data values that are within two standard deviations of the median. Values above and below the whiskers are greater than two standard deviations from the median. Notches that do not overlap indicate that the data represented by the boxes being compared are significantly different at the 95% C.I.

790

791 **WCA-2A Soil Chemistry**

792 Soil samples are collected every other year at 19 monitoring sites in northwestern  
793 WCA-2A. Samples were last collected in March 2008; these data were included in the 2009  
794 SFER – Volume I, Chapter 5. The 2008 data showed no notable changes from prior soil  
795 phosphorus concentrations reported (Garrett and Ivanoff, 2008). Soils will be collected again at  
796 the same stations in WY2010.

797 **WCA-2A Periphyton Nutrient Data**

798 Periphyton samples have been collected annually at permit compliance stations since 1998.  
799 The relative abundance of algal species indicative of higher TP surface water concentrations  
800 (> 16 ppb) decreased from 1998 to 2004, while the relative abundance of species indicative of  
801 lower TP surface water concentrations (< 16 ppb) generally increased (**Figure 5-11**). Similar  
802 trends were observed at other monitoring stations throughout the Everglades system during the  
803 same time period (Garrett and Ivanoff, 2008). Therefore, this positive change in terms of  
804 periphyton community indicators cannot be attributed solely to the STA-2 discharge. In WY2009,  
805 periphyton collections were attempted at all permit-compliance stations in October 2008;  
806 however, not every site had sufficient amounts of periphyton for processing and analysis. From  
807 2005 to 2008, the relative abundance of both high and low TP indicator species remained fairly  
808 constant. Water quality concentrations at these locations have changed little during this period.

809 Periphyton tissue TP concentrations are reported for the six permit compliance stations that  
810 had sufficient amounts of periphyton at the time of collection (**Table 5-16**). Metaphyton (floating  
811 periphyton) and epiphyton (periphyton attached to standing macrophytes) were collected  
812 separately. Mean periphyton tissue TP concentrations at the N<sub>0.25</sub> and FS<sub>0.25</sub> stations were  
813 approximately twice that found in periphyton tissues collected farther downstream of each  
814 respective transect.

815 **WCA-2A Macrophyte Nutrient Data and Composition**

816 Where present, cattail and sawgrass (*Cladium jamaicense*) live leaves were sampled at permit  
817 compliance stations semiannually and analyzed for total nitrogen (TN) and TP. In WY2009, this  
818 sampling occurred in October 2008 and April 2009; however, data from the April 2009 collection  
819 were not available in time to include in this report. Using the TP and TN data, mean N:P ratios  
820 were calculated for each station.

821 Koch and Reddy (1992) found nitrogen: phosphorus (N:P) ratios between 3:1 and 20:1 within  
822 sawgrass tissues from eutrophic regions of WCA-2A and between 37:1 and 132:1 in less  
823 impacted regions of WCA-2A. Between 2006 and 2008, sawgrass leaf tissue N:P ratios from the  
824 N<sub>0.25</sub>, N<sub>1.0</sub>, FS<sub>0.25</sub>, and FS<sub>1.0</sub> stations ranged from 15:1 to 27:1 (**Table 5-17**), which indicates that  
825 these areas fall between highly impacted and intermediately impacted zones. Other permit  
826 compliance stations had sawgrass N:P ratios that were representative of less-impacted conditions.


827 Koch and Reddy (1992) reported that N:P ratios in cattail tissues ranged between 12:1 and  
828 1:1 from a eutrophic region of WCA-2A and between 18:1 and 6:1 from a less impacted region of  
829 WCA-2A. Cattail leaf tissue N:P ratios measured at the permit-compliance sites between 2006  
830 and 2008 ranged from 8:1 to 21:1 (**Table 5-18**). These values are indicative of intermediately  
831 impacted conditions.

832 The areal coverage of several dominant macrophyte species has been measured along fixed  
833 transects twice a year (dry season and wet season) since 2005. Using point-intercept survey  
834 methodology, the presence of sawgrass and/or cattail at meter intervals along 10 m transects was  
835 recorded. These surveys were performed at 19 locations; only data from the permit compliance  
836 sites are presented in this report. **Tables 5-19** and **5-20** show the frequency of occurrence of

837 cattail and sawgrass along each transect. There were no observed changes in sawgrass and cattail  
838 coverage at stations  $N_{0.25}$ ,  $N_{2.0}$ ,  $C_{4.0}$ , and  $FS_{3.0}$  over the survey period. These stations were  
839 predominantly sawgrass, except for  $N_{0.25}$ . The  $N_{4.0}$  station experienced a fire in 2006. Although  
840 the sawgrass coverage at this station decreased for several years thereafter, it nearly returned to  
841 pre-fire conditions after three years by 2009. The  $N_{1.0}$  and  $FS_{1.0}$  stations showed increases in  
842 cattail coverage, but no overall change in sawgrass coverage over the four-year survey period.  
843 The  $FS_{0.25}$  station had the reverse trend, with cattail coverage decreasing and sawgrass coverage  
844 remaining constant over the survey period. It is important to note that transect poles had to be  
845 moved in November 2008 at several sites ( $N_{1.0}$ ,  $N_{2.0}$ ,  $N_{4.0}$ ,  $FS_{0.25}$ , and  $FS_{1.0}$ ). This was due to the  
846 impact of drift from an herbicide application to clear helicopter landing areas for safe access to  
847 sites. In addition, one transect ( $N_{2.0}$ ) was relocated in April 2006 due to trails worn next to the  
848 transect that affected the vegetation along the transect. In each of these cases, transect poles were  
849 moved to the closest possible location away from the disturbance that had the same vegetation  
850 communities.

851


852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872



873  
874  
875  
876  
877  
878

**Figure 5-11.** Relative abundances (%) of periphyton type for six of the permit compliance stations,  $N_{0.25}$  (a),  $N_{1.0}$  (b),  $N_{2.0}$  (c),  $N_{4.0}$  (d),  $C_{4.0}$  (e), and  $FS_{3.0}$  (f), from 1998 to 2008, based on five indicator classes: (1) TP < 10 ppb, (2) TP = 11-15 ppb, (3) TP = 16-20 ppb, (4) TP = 21-30 ppb, and (5) TP > 30 ppb.





879

880

881

Figure 5-11. Continued.

882 **Table 5-16.** Summary statistics for WY2009 periphyton tissue TP concentrations  
 883 (mg/kg) measured at the permit compliance sampling locations at WCA-2A.

Station	Epiphyton TP Concentration		Metaphyton TP Concentration	
	(mg/kg)	N	(mg/kg)	N
N <sub>0.25</sub>	1120	1	-	0
N <sub>1.0</sub>	-	0	-	0
N <sub>2.0</sub>	460 ± 16	3	-	0
N <sub>4.0</sub>	345 ± 6	3	237 ± 19	3
C <sub>4.0</sub>	-	0	-	0
FS <sub>0.25</sub>	-	0	1620 ± 44	3
FS <sub>1.0</sub>	888 ± 94	3	-	0
FS <sub>3.0</sub>	425 ± 5	2	246 ± 19	3

884

885 **Table 5-17.** Nitrogen:Phosphorus ratios in live sawgrass (*Cladium jamaicense*) leaf  
 886 tissues at the permit compliance sampling locations in WCA-2A from 2006 to 2008.

Station	2006		2007		2008	
	Spring	Fall	Spring	Fall	Spring	Fall
N <sub>0.25</sub>	21 ± 6	-	-	-	-	-
N <sub>1.0</sub>	17 ± 3	15 ± 6	22 ± 5	21 ± 5	26 ± 1	20 ± 2
N <sub>2.0</sub>	24 ± 4	28 ± 1	21 ± 4	26 ± 1	34 ± 2	20 ± 3
N <sub>4.0</sub>	35 ± 5	22 ± 2	36 ± 5	39 ± 5	41 ± 0.4	35 ± 4
C <sub>4.0</sub>	37 ± 7	28 ± 1	42 ± 3	37 ± 2	33 ± 1	34 ± 5
FS <sub>0.25</sub>	19 ± 7	20 ± 3	24 ± 2	27 ± 1	23 ± 2	18 ± 1
FS <sub>1.0</sub>	20 ± 6	19 ± 3	22 ± 2	24 ± 3	23 ± 1	20 ± 1
FS <sub>3.0</sub>	37 ± 2	31 ± 8	45 ± 4	38 ± 3	34 ± 1	30 ± 1

887

888 **Table 5-18.** Nitrogen:Phosphorus ratios in live cattail (*Typha domingensis*) leaf  
 889 tissues at the permit compliance sampling locations in WCA-2A from 2006 to 2008.

Station	2006		2007		2008	
	Spring	Fall	Spring	Fall	Spring	Fall
N <sub>0.25</sub>	15 ± 3	8 ± 4	15 ± 1	18 ± 5	14 ± 0.4	13 ± 2
N <sub>1.0</sub>	19 ± 0.4	14 ± 1	17 ± 3	15 ± 1	17 ± 0.4	12 ± 3
N <sub>2.0</sub>	-	14 ± 3	20 ± 1	21 ± 3	19 ± 2	13 ± 2
N <sub>4.0</sub>	-	-	-	-	-	-
C <sub>4.0</sub>	-	-	-	-	-	-
FS <sub>0.25</sub>	9 ± 4	13 ± 1	16 ± 1	14 ± 1	20 ± 13	11 ± 1
FS <sub>1.0</sub>	13 ± 6	14 ± 1	17 ± 1	14 ± 1	15 ± 0.4	11 ± 1
FS <sub>3.0</sub>	-	-	-	-	-	-

890

891

892 **Table 5-19.** Number of points (out of 10 possible points at 1 m intervals along each  
 893 line transect) at the northern transect locations where sawgrass or cattail was  
 894 present. Surveys were completed during the dry and wet seasons each year.

Date	N <sub>0.25</sub>		N <sub>1.0</sub>		N <sub>2.0</sub>		N <sub>4.0</sub>		C <sub>4.0</sub>	
	Saw	Cat	Saw	Cat	Saw	Cat	Saw	Cat	Saw	Cat
Apr 05	1	10	10	0	10	0	10	0	10	0
Oct 05	1	10	9	0	10	0	10	0	10	0
Apr 06	1	10	9	0	10 <sup>W</sup>	0 <sup>W</sup>	10	0	10	0
Nov 06	1	10	10	5	9	0	1 <sup>F</sup>	0 <sup>F</sup>	10	0
Apr 07	1	10	10	9	10	0	6	0	10	0
Oct 07	0	9	10	2	10	0	2	0	10	0
Mar 08	0	10	10	0	10	0	4	0	10	0
Oct 08	1	10	5	2	10	0	8	0	10	0
Apr 09	1	10	10 <sup>S</sup>	4 <sup>S</sup>	10 <sup>S</sup>	0 <sup>S</sup>	9 <sup>S</sup>	0 <sup>S</sup>	10	0

895 <sup>S</sup> indicates that transect areas moved due to herbicide overspray.  
 896 <sup>W</sup> indicates that transect was moved due to worn trails next to transect.  
 897 <sup>F</sup> indicates the site experienced a fire prior to that survey period.

898  
 899  
 900

901 **Table 5-20.** Number of points (out of 10 possible points at 1 m intervals along each  
 902 line transect) at the southern transect locations where sawgrass or cattail was  
 903 present. Surveys were completed during the dry and wet seasons each year.

Date	FS <sub>0.25</sub>		FS <sub>1.0</sub>		FS <sub>3.0</sub>	
	Saw	Cat	Saw	Cat	Saw	Cat
Apr 05	7	8	7	0	10	0
Oct 05	3	9	3	3	10	0
Apr 06	7	4	7	6	10	0
Nov 06	8	5	8	7	10	0
Apr 07	8	5	8	8	9	0
Oct 07	8	2	8	5	10	0
Mar 08	8	4	8	8	10	0
Oct 08	6	6	6	5	10	0
Apr 09	8 <sup>S</sup>	4 <sup>S</sup>	8 <sup>S</sup>	2 <sup>S</sup>	10	0

904 <sup>S</sup> indicates that transect poles were moved due to herbicide overspray.

905

## 906 **Rotenberger Wildlife Management Area**

### 907 ***Rotenberger Configuration***

908 The Rotenberger Hydropattern Restoration Project is a component of the District's  
909 Everglades restoration efforts. The project goal is to slow, alter, and eventually reverse the  
910 ecosystem degradation within the Rotenberger Wildlife Management Area (RWMA)  
911 (**Figure 5-12**), primarily by restoring a more natural hydropattern. This degradation is  
912 predominantly caused by overly dry conditions that have resulted in repeated peat fires, soil  
913 oxidation and compaction, nutrient release from surface soils, and conversion of obligate wetland  
914 vegetative communities to upland-type communities. Anticipated benefits include the  
915 preservation and encouragement of additional desirable wetland vegetation species and the  
916 initiation of peat formation. Project features include a 240 cfs electric pump station (G-410) to  
917 withdraw treated water from the STA-5 discharge canal for release into the RWMA. This pump  
918 station distributes water through a 3.5-mile spreader canal located parallel to the west perimeter  
919 levee of the RWMA. Surface water that is released out of the RWMA goes into the Miami Canal  
920 (L-28 Canal) through four gated culverts (G-402A through G-402D) along the eastern boundary  
921 of the RWMA. There is a quarter-mile-long collection canal upstream of each outlet structure.

922 There are 20 monitoring stations within the area distributed across five transects that span out  
923 across the entire area from the G-410 inflow point. Eight of these stations (the entire RA- and  
924 RC-transects) are monitored for various water quality parameters. These stations are also sampled  
925 for periphyton tissue nutrients and taxonomic species composition. In addition, soil sampling and  
926 vegetation composition monitoring occurs at these sites as well as the remaining 12 stations. The  
927 RC1, RC2, and RC3 stations are EFA permit compliance locations within the RWMA.  
928 Monitoring data for the stations downstream of STA-5 can be located within two District  
929 databases, ERDP and DBHYDRO (Appendix 5-8).

930 Water levels have historically been monitored at the Rott.N and Rott.S stage gauges. New  
931 groundwater wells were installed next to each of the older stage gauges in late 2008. These new  
932 wells have the ability to detect lower groundwater levels than the older stage gauges. Beginning  
933 January 1, 2009, the hydrologic stages reported were obtained from the new groundwater wells  
934 instead of the older stage gauges; however, all gauges will remain in service.

### 935 ***Rotenberger Water Budget***

936 Annual water budgets from 2003–2008 are presented in **Table 5-21**. Approximately 80 to 90  
937 percent of the inflows and outflows in each water budget were attributed to rainfall and  
938 evapotranspiration (ET). Seepage values were not accounted for in these calculations. Errors  
939 noted on WY2006 and WY2007 budgets could have been due to the large-scale fire that occurred  
940 in 2006, which resulted in loss of surface vegetation in sizable portions of the area.

### 941 ***Rotenberger Hydrologic and Total Phosphorus Loads***

942 In WY2009, approximately 32,297 acre-feet (ac-ft) of STA-5 water was discharged into the  
943 RWMA through G-410 (**Figure 5-13**). The inflow TP FWMC was 47 ppb, yielding an inflow TP  
944 load of about 1.88 mt. Approximately 25,125 ac-ft of water was released through G-402A–C.  
945 The outflow TP FWMC concentration was 69 ppb and outflow TP load was about 2.15 mt  
946 (**Figure 5-14**). A limited amount of water was released via G-402D from August 26 to September  
947 14, 2008, after heavy rainfall from Tropical Storm Fay. While flow through G-402D is not  
948 currently measured, the District estimated that 2,344 ac-ft passed through this structure during the  
949 19.7 days that its gate was fully open.

950

951  
952  
953  
954

**Table 5-21.** Water budgets calculated for WY2003 through WY2008. Inflows (ac-ft) represent discharges into the RWMA from the G-410 and outflows (ac-ft) represent water releases from the G-402A–D structures.


WY	Inflow	Rainfall/ Seepage In	Total Inflow	Outflow	ET/ Seepage Out	Total Outflow	ERROR %
2003	54306	111179	165485	25312	125410	150722	-9.3
2004	16849	114620	131469	352	123546	123897	-5.9
2005	44414	113868	158281	33788	123847	157634	-0.4
2006	29886	114605	144491	54648	124451	179100	21.0
2007	16195	85538	101733	4630	123403	128033	22.3
2008	11646	108725	120371	0	124900	124900	13.8
TOTAL	173296	648535	821831	118730	745557	864287	6.4

	G-410 Inflow	Rainfall/ Seepage
% Inflow	21.1 %	79 %

	G-402 Outflow	ET/ Seepage
% Outflow	13.8 %	86.3 %

955  
956  
957  
958  
959

960




961  
962  
963  
964  
965

**Figure 5-12.** Map of Rotenberger Wildlife Management Area (RWMA) showing major structures and monitoring transects RA, RB, RC (permit compliance monitoring transect), RD, and RE.

966

967




968

Figure 5-13. Monthly flow and TP loads for the RWMA for WY2008 and WY2009.

969

970



971

972

973

Figure 5-14. Comparison of monthly to 12-month moving average TP concentrations for the RWMA outflow during WY2008.

974 ***Rotenberger Hydropattern Restoration***


975 Daily target stages for the RWMA are set based on the District's Natural System Model  
976 (NSM) values plus 0.25 ft. Rainfall during the beginning of WY2008 was well below average,  
977 and as a result, the stage dropped over 1 foot below NSM targets for most of this water year  
978 (**Figure 5-15**). During May 2007 and a portion of June 2007, the water level receded below the  
979 bottom of the stage recorder's stilling wells. Therefore, the mean stage appeared to hold steady  
980 at approximately 10.90 feet, but most certainly was lower. The stage gauges malfunctioned in  
981 mid-October 2007 and data were unavailable until repairs were completed in March 2008.  
982 Treated water from STA-3/4 was delivered into the area in March 2008.

983 Average stages were typically within five or six inches of the target stage from May 2008 to  
984 March 2009. Tropical Storm Fay delivered approximately seven inches of rain to the RWMA in  
985 August 2008. Stages rose to 13.67 feet National Geodetic Vertical Datum of 1929 (ft NGVD), but  
986 the water level was quickly lowered by opening the G-402 structures. The stages dropped rapidly  
987 in March and April 2009 due to lack of rainfall. Stages measured with the new groundwater wells  
988 were below 10 ft NGVD at the end of April 2009.

989 In June 2008, the District met with representatives from the Florida Fish and Wildlife  
990 Conservation Commission and the FDEP to review and update the RWMA Operation Plan  
991 (SFWMD, 2004) in order to improve the operational water delivery strategy for the area. It was  
992 determined that an updated topographic survey was needed to develop the Operation Plan. The  
993 RWMC was last surveyed in 2004; this survey utilized 31 points, and the average elevation was  
994 12.12 ft NGVD 29. In November 2008, 70 points were surveyed. This survey included the same  
995 31 points from 2004, plus an additional 39 points. The average marsh elevation using the 70-point  
996 grid was 12.07 ft NGVD 29. However, when comparing the same 31 points that were surveyed in  
997 both 2004 and 2008, the calculated ground elevation from the new survey was 12.14 ft NGVD  
998 29. Appendix 5-9 shows topographic maps derived from the 2004 and 2008 surveys.

999 The revised RWMA Operation Plan will give the District the ability to hold another quarter  
1000 foot of water in the marsh at the onset of the dry season to help minimize the impacts of future  
1001 drought conditions. It is recognized that during severe droughts, due to the lack of outside  
1002 supplemental water, the RWMA will inevitably dry out. The revised Operation Plan has not yet  
1003 been finalized.





1004 **Figure 5-15.** Daily target stage levels and mean daily stage readings (average of  
 1005 Rott.N and Rott.S stages) for WY2008 and WY2009. The average ground elevation is  
 1006 also displayed. Erroneous readings due to gauge failure were excluded. Target stages  
 1007 were based on Natural System Model for the RWMA plus 0.25 ft.  
 1008

### 1009 ***Rotenberger Surface Water Quality***

1010 Surface water quality samples were collected at eight stations within the RWMA on a  
1011 monthly basis when sufficient water (depth  $\geq 10$  cm) was available for retrieving representative  
1012 samples. Mean surface water TP concentrations (**Table 5-22**) and specific conductivity  
1013 measurements (**Table 5-23**) were calculated for each station. There were notable decreases in TP  
1014 and specific conductivity in WY2009 compared to WY2008 (**Table 5-24**). This could be  
1015 attributed to various factors, including increased rainfall, a longer hydroperiod, and reduced TP  
1016 loads and specific conductivity concentrations from STA-5. It should be noted that WY2008 data  
1017 is presented in this report because calendar year data was presented in the previous SFER.

### 1018 ***EFA Permit Compliance Transect Total Phosphorus and Conductivity at*** 1019 ***STA-5 Downstream Area (Rotenberger Wildlife Management Area)***

1020 As previously mentioned, the RWMA EFA permit compliance transect comprises three  
1021 monitoring stations (RC-1, RC-2, and RC-3) that extend approximately 4 km downstream of  
1022 pump station G-410 (**Figure 5-12**). All stations along this transect are identified as impacted.

1023 All specific conductivity levels along the RWMA transect were well below the 1,275  $\mu\text{S}/\text{cm}$   
1024 for Class III waters (**Table 5-9**). While conductivity levels did not change substantially along the  
1025 RWMA transect, median TP concentrations decreased by at least 15 ppb over a distance of 4 km  
1026 from the canal (**Figure 5-16**). The overall change in TP concentrations along the RWMA transect  
1027 was statistically significant ( $p < 0.001$ ) (**Table 5-10**).

### 1028 ***Rotenberger Soil Chemistry***

1029 Soil samples are collected every other year at 20 monitoring stations in the RWMA. Samples  
1030 were collected in March 2005, 2007, and 2009. Triplicate cores were collected from each station.  
1031 Cores were originally split into 0-2 and 2-10 cm sections for analysis, but results are presented for  
1032 the entire 0-10 cm soil core in this report. Samples were corrected for bulk density when  
1033 combining the results of both soil layers. Mean values were then calculated for each station from  
1034 the triplicate cores. No samples were collected along the RE-transect in 2005.

1035 The average soil TP concentrations varied among sites and between years (**Table 5-25**). An  
1036 overall decrease in mean soil TP concentrations ( $\pm$  standard deviation) was observed between  
1037 2007 and 2009 cores. Mean soil TP concentration in 2007 was  $994 \pm 80$  milligrams per kilogram  
1038 (mg/kg). In 2009, mean soil TP concentration was  $736 \pm 59$  mg/kg. The 2007 results were  
1039 influenced by the large-scale fire that occurred in May 2006, which included several peat fires in  
1040 northern sections of the RWMA (Pietro et al., 2008). The reduction in the mean TP concentration  
1041 from 2007 to 2009 may represent post-fire soil recovery.

1042 Among the 60 soil cores collected in 2009, five contained a floc layer above the consolidated  
1043 soil, indicating recent soil accretion. The depth of this floc layer and its TP concentration are  
1044 displayed in **Table 5-26**.

### 1045 ***Rotenberger Periphyton and Macrophytes***

1046 Periphyton collections were attempted at eight stations in October 2008; however, only five  
1047 stations had sufficient biomass for collection. This sampling will continue annually during the  
1048 late wet season in 2009 (WY2010). Periphyton taxonomic data from this single collection is  
1049 insufficient to make determinations using species composition as an indicator of changing water  
1050 quality status. Additional data is expected to be reported in future SFERs.

1051 Periphyton tissue TP concentrations are listed in **Table 5-27**. Using an ANOVA combined  
1052 with a post-hoc test, it was determined that the RA1 and RC1 stations had significantly  
1053 ( $p < 0.0001$ ) higher periphyton tissue TP concentrations than samples collected farther

1054 downstream of the G-410 pump station. This could be due to the fact that these two locations are  
1055 within an area that experienced peat fires in 2006 and because they are closest to the G-410 pump  
1056 station, both factors that could result in increased surface water TP and therefore increased  
1057 periphyton tissue nutrients.

1058 Cattail and sawgrass live leaf and root tissues were sampled in April 2009 at the RC1, RC2,  
1059 and RC3 stations. These collections are planned to occur semiannually. It is anticipated that data  
1060 from these analyses will be included in future SFERs.

1061 Using point intercept survey methodology, the areal coverage of dominant macrophyte  
1062 species has been surveyed along fixed 10 m long transects twice a year (dry and wet seasons)  
1063 since 2005. These surveys were performed at 20 locations across the RWMA; only the RC1,  
1064 RC2, and RC3 data are presented in this report because the remaining sites are in review. The  
1065 presence of sawgrass and/or cattail 1 m intervals along each transect was recorded  
1066 (**Table 5-28**). Sawgrass coverage decreased and cattail coverage increased at the RC1 station over  
1067 the four-year survey period, while the reverse trend was observed at RC2. The 2006 fire likely  
1068 had a strong effect on the vegetative change at the RC1. This site was located in area that  
1069 experienced peat fires, and nearly all the vegetation along the transect was removed in the fire. In  
1070 addition, this site was flooded in order to suppress the peat fires, while the other two sites  
1071 remained dry one month post-fire. Sawgrass and cattail coverage at the RC3 site remained fairly  
1072 constant over the survey period.

### 1073 ***Rotenberger Restoration Activities***


1074 The District is currently developing plans to construct a supplemental inflow pump station  
1075 (approximately 100 cfs capacity) on the western side of the RWMA to allow discharge of treated  
1076 water from STA-5 and future Compartment C STAs into the RWMA. This supplemental pump  
1077 station is intended to provide water managers more flexibility in achieving the desired water  
1078 depths and hydroperiods within the RWMA.

1079 The District, in cooperation with the Florida Game and Fish Conservation Commission, is in  
1080 the process of restoring approximately 19 acres of tree islands in the southwestern corner of the  
1081 RWMA. These islands were overgrown with exotics, primarily Brazilian pepper (*Schinus*  
1082 *terebinthifolius*; **Figure 5-17**) and Peruvian primrose-willow (*Ludwigia peruviana*). Both species  
1083 have been classified as Category I invasive species in Florida (FLEPPC, 2007). The pepper and  
1084 primrose-willow were cut and sprayed with herbicide to prevent regrowth (**Figure 5-18**). In July  
1085 2009, an assortment of 3,000 native trees and shrubs will be planted on the islands. It is expected  
1086 that this native vegetation will be beneficial to wildlife within the RWMA. The newly planted  
1087 trees and shrubs will be monitored to determine the planting success. Additional monitoring will  
1088 include measurement of soil accretion/subsidence, stress levels of the newly planted trees and  
1089 shrubs, canopy development, and wildlife usage.

1090 Several large areas (some greater than 2,000 acres in size) within the northern section of the  
1091 RWMA have become dominated by Carolina willow (*Salix caroliniana*) and Peruvian primrose-  
1092 willow. In June 2009, the District aerially applied herbicide to a 100-acre area of the RWMA to  
1093 test effectiveness of spraying to eliminate these large stands found in the P-enriched soils. The  
1094 District will replant these areas with sawgrass following the 2010 dry season. If planting proves  
1095 successful, then the method will be used to return thousands of acres of the RWMA now  
1096 dominated by willow and primrose-willow back to sawgrass habitat.

1097 A vegetation mapping effort is under way for the RWMA based on 2008 overflight imagery.  
1098 The vegetation in the RWMA was last mapped in 2004. Maps and an analysis of changes in the  
1099 vegetation community between 2004 and 2008 are expected to be presented in future SFERs.

1100



1101 **Figure 5-16.** Notched box and whisker plots of conductivity and total phosphorus  
 1102 levels measured at permit compliance transect stations (RC1, RC2, and RC3) during  
 1103 WY2009 for STA-5. The notch on a box plot represents the 95% C.I. about the  
 1104 median, which is represented by the narrowest part of the notch. The top and  
 1105 bottom of the box represent the 75<sup>th</sup> and 25<sup>th</sup> percentiles, respectively. The whiskers  
 1106 represent the highest and lowest data values that are within two standard deviations  
 1107 of the median. Values above and below the whiskers are greater than two standard  
 1108 deviations from the median. Notches that do not overlap indicate that the data  
 1109 represented by the boxes being compared are significantly different at the 95% C.I.  
 1110

1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137



**Figure 5-17.** Dense standing Brazilian pepper (*Schinus terebinthifolius*) in the RWMA (photo by the SFWMD).



1138  
1139  
1140

**Figure 5-18.** Brazilian pepper removal in the RWMA. Very little vegetation was left after the pepper was removed (photo by the SFWMD).

1141 **Table 5-22.** Mean surface water TP concentrations  $\pm$  standard deviations measured  
 1142 during WY2009 in the RWMA. Asterisk (\*) indicates permit compliance location.

<b>WY2009</b>					
<b>Station</b>	<b>TP (ppb)</b>	<b>N</b>	<b>Min</b>	<b>Median</b>	<b>Max</b>
RA1	23 $\pm$ 17	11	11	18	72
RA2	11 $\pm$ 3	8	7	11	15
RA3	12 $\pm$ 3	7	8	11	17
RA4	13 $\pm$ 5	9	8	10	22
RC1*	26 $\pm$ 9	11	13	28	44
RC2*	12 $\pm$ 3	9	7	12	17
RC3*	14 $\pm$ 7	8	8	13	26
RC4	17 $\pm$ 6	8	10	16	28

1143  
 1144  
 1145  
 1146  
 1147

**Table 5-23.** Mean surface water specific conductivity  $\pm$  standard deviations measured during WY2009 in the RWMA. Asterisk (\*) indicates permit compliance location.

<b>WY2009</b>					
<b>Station</b>	<b>Sp Cond (<math>\mu</math>S/cm)</b>	<b>N</b>	<b>Min</b>	<b>Median</b>	<b>Max</b>
RA1	599 $\pm$ 152	11	358	588	822
RA2	415 $\pm$ 192	8	108	444	669
RA3	163 $\pm$ 53	7	96	143	248
RA4	218 $\pm$ 57	9	142	202	321
RC1*	607 $\pm$ 199	11	290	583	1009
RC2*	500 $\pm$ 180	9	186	527	724
RC3*	467 $\pm$ 206	8	142	473	709
RC4	248 $\pm$ 78	8	148	254	359

1148  
 1149  
 1150  
 1151  
 1152  
 1153

**Table 5-24.** Mean surface water TP and specific conductivity  $\pm$  standard deviations measured during WY2008 in the RWMA. Asterisk (\*) indicates permit compliance location.

<b>Station</b>	<b>WY2008 TP (ppb)</b>	<b>Samples collected WY2008</b>	<b>WY2008 Sp Cond (<math>\mu</math>S/cm)</b>	<b>Samples collected WY2008</b>
RA1	47 $\pm$ 36	4	713 $\pm$ 123	3
RA2	16	1	419	1
RA3	13	1	239	1
RA4	24 $\pm$ 10	3	385 $\pm$ 96	3
RC1*	56 $\pm$ 28	5	734 $\pm$ 94	4
RC2*	30 $\pm$ 23	3	766 $\pm$ 182	2
RC3*	32	1	547	1
RC4	32	1	312	1

1154

1155

1156

1157

1158

**Table 5-25.** Mean soil TP concentrations (milligrams per kilogram, or mg/kg)  $\pm$  standard errors from 2005, 2007, and 2009 collections in the RWMA. Each value is the mean of results from three soil cores collected to a depth of 10 cm. The RE-transect was not sampled in 2005. Asterisk (\*) indicates permit compliance location.

Station	2005 Mean TP <sub>0-10</sub> (mg/kg)	2007 Mean TP <sub>0-10</sub> (mg/kg)	2009 Mean TP <sub>0-10</sub> (mg/kg)
RA1	375 $\pm$ 22	483 $\pm$ 76	377 $\pm$ 141
RA2	378 $\pm$ 80	372 $\pm$ 106	606 $\pm$ 40
RA3	452 $\pm$ 44	605 $\pm$ 114	678 $\pm$ 4
RA4	735 $\pm$ 115	664 $\pm$ 102	799 $\pm$ 20
RB1	495 $\pm$ 55	633 $\pm$ 142	1699 $\pm$ 954
RB2	468 $\pm$ 122	818 $\pm$ 72	675 $\pm$ 19
RB3	372 $\pm$ 23	534 $\pm$ 65	493 $\pm$ 61
RB4	563 $\pm$ 33	816 $\pm$ 29	683 $\pm$ 41
RC1*	467 $\pm$ 25	2847 $\pm$ 388	1521 $\pm$ 33
RC2*	510 $\pm$ 37	669 $\pm$ 77	534 $\pm$ 109
RC3*	334 $\pm$ 13	634 $\pm$ 98	614 $\pm$ 46
RC4	639 $\pm$ 16	712 $\pm$ 76	711 $\pm$ 42
RD1	447 $\pm$ 28	1858 $\pm$ 475	808 $\pm$ 154
RD2	500 $\pm$ 85	792 $\pm$ 50	647 $\pm$ 40
RD3	561 $\pm$ 65	889 $\pm$ 80	875 $\pm$ 29
RD4	802 $\pm$ 257	1573 $\pm$ 209	851 $\pm$ 180
RE1	-	666 $\pm$ 75	537 $\pm$ 57
RE2	-	687 $\pm$ 120	512 $\pm$ 43
RE3	-	1671 $\pm$ 451	692 $\pm$ 77
RE4	-	447 $\pm$ 82	405 $\pm$ 44

1159

1160

1161

1162

1163

1164

1165

**Table 5-26.** Flocculent soil TP concentrations (mg/kg) of the five cores that contained flocculent soil development during the 2009 collections in the RWMA. Each flocculent soil sample represents a single sample. Asterisk (\*) indicates permit compliance location.

Station	Flocculent Soil Depth (cm)	Floc TP Concentration (mg/kg)
RB2	0 – 0.5	719
RC1*	0 – 0.5	3090
RE2	0 – 2.0	1010
RE2	0 – 2.0	752
RE3	0 – 2.0	559

1166

1167

1168

1169

1170

**Table 5-27.** Mean periphyton tissue TP concentrations (mg/kg)  $\pm$  standard errors from 2008 collections in the RWMA. RA3, RC2, and RC4 did not have sufficient amounts of periphyton for collection. Asterisk (\*) indicates permit compliance location.

Station	Periphyton TP Concentrations (mg/kg)
RA1	3253 $\pm$ 74
RA2	814 $\pm$ 34
RA3	-
RA4	798 $\pm$ 8
RC1*	2910 $\pm$ 174
RC2*	-
RC3*	889 $\pm$ 13
RC4	-

1171

1172

1173

1174

1175

1176

1177

1178

**Table 5-28.** Number of points along fixed transects where sawgrass or cattail was present, out of 10 possible points. Each point represents a distance of 1 m. Surveys were completed during the dry (April) and wet (October or November) seasons each year. Surveys were not completed at RC3 in October 2007 due to site inaccessibility. Asterisk (\*) indicates permit compliance location.

Date	RC1*		RC2*		RC3*	
	Saw	Cat	Saw	Cat	Saw	Cat
Apr 05	9	4	7	6	10	0
Nov 05	9	0	10	6	10	0
Apr 06	9	0	10	6	10	0
Oct 06	3	4	5	2	10	1
Apr 07	3	3	7	4	10	4
Oct 07	2	1	9	3	-	-
Apr 08	4	1	9	1	10	0
Oct 08	5	5	9	0	10	1
Apr 09	3	7	10	0	10	1

1179



1180

---

## ANALYSIS AND INTERPRETATION

---

1181 This section reports on the Process Development and Engineering (PDE) component of  
1182 the Long-Term Plan for Achieving Water Quality Goals in the Everglades Protection Area  
1183 (Long-Term Plan). The longer-term STA performance is included along with a summary of the  
1184 impact of extreme weather conditions (drought/storm) on the STAs. The performance of the  
1185 individual treatment cells in each STA as well as updates on various rehabilitation activities that  
1186 have occurred in the STAs are presented.

1187

### DROUGHT IMPACTS ON THE STAS

1188 Operating plans have been established for each the six STAs which specify the stages in  
1189 which cells are to be maintained throughout the year during routine operation (SFWMD, 2007a-d;  
1190 2009a). The STA Drought Contingency Strategy Document (SFWMD, 2007e) has also been  
1191 established in an effort to prepare the STAs when a drought period is forecasted at which time  
1192 target water stages are adjusted slightly higher in attempt to keep each cell hydrated throughout  
1193 the drought period. The drought contingency approach prioritizes SAV cells to maintain a  
1194 minimum of six inches water depth to minimize impacts to the SAV. When supplemental water is  
1195 not available to maintain the drought target stages, some cells dry out (**Figures 5-19** and **5-20**).  
1196 Dry-out conditions in SAV cells can be detrimental to the plant community. Field observations in  
1197 the past indicates that dry-out conditions in the emergent community for shorter periods do not  
1198 seem to significantly impact the emergent plant communities and, in fact, they can be beneficial  
1199 in encouraging new growth. However, extended periods of dryout condition have visibly  
1200 impacted the emergent plant communities in terms of die-off of standing vegetation. When cells  
1201 are rewetted, the vegetation tends to recuperate. In the STA Operation Plans, the minimum target  
1202 for emergent cells is 6 inches below the average ground elevation. A study on evaluating the  
1203 effects of duration and extent of dry outs on cattails in the STAs is under way.

1204 **Table 5-29** shows a list of STA cells that dried out by the end of WY2009. In general, except  
1205 for a couple of cells, the SAV cells remained hydrated throughout the entire dry season. The  
1206 emergent cells in STA-2, STA-3/4, STA-5, and STA-6 experienced periods in which the cells  
1207 dried out. Water levels remained above ground level in STA-1W and STA-3/4 throughout the  
1208 entire dry season. Aerial flights and field visits throughout the dry season showed that there was  
1209 very little impact to the vegetation in any of the cells as a direct result of the drought conditions.  
1210 Evaluation of impacts of dry out to phosphorus flux and the effects of subsequent flows following  
1211 a dryout period on vegetation is expected to be reported in future SFERs.

1212

1213  
1214  
1215

**Table 5-29.** Drought conditions resulted in low water levels and some of the water quality monitoring stations within the STAs were suspended during the dry conditions and resumed after rehydration.

STA	Location	Inflow					Outflow				
		Structure	Grabs Suspended	A/S Suspended	Date Suspended	Date Resumed	Structure	Grabs Suspended	A/S Suspended	Date Suspended	Date Resumed
STA-1E	Cell 1	S-363 C	Yes	No	04/16/09	05/27/09	S-364 A	Yes	No	04/16/09	06/29/09
	Cell 2	Cell 2 inflow is the Cell 1 outflow					S-365 A&B	Yes	Yes	04/16/09 G 05/21/09 A/S	Not until USACE S-365 repairs are complete
	Cell 3	S-366 B&D	Yes	No	04/16/09	06/30/09	S-367 B	Yes	No	04/16/09	06/22/09
							S-376 D	Yes	No	04/16/09	06/29/09
	Cell 4N	Cell 4N inflow is the Cell 3 outflow					S-368 B&D	Yes	No	04/16/09	06/29/09
	Cell 5	S-370 A&C	Yes	No	05/15/09	05/19/09	S-371 A&C	Yes	No	05/15/09	05/26/09
STA-2	Cell 1	G-329B	Yes	No	05/06/09	05/20/09	G-330D	Yes	No	04/15/09	05/27/09
	Cell 2	G-331D	Yes	No	05/13/09	05/20/09	G-332	Yes	No	05/13/09	05/20/09
STA-5	Cell 1A	G-342A & B	Yes	Yes	12/10/08	Offline	G-343B & C	Yes	Yes	12/18/08	Offline
	Cell 1A	G-349A (PS)	Yes	Yes	02/04/09	Offline	G-343B & C	Yes	Yes	12/18/08	Offline
	Cell 2A	G-342C & D	Yes	Yes	04/15/09	06/03/09	G-343F & G	Yes	Yes	04/15/09	06/17/09
	Cell 3A	G-342 E & F	Yes	Yes	01/14/09	06/25/09	G-343I & J	Yes	Yes	01/14/09	06/25/09
	Cell 3B	Cell 3B inflow is the Cell 3A outflow					G-344E & F	Yes	Yes	01/14/09	06/25/09
STA-6	Sec 2	G-396B	Yes	Yes	01/13/09	06/02/09	G-352B	Yes	Yes	01/13/09	06/02/09
		G-396A&C	Yes	N/A	01/13/09	06/16/09	G-352A&C	Yes	N/A	01/13/09	06/16/09
	Cell 5	G-353A & B	Yes	Yes	01/13/09	06/02/09	G-354C	Yes	Yes	01/13/09	06/02/09
	Cell 3	G-353C	Yes	Yes	01/13/09	06/02/09	G-393B	Yes	Yes	01/13/09	06/02/09
	End of L3 Supply Canal	G-407 Div. Structure	Yes	Yes	01/13/09	06/02/09	N/A				

Notified FDEP on 06/03/09 of resumption of sampling.

Notified FDEP on 06/04/09 of resumption of sampling.

Notified FDEP on 07/01/09 of resumption of sampling.  
 STA-5, Cell1A and 1B, Flow-way 1, have been offline due to maintenance activities; they were not suspended as part of dryout.  
 STA-6, G-396A and C and G-352A and C do not have autosamplers; they are grab-only sites.

- A/S = Autosampler
- G = Grab sampling
- PS = Pump Station



**Figure 5-19.** An aerial photo of STA-1E, Cell 4, in May 2009, showing cell dryout, resulting in loss of SAV (photo by the SFWMD).

1216  
1217  
1218  
1219

1220  
1221



**Figure 5-20.** An aerial photo of STA-2, Cell 2, in May 2009, showing emergent vegetation communities during dryout periods as a result of low water conditions (photo by the SFWMD).

1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233

1234  
1235  
1236

1237 **TROPICAL STORM FAY IMPACTS ON THE STAS**

1238 In August 2008, Tropical Storm Fay dumped five to six inches of rain over a two-week  
 1239 period across large parts of South Florida causing severe flooding. Immediately after the storm  
 1240 passed, the District conducted a post-storm assessment in all STAs to document any damage to  
 1241 the vegetation caused by winds or high water conditions (**Figure 5-21**). The STAs were  
 1242 resurveyed by the District in February 2009 to evaluate recovery of the affected areas. The  
 1243 assessments were conducted by driving along the levees and, in some cases, inspection of the cell  
 1244 interiors via airboat, and included photographic documentation, water depth measurements, and  
 1245 qualitative assessment of vegetation conditions.

1246 **Initial Vegetation Assessment**

1247 To minimize damage resulting from deepwater conditions, STA Operation Plans specify that  
 1248 water depth and duration in emergent aquatic vegetation (EAV) cells should not exceed more  
 1249 than 4 ft for three consecutive days, 3.5 ft for seven consecutive days, and 3 ft for 10 consecutive  
 1250 days. The District monitors water depths closely during peak periods.

1251 The initial post-storm vegetation assessment focused on EAV cells where the water depth and  
 1252 duration threshold had been exceeded specifically, the survey involved visual inspection of the  
 1253 vegetation in the interior of STA-1E, Cell 7; STA-1W, Cell 1A; and STA-3/4, Cells 1A and 2A  
 1254 (**Table 5-30**). Although STA-3/4, Cell 3A, exceeded the 3 ft depth for 19 days, no internal  
 1255 site visit was performed. In general, minimal impacts to SAV communities in these cells were  
 1256 observed, involving only a small amount of plant material washed out and deposited along  
 1257 the levees.

1258

1259

1260 **Table 5-30.** STA cells that exceeded Operating Plan water depth/duration  
 1261 thresholds following Tropical Storm Fay, September 11, 2008.

Water Depths	Number of days of inundation								
	STA-1W			STA-1E				STA-2	
	Cell 1A	Cell 2A	Cell 5A	Cell 1	Cell 3	Cell 5	Cell 7	Cell 1	Cell 2
3 ft	19	15	10	0	4	2	16	0	9
4 ft	9	0	0	0	0	0	7	0	0

Water Depths	Number of Days of inundation								
	STA-3/4			STA-5			STA-6		
	Cell 1A	Cell 2A	Cell 3A	Cell 1A	Cell 2A	Cell 3A	Cell 3	Cell 5	Section 2
3 ft	25	24	19	0	0	0	0	0	0
4 ft	13	1	0	0	0	0	0	0	0

1262

1263 **STA-1E**

1264 Water depths in the Eastern Flow-way remained well below two feet. Water depth in both  
1265 Cells 3 and 4N exceeded 3 ft for approximately four days. The Western flow-way experienced the  
1266 greatest increase in water depth, with Cell 7 experiencing seven days with water depths above 4 ft  
1267 and 16 days with depths greater than 3 ft.

1268 Majority of cattail establishment in Cell 7 has been poor, primarily due to repeated and  
1269 persistent high water conditions. Over 40 percent of the cell lack vegetation. Post-storm  
1270 assessment indicate a large portion of the standing cattails were stressed, e.g., sparse density and  
1271 loosely anchored cattail roots that are easily dislodged (**Figure 5-22**), while some remained intact  
1272 with standing plants throughout the cell. There are many individual floating plants throughout  
1273 portions of the cell, and these plants were found to have poor below ground structure  
1274 (**Figure 5-23**). There were no floating tussocks observed during this survey.

1275 **STA-1W**

1276 All the EAV cells in STA-1W exceeded the depth and duration threshold guidelines with the  
1277 exception of Cell 5A, which was at the limit of the 3 ft threshold at the time of survey. Cell 1A  
1278 had depths greater than 4 ft for nine days and 3 ft for 19 days, Cell 2A had depths greater than 3 ft  
1279 for 15 days, and Cell 5A depths went above 3 ft for 10 days.

1280 Overall, the cattail community appeared to be expanding slowly throughout Cell 1A from the  
1281 2007 rehabilitation efforts and the storm seemed to have had little effect on the vegetation, except  
1282 in a few cases where the cattail had uprooted (**Figure 5-24**). Floating tussocks formation has  
1283 historically been a concern in this cell. Tussock islands observed along the western edge of  
1284 Cell 1A could have been reformed from old tussocks. There were also a few small areas where  
1285 new floating peat mats were observed (**Figure 5-25**). All floating tussocks or floating peat mats  
1286 appear to be isolated to a small area; however, this could become more problematic as this  
1287 material begins to migrate throughout the cell.

1288 **STA-2**

1289 Based on stage data, the EAV cells in STA-2 did not exceed the depth/duration threshold  
1290 guidelines; therefore, no internal evaluation was necessary. A levee survey of STA-2 conducted  
1291 in August 2008 found no visible damage to the cattail community.

1292 **STA-3/4**

1293 Water depths in all the EAV cells of STA-3/4 had been higher than 3 ft for more than  
1294 15 consecutive days. Cell 1A experienced water depths greater than 4 ft for 13 days. Cell 2A  
1295 surpassed the 4 ft threshold only for one day, but field observations showed areas in which depths  
1296 reached as high as 4.5 ft for a longer period of time.

1297 There were large areas in Cells 1A and 2A with floating cattail. In areas where cattails were  
1298 still standing, the plants were only loosely anchored and were easily uprooted from the ground,  
1299 indicating poor root structure. Visible weakness in the roots and rhizomes and evidence of  
1300 etiolation in the shoots were evident.

1301 **STA-5**

1302 Water levels in STA-5 remained at or below 2.75 ft throughout the duration of the high flow  
1303 event. There were no visible signs of stress on the EAV or the SAV. There was a significant  
1304 reduced cattail stands throughout all three EAV cells due to low water conditions during the  
1305 previous two year drought period.

1306 **STA-6**

1307 There were no visible signs of stress on the EAV or the SAV in STA-6. There was a lack of  
1308 cattail stands in this STA due to impacts of the prior two-year drought period.

1309 **Aerial Vegetation Assessment**

1310 An aerial survey of the STAs conducted on September 30, 2008, also confirmed the findings  
1311 of the levee and interior surveys. In STA-1E, Cell 7, while significant amounts of cattail remained  
1312 standing, there was a large portion of the cell where the cattail was either floating or had fallen  
1313 over. Similarly, in STA-1W, Cell 5A, there was a large portion of the cattail community that was  
1314 either floating or had fallen over. In STA-3/4, the northern quarter portion of all three EAV cells  
1315 had large areas where the cattail coverage had been substantially reduced.

1316 **Post-Storm Recovery Assessment**1317 **STA-1E, Cell 7**

1318 The cattail community in STA-1E, Cell 7, struggled due to persistent high water conditions  
1319 resulting from its lower ground elevation (approximately one foot lower than adjacent cells).  
1320 Water depth up to 3.5 ft was still observed in this cell in the months after Tropical Storm Fay.  
1321 The observed conditions pose a concern that massive mortality of existing cattail stands will  
1322 occur and will result in difficulty of reestablishing emergent vegetation in this area. A field study  
1323 to evaluate the effects of the hydraulic conditions on cattail growth was started in June 2009.

1324 **STA-1W, Cell 1A**

1325 The EAV in STA-1W, Cell 1A, was expanding and appeared to be healthy at the time of the  
1326 survey. The floating tussock problems still existed; however, the low-water levels seemed to have  
1327 allowed the tussocks to settle to the bottom at least on an interim basis.

1328 **STA-3/4, Cell 1A**

1329 At the time of survey, STA-3/4, Cell 1A, showed visible signs of recovery. Large numbers of  
1330 dead cattail plants remained floating in previously impacted areas. Water depths averaged slightly  
1331 over 2 ft in impacted areas allowing some new sprouting of cattails. Although water depths in  
1332 STA-3/4 had returned to the target levels, Cell 1A continued to exhibit higher water depths than  
1333 the other cells. After a reviewing of the 2008 topographic surveys, it was concluded that the  
1334 differences in water depths among cells in STA-3/4 and internal locations in Cell 1A could be  
1335 attributed to variations in micro-topography.

1336



1337

1338

**Figure 5-21.** SAV wash-up in STA-1W, Cell 5B, following Tropical Storm Fay, August 2008 (photo by the SFWMD).

1339

1340

1341



1342

1343

**Figure 5-22.** Evidence of uprooted or floating cattail in STA-1E, Cell 7, September 2008 (photo by the SFWMD).

1344

1345

1346



1347

1348 **Figure 5-23.** Comparison of cattail root system from shallow and deep areas in  
1349 STA-1E, September 11, 2008. Left panel: healthy rhizome formation; right panel:  
1350 poor root system from deep areas in Cell 7 (photo by the SFWMD).

1351

1352

1353

1354

1355

1356

1357

1358

1359

1360

1361



1362

1363 **Figure 5-24.** Uprooted cattail in STA-1W, Cell 1A  
1364 (photo by the SFWMD).

1365




1366



1367  
1368  
1369  
1370

**Figure 5-25.** Floating tussocks in STA-1W, September 2008 (photos by the SFWMD).

1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383



**Figure 5-26.** Areas in STA-3/4 with water depth greater than 4 feet.



**Figure 5-27.** New cattail sprouting in STA-3/4, Cell 1A, six months after Tropical Storm Fay (photo by the SFWMD).

1384  
1385  
1386

1387 **CELL AND FLOW-WAY ANALYSIS AND INTERPRETATION**


1388 This section includes the individual annual (water year) water and TP mass balance budgets  
1389 (hereafter “budgets”) for individual STA treatment cells or flow-ways (hereafter “cells”). The  
1390 District conducts the field sampling and laboratory analyses associated with this effort under the  
1391 Everglades Construction Project (ECP) Operations Monitoring Project. The assumptions and  
1392 methods used in the computation of cell budgets (Appendix 5-10, Tables 1 and 2) are provided in  
1393 the 2008 and 2009 SFERs – Volume I, Chapter 5. Budgets were prepared for each of the  
1394 cells listed below; changes or additions to the WY2009 budgets from budgets in previous SFERs  
1395 are noted:

- 1396 • **STA-1E.** Cells 3, 4N, 4S, 5, 6, and 7.
- 1397 • **STA-1W.** Cells 1A, 2, 1B and 3, 4, and the North Flow-way (Cells 5A and 5B): flow  
1398 monitoring has been discontinued at the G-253 levee separating Cells 1 and 3 and  
1399 initiated at the G-248 levee separating Cells 1A and 1B, which necessitated that WY2009  
1400 budgets be computed for Cell 1A and a combination of Cell 1B and 3 rather than for  
1401 Cells 1 and 3 as has been done in previous years.
- 1402 • **STA-2.** Cells 1, 2, 3, and 4: Cell 4 flow and TP data became available in WY2009 and  
1403 budgets are included in this year’s report.
- 1404 • **STA-3/4.** Cells 1A, 1B, 2A, 2B, 3A, and 3B: flow monitoring was initiated at the G-384  
1405 levee that divides Cell 3, which enabled the calculation of separate budgets for Cells 3A  
1406 and 3B this year rather than combined Cell 3 budgets as has been done in previous years.
- 1407 • **STA-5.** Cells 1A, 1B, 2A, 2B, 3A, and 3B: flow monitoring was initiated at the G-343  
1408 levee, which enabled the calculation of separate budgets for Cells 1A, 1B, 2A, and 2B  
1409 this year rather than combined budgets for the North and Center Flow-way as has been  
1410 done in previous years (Note that the cells which now comprise the Center Flow-way  
1411 [Cells 2A and 2B] were referred to as the South Flow-way in previous SFERs); Cell 3A  
1412 and 3B flow and TP data became available in WY2009 and budgets are included in this  
1413 year’s report.
- 1414 • **STA-6.** Cells 3 and 5 and Section 2: Section 2 flow and TP data became available in  
1415 WY2009 and budgets are included to this year’s report.

1416 Budgets were developed using available data at the time of this report, which may reflect  
1417 revisions to data reported in previous SFERs. Water budgets in WY2009 were dominated by  
1418 surface flow as in previous years (Appendix 5-10, Table 1). Groundwater and precipitation in the  
1419 STAs generally made up less than 15 percent of the total inflow water volume, while surface  
1420 outflow comprised at least 80 percent of total outflow. Exceptions occurred in some cells of  
1421 STA-5 and STA-6, where seepage losses and ET made up a larger proportion of total outflow.  
1422 More detailed discussions of water budgets are presented in the 2008 and 2009 SFERs – Volume  
1423 I, Chapter 5.

1424 TP budgets in WY2009 were again dominated by surface water inflow and outflow TP as in  
1425 previous years (Appendix 5-10, Table 2). Previous SFERs have documented an inverse  
1426 relationship between cell treatment performance and inflow TP (measured as flow-weighted  
1427 mean concentration, load, or areal loading); increasing inflow TP resulted in higher outflow TP  
1428 and correspondingly reduced treatment. In general, cell treatment performance has been  
1429 consistent with how other treatment wetlands respond to increasing inflow TP (e.g., Kadlec,  
1430 2006; Richardson and Qian, 1999). In this report, the cell treatment performance is examined  
1431 from the perspective of vegetation community type (Appendix 5-10, Tables 2 and 3). Cells were  
1432 classified as being EAV, SAV, or both in cases such as the North flow-way of STA-1W that has  
1433 EAV and SAV cells. The annual outflow TP load and FWMC were plotted against the

1434 corresponding annual TP inflow load and FWMC, respectively; both TP outflow load and FWMC  
 1435 also were both plotted against the corresponding annual TP areal loading (**Figure 5-28**). There  
 1436 were weak regression relationships ( $r^2$  values ranged from 0.23 to 0.37) for data pooled over all  
 1437 vegetation community types, indicating that annual inflow TP generally accounted for only a  
 1438 small amount of the variation in treatment performance. Much of the unexplained variance in  
 1439 outflow TP is attributed to other factors such as soil characteristics, the occurrence and duration  
 1440 of dryout, or changes in plant community species composition. **Figure 5-28** reveals that the  
 1441 individual data points for the different vegetation community types were not segregated from  
 1442 each other; rather, there was considerable overlap among data points over almost the entire range  
 1443 in inflow TP levels. The EAV and SAV designations used to classify cells clearly do not  
 1444 correspond with distinct differences in annualized treatment performance.



1465 **Figure 5-28.** Comparison of annual treatment performance in STA treatment  
 1466 cells and flow-ways with variation in annual inflow TP levels. Insets show inflow  
 1467 versus outflow TP flow-weighted mean concentration (FWMC) (A), inflow versus  
 outflow TP load (B), inflow TP areal loading versus outflow TP FMWC (C), and  
 inflow TP areal loading versus outflow TP load (D). Treatment cells were classified  
 as either EAV or SAV based on their description in **Table 5-1**; flow-ways with  
 both EAV and SAV treatment cells are designated as "both".

1468 **STA-1W POST-REHABILITATION UPDATE**

1469 Details of the 2006 and 2007 rehabilitation efforts in STA-1W were reported in the 2008 and  
1470 2009 SFERs – Volume I, Chapter 5. Rehabilitation was done to make environmental conditions  
1471 more favorable for SAV recruitment and establishment in Cells 1B, 2B, 4, and 5B (**Figure 5-29**).  
1472 In 2007, an effort to convert from EAV to SAV was also implemented in Cell 3, in accordance  
1473 with the Long-Term Plan requirements. An updated evaluation of these cells is provided below.

1474 Since May 2003, STA-1W has been impacted by major storm or construction events and has  
1475 received variable inflow TP concentrations (**Figure 5-30**). Inflow and outflow hydraulic and TP  
1476 loads have been variable (**Figure 5-31**). TP loads into STA-1W were reduced in WY2007–  
1477 WY2009 (26 to 50 mt annually) compared to WY2003–WY2005 (51 to 112 mt annually).  
1478 Changes in overall water quality and vegetation indicate that STA-1W continued to improve  
1479 since the rehabilitation completion. Outflow TP and total suspended solids (TSS) concentrations  
1480 continued to decrease in WY2009 (**Figure 5-32**). Individual flow-way outflow data also indicated  
1481 improved treatment performance. It should also be noted that reduced hydraulic and TP loads into  
1482 the STA during the two-year period could have also contributed to this trend (**Figure 5-31**).

1483 **Northern Flow-way:** Effluent water quality from the Northern Flow-way has improved in  
1484 terms of TP and TSS concentrations compared to pre-rehabilitation years. Average annual  
1485 arithmetic mean outflow TP concentrations decreased dramatically from about 240 ppb (WY2006  
1486 prior to rehabilitation) to less than 45 ppb (WY2007–WY2009) (**Figure 5-31**). Examination of  
1487 the individual cell outflow water quality indicated that Cell 5B is providing most of the treatment  
1488 for this flow way. Cell 5B continued to have very high SAV coverage throughout the cell, which  
1489 is credited to the 2006 rehabilitation efforts, with Southern naiad (*Naiad quadalupensis*) and  
1490 *Hydrilla sp.* as the most dominant species. In Cell 5A, cattail continued to be restricted to shallow  
1491 areas, while deeper areas continued to have poor or lack of vegetation. Efforts to plant bulrush are  
1492 planned for early WY2010, with results anticipated to be included in future SFERs.


1493 **Eastern Flow-way:** TP and TSS concentrations continued to improve in the Eastern  
1494 Flow-way (**Figures 5-32 and 5-33**). Initial annual average TP concentrations in WY2008 were  
1495 high (105 ppb) and may be attributed to (1) the “first flush” associated with restarting the  
1496 flow-way after rehabilitation, (2) decomposing biomass associated with vegetation conversion  
1497 efforts in Cell 3, and (3) minimal SAV coverage in Cell 3. Since that time, average annual  
1498 outflow TP concentrations have decreased to 33 ppb. Data indicate that all three cells in this  
1499 flow-way continue to have improved treatment performance (**Figure 5-32 and 5-33**).

1500 Field observations indicate that cattail coverage continues to increase throughout Cell 1A,  
1501 while *Chara sp.* continues to dominate in Cell 1B. A vegetation survey conducted in Cell 3 in  
1502 September 2008 found that *N. quadalupensis* was the dominant SAV species although *Chara* and  
1503 *Hydrilla* were abundant in some portions of the cell. Based on the extent of the SAV coverage in  
1504 Cell 3, the vegetation conversion effort initiated in this cell in 2007 is considered to be complete  
1505 (**Figure 5-34**).

1506 **Western Flow-way:** As reported in the 2008 and 2009 SFERs – Volume I, Chapter 5, the  
1507 2007 rehabilitation has resulted in dramatic increase in SAV coverage throughout Cells 2B and 4.  
1508 Water quality has also improved. Outflow TP concentrations in Cell 2 for WY2003–WY2005 and  
1509 Cell 2B in WY2007 exceeded 100 ppb, while outflow from Cell 4 approached 100 ppb prior to  
1510 rehabilitation. Outflow TP concentrations in both cells declined substantially in WY2008 and  
1511 WY2009 with average annual arithmetic mean of less than 70 ppb (Cell 2B) and 32 ppb (Cell 4)  
1512 (**Figure 5-32**).


1513 *Chara* continued to dominate the vegetation community in Cell 2B, however pockets of  
1514 *Hydrilla* and *N. quadalupensis* appear to be expanding in coverage. In Cell 4, both *Chara* and *N.*  
1515 *quadalupensis* were found in dense beds throughout the cell.

1516       **Summary:** SAV coverage increased significantly throughout Cells 1B, 2B, 3, 4, and 5B.  
1517       Current data and field investigations indicate that the SAV communities successfully established  
1518       and continued to persist in these cells since completion of rehabilitation. TP and TSS outflow  
1519       concentrations have improved dramatically in all three flow-ways since rehabilitation.  
1520       In summary, (1) the rehabilitation efforts of 2006 and 2007 have been successful, and (2) STA-  
1521       1W is on the path to providing optimal treatment performance. Efforts to further examine  
1522       conditions and implement more optimization strategies will continue to further improve  
1523       performance of this STA.  
1524




**Figure 5-29.** Schematic of STA-1W showing the layout of treatment cells.

1525




1526  
 1527  
 1528  
 1529  
 1530  
 1531  
 1532

**Figure 5-30.** Monthly inflow and outflow TP flow-weighted mean concentrations in STA-1W.



1533  
 1534  
 1535  
 1536

**Figure 5-31:** Annual average inflow and outflow TP loads and flows in STA-1W.




1537  
1538

**Figure 5-32:** Average annual arithmetic mean TP concentrations in STA-1W.



1539




1540

1541

**Figure 5-33:** Average annual arithmetic mean total suspended solids (TSS) concentrations in STA-1W.

1542



1543

1544

1545

1546

**Figure 5-34:** Vegetation map of STA-1W, Cell 3, illustrating the extent of SAV coverage.

## 1547 **STA-5 PERFORMANCE ANALYSIS AND REHABILITATION**

1548 Stormwater Treatment Area 5 (STA-5) is one of six treatment wetlands constructed to reduce  
1549 phosphorus levels in runoff from agricultural and urban areas prior to being discharged into the  
1550 Everglades Protection Area. Since becoming operational in 1999, TP mass removal by STA-5 has  
1551 ranged from 41 to 74 percent; the average removal rate for all Everglades STAs is about 85  
1552 percent. Outflow FWMC TP from STA-5 has also been higher than any of the other STAs  
1553 (**Figure 5-35**). To understand the reasons for the relatively poor performance and implement  
1554 remedial strategies, the District evaluated performance data and causal variables, including  
1555 hydraulic and TP loading, soil chemical and physical properties, vegetation characteristics, and  
1556 topography. Using the information gleaned from the research and monitoring, a series of  
1557 rehabilitation options were evaluated (see **Table 5-31**).

1558 Over the STA operational period, the hydraulic and phosphorus loading rates (HLR and PLR,  
1559 respectively) to each STA treatment cell (or flow-way as in the case of STA-5) was compared  
1560 (see 2009 SFER – Volume I, Appendix 5-8). The Northern and Southern flow-ways have similar  
1561 HLRs as the other STAs; the HLRs at STA-5 were slightly lower than STA-1W, STA-3/4, and  
1562 STA-6 and about equal to STA-2. The PLR for STA-5 was greater than the PLR in STA-2,  
1563 STA-3/4, and STA-6 but less than in STA-1W (Pietro, et al., 2008).

1564 Focusing on the Northern Flow-way (Cells 1A and 1B), TP concentrations at the mid-levee  
1565 structures (G-343A-D) showed little phosphorus reduction, indicating that there was limited  
1566 treatment occurring in the upstream areas of the cell (**Figure 5-36**). This was also confirmed  
1567 through an internal transect water quality sampling conducted by DB Environmental  
1568 Laboratories, Inc. The internal transects showed very little TP removal in Cell 1A and that  
1569 treatment in the Northern Flow-way occurs primarily in the SAV cell (Cell 1B) (**Figure 5-37**).

1570 Soil TP levels in STA-5 surface soil layer (0-10 cm) were similar during the first three years  
1571 of operation (2000, 2002, and 2003) (**Figure 5-38**). Soil TP levels in 2007 were notably higher,  
1572 which could be due to the accumulation of detrital matter that became part of the 0-10 cm layer in  
1573 time over cycles of drying and re-wetting in these areas. Soil floc TP was also measured (when  
1574 present) and concentrations ranged from 1,000 to 1,500 mg/kg.

1575 Hydraulic efficiency, hydrologic patterns, and vegetation coverage are critical in effective  
1576 wetland phosphorus removal. The movement of water throughout the treatment cell is influenced  
1577 by the topographic profile in the area. In 2008, the topographic survey conducted in Cell 1A  
1578 showed that the treatment cell had highly variable topography (**Figure 5-39**). A lower slough area  
1579 located in the southern section of the treatment cell was found to be about 1.5 to 3 feet lower in  
1580 elevation on average as compared to the northern part of the cell. The lower slough area was  
1581 virtually devoid of vegetation based on 2005 aerial imagery (**Figure 5-40**) and the same was  
1582 observed in the field in subsequent years. These findings indicated that a deeper water slough was  
1583 creating a hydrologic “short circuit,” therefore underutilizing the rest of the cell and not providing  
1584 sufficient time for treatment, thus contributing to poor phosphorus treatment performance. This  
1585 cell’s emergent vegetation was impacted by regional drought conditions and uneven water  
1586 distribution throughout the cell, resulting in vegetation communities with dominance of mixed  
1587 grasses with little cattail coverage.

1588 Based on these analyses, the poor performance at STA-5 might be due to several factors  
1589 (**Table 5-31**). The data analysis indicated that the key potential causes of the poor performance in  
1590 this STA were (1) high inflow load since it began operation in 1999 (Appendix 5-2); (2) highly  
1591 variable topography, resulting in frequent cycles of alternating wet-dry periods in some areas;  
1592 (3) short-circuiting, including the presence of a slough in Cell 1A; (4) poor vegetation  
1593 establishment in both the EAV (Cell 1A) and SAV (Cell 1B) cells; and (5) presence of high levels  
1594 of easily hydrolyzable phosphorus in the floc and the surface soil layer (0-10 cm).

1595 Several remedial strategies and improvement options were evaluated to improve the  
1596 performance of STA-5. The suggested options included vegetation management components,  
1597 operational changes, and construction activities. It was determined that the hydrology of the cell  
1598 was the primary reason for poor performance in Cell 1A, and the option chosen for  
1599 implementation focused on improvements in the northern inflow treatment cell, Cell 1A,  
1600 specifically in filling the slough area.

### 1601 **Cell 1A Rehabilitation**

1602 On January 29, 2009, construction work began in Cell 1A to fill the deeper slough area using  
1603 material from the westernmost sections of the treatment cell (previously referred to as the  
1604 non-effective treatment area) to remedy the short-circuiting in this area and distribute the water to  
1605 the rest of the cell for improved treatment.

1606 To evaluate sediment phosphorus release as a function of location within the STA-5 footprint,  
1607 laboratory incubations were performed to characterize the impacts of internal loading on  
1608 performance for the soil used for fill material. Following completion of this construction effort,  
1609 soil cores were collected from the filled-in slough as well as from an adjacent wetland area that  
1610 was not impacted by construction activity (**Figure 5-41**). The cores were transported to the  
1611 laboratory, reflooded with waters containing low levels of soluble reactive phosphorus (SRP) and  
1612 incubated under anoxic conditions.

1613 During two, 14-day incubations, the slough site exported little SRP to the water column,  
1614 whereas the waters overlying the wetland site soils exhibited an increase in P concentrations to as  
1615 high as approximately 1,600 ppb (**Figure 5-42**). This could be attributed to the fact that the  
1616 average soil TP in the 0-10 cm layer in the wetland area is 694 mg/kg, while the fill material has a  
1617 soil TP concentration of 71 mg/kg. These data suggest that in addition to providing hydraulic  
1618 benefits (elimination of a short circuit), the recently completed construction effort will help  
1619 reduce internal sediment P loading within the wetland.

1620 Prior to any fill moving activities, the plants in the non-effective treatment area of the cell  
1621 were burned to reduce the amount of vegetation biomass and to aid in soil scraping. The  
1622 non-effective treatment area is located within the STA-5, Cell 1A, levee boundaries and is  
1623 considered to be non-effective because the ground elevations were high in this area. By the end of  
1624 May 2009, using fifteen 30-ton dump trucks, three bulldozers, and three excavators,  
1625 approximately 80 to 100 acres of the slough area were filled, totaling 407,240 cubic yards of  
1626 material moved. The slough filling portion of the rehabilitation project was successful and the  
1627 field team far exceeded the original expectations for the effort, almost tripling the amount of fill  
1628 to the slough than was originally anticipated. In June 2009, the filled areas were planted with  
1629 cattail and sawgrass seeds. Various wetland plants were also planted to encourage vegetation  
1630 establishment. A post-rehabilitation monitoring plan has been initiated to assess the success of the  
1631 rehabilitation effort using interior sampling sites monitored for water quality, stage, and  
1632 hydraulics along with an evaluation of the vegetation establishment. The results of the interior  
1633 monitoring evaluation are expected to be presented in future SFER reports.

1634

1635

1636  
1637  
1638  
1639

**Table 5-31.** Summary of performance issues contributing to the poor phosphorus removal at STA-5 and the goals of the rehabilitation efforts to provide optimized and sustainable performance.

---

**STA-5 Performance issues**

---

High historic phosphorus loading rates and inflow concentrations

Experiences periods of high flows/loads followed by periods of low to no inflow

Historically, has lowest TP removal efficiency (58%) as compared to other STAs (80%)

Experiences regular dry-out conditions in parts of or entire cells, particularly the EAV cells

Poor vegetation establishment and sustainability

Increasing TP levels in floc and surface soil layers

---

**Rehabilitation goals:**

---

Optimize TP removal efficiency

Reduce hydraulic short-circuiting

Increase effective treatment area

Provide long-term fix (sustainability of performance)

**Cost-Savings Approach:**


Take advantage of low water conditions (opportunistic scheduling)

Use fill from high elevation areas within the STA

Fully utilize Field Station personnel


Encourage growth of more efficient and sustainable plant communities

1640  
 1641  
 1642  
 1643  
 1644  
 1645  
 1646  
 1647  
 1648  
 1649  
 1650  
 1651  
 1652  
 1653  
 1654




**Figure 5-35.** Comparison of STA outflow TP FWMC from WY2001–WY2008.  
 [Note that the TP FWMC from STA-5 is the highest of all the STAs].

1655  
 1656  
 1657




1658  
1659  
1660  
1661  
1662

**Figure 5-36.** Grab samples collected at the inflows and mid-levee structures of STA-5, Cell 1A, showing that there is very little reduction in TP concentrations.



**Figure 5-37.** Surface water TP along internal transects in the Northern Flow-way of STA-5, sampled in August 2008 by DB Environmental Laboratories, Inc. Mean inflow for two weeks prior to sampling was 244 cubic feet per second (cfs). SRP = soluble reactive phosphorus, DOP = dissolved organic phosphorus, PP = particulate phosphorus.


1663



**Figure 5-38.** TP concentration in the surface soil layer (0-10 cm) of STA-5 from 2000 to 2007, compared with values from in well-performing STAs (STA-2 and STA-6). STA-5 data are circled.



1664  
 1665  
 1666  
 1667  
 1668  
 1669  
 1670  
 1671  
 1672  
 1673  
 1674



**Figure 5-39.** 2008 topographic map of STA-5, Cell 1A, showing that the ground elevation in the slough in the southern portion of the cell was about 1.5 to 3 feet lower than the rest of Cell 1A.

1675






Figure 5-40. Vegetation map of STA-5 derived from aerial photographs taken in 2005.

1676



1677 **Figure 5-41.** Soil sampling locations in STA-5, Cell 1A, for the laboratory core  
 1678 incubations. At the time of sampling, the slough station had been filled in with  
 1679 mineral soils borrowed from a higher elevation region to the west.

1680



1681 **Figure 5-42.** Soluble reactive phosphorus (SRP) release into the water column  
 1682 from STA-5, Cell 1A, soil cores incubated in the laboratory under anoxic conditions.  
 1683 Two, 14-day batch incubations were performed. Soil cores were obtained from the  
 1684 slough site recently filled in with mineral soils, and from a wetland site, unimpacted  
 1685 by construction activities (see **Figure 5-41**).

1686

## 1687 STA-6 PERFORMANCE EVALUATION

1688 Until WY2007–WY2008, annual outflow TP concentrations at STA-6 were some of the  
1689 lowest compared to the other Everglades STAs. Since 1999, average annual outflow TP FWMC  
1690 from Cells 3 and 5 combined was between 20 and 30 ppb for all years except for WY2007 and  
1691 WY2008, where outflows rose to 45 ppb and 38 ppb, respectively<sup>4</sup>. In WY2009, outflow  
1692 concentrations were lower (28 ppb). Because operations at STA-6 changed due to the use of the  
1693 new expansion cell (Section 2), the inflow also changed so that comparisons of inflow to outflow  
1694 in this analysis do not include the current water year. The following discussion summarizes an  
1695 investigation that was conducted in spring 2009 into the possible reasons for the increase in  
1696 outflow TP concentration in WY2007 and WY2008 in order to identify the major drivers leading  
1697 to the decline in performance.

1698 The performance data were examined to determine if the increases in outflow TP  
1699 concentrations could be attributed to higher loadings or other operating conditions, such as  
1700 sporadic inflows, prolonged dry-out conditions in the soil, loss of wetland vegetation, or  
1701 fluctuating water depths in the marsh. The trends in inflow water load, TP load and TP FWMC  
1702 were considered along with the water depths in the marsh and soil nutrient data. For most of the  
1703 period of record (POR), STA-6 was operational except for February and March 2007 when  
1704 inflows to the STA were stopped for Long-Term Plan Enhancements construction. Other times of  
1705 no inflow are reflective of the variable rainfall in the contributing basin. From October 1999 until  
1706 April 2005, STA-6 received runoff from sugarcane farms. After that, the fields were fallow and  
1707 inflows were limited to what was needed for flood control within the basin.


1708 An analysis of POR data showed that the outflow TP FWMC was higher in WY2007–  
1709 WY2008 than WY1999–WY2006 (**Figure 5-43**). Inflow hydraulic and TP loads appear to be  
1710 unlikely causes for the recent increase in outflow TP because they were substantially reduced in  
1711 WY2007–WY2008 compared to previous years. Although the mean inflow TP concentration was  
1712 about 25 ppb higher in WY2007–WY2008, there were also comparable annual values during the  
1713 WY1999–WY2006 period, which did not elicit high outflow values; therefore, higher inflow TP  
1714 concentration does not appear to explain the change in performance (**Figure 5-44**). The annual  
1715 data show that the inflow loads, TP FWMC, and the hydraulic and TP loads were about the same  
1716 over the years, except for WY2008 that had much reduced inflow and outflow loads and volumes.  
1717 During drought years (WY2001, WY2006, WY2007, and WY2008), annual outflow  
1718 concentrations have been higher.

1719 Monthly data show that there were substantially higher outflow concentrations following  
1720 flow events that were preceded by periods of little to no inflow. Following periods of no inflows  
1721 or outflows, the outflow concentrations have been magnitudes higher than the average  
1722 concentrations that range from 25 to 40 ppb (**Figure 5-45**). High outflow concentrations persisted  
1723 for about one to two months after rehydration. High concentrations observed in June 2005 and  
1724 August 2007 had very low associated monthly flows (5 and 139 ac-ft, respectively) and, although  
1725 the concentrations were high, the resulting loads were low (**Table 5-32**). The duration of lack of  
1726 inflow has also increased in the later water years. In WY2007 and WY2008, there were four and  
1727 seven months of no inflow, respectively, as compared to previous years where lack of inflow only  
1728 lasted for one to two months. The sporadic flows and resulting decreases in water depths and  
1729 resulted in dry-out conditions in parts of or the entire cells which notably affected the outflow  
1730 concentrations (**Figure 5-46**).

---


<sup>4</sup> Only Cells 3 and were evaluated because STA-6 Section 2 was not operational until WY2008.

1731  
 1732  
 1733  
 1734  
 1735  
 1736  
 1737  
 1738  
 1739  
 1740  
 1741  
 1742  
 1743  
 1744  
 1745  
 1746  
 1747  
 1748  
 1749  
 1750  
 1751  
 1752  
 1753  
 1754  
 1755  
 1756  
 1757  
 1758  
 1759  
 1760  
 1761  
 1762  
 1763




**Figure 5-43.** Comparison of STA-6 inflow FWM TP, water load, and inflow TP load between WY1999–WY2006 and WY2007–WY2008. The bars represent mean values for each period while the spreader lines represent the range of annual values. The inflow FWM TP was higher in WY2007–WY2008, but the inflow volume and inflow TP load were about half that of previous years.

1764  
 1765  
 1766  
 1767  
 1768  
 1769  
 1770  
 1771  
 1772  
 1773  
 1774  
 1775  
 1776  
 1777  
 1778  
 1779  
 1780  
 1781  
 1782  
 1783  
 1784  
 1785  
 1786  
 1787  
 1788  
 1789  
 1790  
 1791  
 1792  
 1793  
 1794  
 1795  
 1796  
 1797  
 1798  
 1799



**Figure 5-44.** Annual flow, TP load, and FWMC TP, hydraulic and phosphorus loading rates, and outflow flow-weighted mean TP for STA-6 over the period of operation (WY1999–WY2008).

1800



1801

1802

**Figure 5-45.** Monthly TP FWMC from STA-6, Cells 3 and 5 outflow. Spikes in outflow concentrations have been observed following periods of no inflow and dry-out conditions.

1803

1804


1805

1806

1807

1808

1809



1810

1811

1812

1813

1814

1815

1816

1817

1818

1819

**Figure 5-46.** Daily mean water depth in STA-6, Cells 3 and 5. Red areas indicate depths that were below mean ground elevation.

1820

1821

1822

1823

1824

1825

1826

1827

1828

1829

1830

1831

1832

1833

1834

1835

1836

1837

1838

1839


1840

1841

1842

1843

1844



**Figure 5-47.** Effects of dry-out conditions in STA-6 performance: (A) duration of dry-out period in WY2007–WY2008 compared to WY1999–WY2006; and (B) annual outflow FWM TP as affected by the duration of dry-out conditions.



1845  
1846  
1847  
1848

**Table 5-33.** Peak outflow load and concentrations observed after periods of no inflow and low stage conditions.

Date	Outflow Flow (ac-ft)	Outflow TP Load (mt)	Outflow FWMC TP (ppb/month)
Jun-05	5	0.002	248
Jul-05	1007	0.191	153
Jul-06	2708	0.513	154
Aug-07	139	0.019	112

1849  
1850


1851 Stage data indicate that the water levels within the treatment cells fluctuated widely within  
1852 and among years. During the dry season in almost every year, water levels fell below the ground  
1853 level in both cells (**Figure 5-46**). The marsh water depth was estimated by averaging the stage  
1854 data measured at the inflow and outflow structures, then subtracting the average ground elevation.  
1855 A scatter plot of dry out duration and outflow TP concentrations shows a moderate correlation ( $r=$   
1856 0.61) between these two variables (**Figure 5-47**).

1857 Nutrient analysis of the soil collected in November 2008 from 0-10 cm cores from Cells 3  
1858 and 5 shows that the soil TP ranged from 98–1,880 mg/kg (**Figure 5-48**). These concentrations  
1859 are considered to be moderately high and P flux from the sediment into the water column may  
1860 have contributed to the increases in surface water concentrations. During dry-out conditions, the  
1861 rate of soil mineralization greatly increases and consequently results in spikes in TP concentration  
1862 upon rehydration.

1863 The analysis of the performance data indicates that the decreased performance over the last  
1864 two years was probably related to the duration of dryout. In addition, severe dry-out conditions  
1865 influenced vegetation condition and coverage. The vegetation in Cell 5 is a mixture of cattail and  
1866 grasses at inflow locations and SAV at outflow regions while Cell 3 is mostly a mixture of  
1867 sawgrass and willow. During the extended drought periods, there was visible browning  
1868 throughout Cells 3 and 5, indicating plant stress in some areas. Decomposing biomass from  
1869 severely affected vegetation is suspected to have contributed to the spike in TP concentrations  
1870 upon rehydration. Also, aerial inspection during dry conditions revealed a shift of vegetation from  
1871 wetland to mainly terrestrial plant species, especially in Cell 5. When the treatment cells were  
1872 reflooded, these terrestrial plants died and decomposed upon rehydration contributing phosphorus  
1873 to the surface water. In STA-6, the first flush following dry-out conditions shows the relatively  
1874 large outflow TP concentrations peak for one to two months after rehydration. The duration of  
1875 dry-out conditions has increased in WY2007, WY2008, and WY2009. The lack of sufficient  
1876 inflows to maintain hydrated conditions for viable wetland (treatment) vegetation was found to  
1877 have negative impacts on performance, particularly in this STA.

1878

1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904



**Figure 5-48.** Soil TP concentrations at 0-10 cm layer collected in STA-6 on November 2008. The average soil TP concentration ranged from 98–1,880 mg/kg in Cells 3 and 5.

1905 **TEMPORAL CHANGES IN COVERAGE AND DENSITY OF CATTAIL**  
 1906 **IN SELECTED EMERGENT AQUATIC VEGETATION CELLS BASED**  
 1907 **ON AERIAL IMAGERY**

1908 Vegetation is known to have a major role in water quality improvement in constructed  
 1909 treatment wetlands through reduction in water velocity, thereby allowing suspended particles to  
 1910 settle (Brueske and Barrett, 1994), and through nutrient uptake (Reddy and DeBusk, 1985).  
 1911 Vegetation in treatment wetlands also influences microbial processes by increasing oxygen  
 1912 availability in the rhizosphere (Allen et al., 2002), releasing exudates like carbohydrates and  
 1913 amino acids (Brix, 1997; Coleman et al., 2001), and providing additional surfaces for growth and  
 1914 proliferation of microbial populations (Wetzel, 1990).

1915 However, there have been relatively limited studies on long-term vegetation dynamics in  
 1916 treatment wetlands (Chimney et al. 2000; Luckeydoo et al., 2002, Ray and Inouye 2007).  
 1917 Changes in vegetation in the STAs have been documented in vegetation maps derived from aerial  
 1918 photographs and (Nick Miller, Inc., 2003 and 2005; Pickett Surveying & Photogrammetry, 2006),  
 1919 but these maps have not been quantitatively analyzed. Chimney et al. (2000) reported changes in  
 1920 vegetation coverage in the Everglades Nutrient Removal Project from 1993 to 1998 and observed  
 1921 loss in cattail coverage in portions of some treatment cells. Those changes in vegetation coverage  
 1922 did not have an observable impact on P removal efficiency of the treatment wetland.

1923 The objective of this study was to quantify changes in vegetation aerial coverage and density  
 1924 in terms of normalized difference vegetation index (NDVI) as a surrogate for density of cattail  
 1925 communities in three EAV treatment cells in the STAs during a multiyear POR. This analysis will  
 1926 provide insight for future vegetation management strategies in the STAs.

1927 The study sites used in this analysis, STA-1E, Cells 5 and 7, and STA-3/4, Cell 1A, have  
 1928 been managed as an EAV system and were dominated by cattail. STA-1E was initially flooded in  
 1929 summer 2004 and it began start-up in September 2004. STA-3/4 began start-up in October 2003  
 1930 and achieved full flow-through operation in September 2004. The study sites were selected due to  
 1931 the fact that these cells have experienced numerous extended periods of deepwater conditions  
 1932 (i.e., greater than 3 feet) during calendar years 2004–2009.

1933 Twelve 1/16 acre quadrats in both Cells 5 and 7 of STA-1E and eight 1/16 acre quadrats in  
 1934 the northern one-third of Cell 1A of STA-3/4 (**Figure 5-49**) were selected for analysis from aerial  
 1935 photographs taken on February 2005, March 2006, April 2007, and April 2008.

1936 The NDVI value of cattail (dimensionless) in each quadrat was calculated based on the  
 1937 intensity of aerial imagery bands with the following equation:

$$NDVI = \frac{(NIR - Red)}{(NIR + Red)}$$

1938 where, NIR= intensity of near infrared band and Red = intensity of red band in the subject  
 1939 imagery (Jensen, 2004). The NDVI values output by the above equation and analyzed in this  
 1940 study were averaged within the selected 1/16 acre quadrats.

1941 The Raster Calculator in ESRI's ArcGIS Spatial Analyst Extension was employed to  
 1942 calculate the NDVI based on the four consecutive years of high resolution (< 2 ft ground  
 1943 resolution) aerial imagery. The NDVI ranges from -1.0 to +1.0, with negative values indicative  
 1944 of clouds and water, positive values near zero suggestive of bare soil, and higher positive values  
 1945 indicative of sparse (0.1 to 0.5) to dense (0.6 and above) green vegetation.

1946 The area of cattail in each cell dominance was defined by examining existing vegetation  
 1947 maps and/or digitizing the annual aerial images from 2005 to 2008. Acreages corresponding to

1948 each year's cattail dominance extent were obtained from the resultant vector files. The vector  
 1949 files of each year's cattail dominance area were then geometrically intersected using the  
 1950 "Intersect" tool in ArcToolbox to establish the area of dominance common to all four years – the  
 1951 area of cattail persistence. Quadrats for NDVI calculation were sited within the area of cattail  
 1952 persistence in the three study areas cells.


1953 Cattail coverage was calculated as a percentage of cell area as well as a percentage of total  
 1954 emergent vegetated area. Emergent vegetation extent was obtained by unsupervised classification  
 1955 utilizing ERDAS Imagine, a remote sensing software application. An initial 40-class  
 1956 classification scheme was re-classed to two groups (open water and emergent vegetation) and  
 1957 further processed using other ERDAS tools. The classified raster image was converted to a vector  
 1958 file for analysis, display, and acreage calculation.

1959 Differences in the NDVI value among years in each cell were analyzed with one-way  
 1960 analysis of variance (ANOVA) at  $\alpha < 0.05$ . Differences among years were tested using a post hoc  
 1961 Tukey's HSD (Honestly Significant Difference) test.

1962 Cattail coverage as a percent of Cell 5 surface area greatly increased from calendar years  
 1963 2005 to 2008, reaching 67 percent in 2008 (**Figure 5-50**). Annual mean NDVI values differed  
 1964 significantly (**Table 5-33**). Average NDVI value in the 12 quadrats decreased from 0.37 in 2006  
 1965 to 0.13 in 2008 (**Figure 5-51**).


1966

1967



1968 **Figure 5-49.** Locations of selected quadrats in STA-1E, Cells 5 and 7, and  
 1969 STA-3/4, Cell 1A. Labeled points such as P1 and P3 indicate selected quadrats.  
 1970

1971



1972

**Figure 5-50.** Changes in cattail aerial coverage in STA-1E, Cell 5, from 2005–2008. Note that cattail community was not present in Cell 5 in 2005 when the aerial photograph was taken.

1976

1977

1978

1979

1980


**Table 5-33.** Results of one-way analysis of variance (ANOVA) comparing yearly normalized difference vegetation index (NDVI) values of cattail communities in STA-1E, Cells 5 and 7, and STA-3/4, Cell 1A, from 2005–2008.

1981

1982

STA Cells	Source	DF	SS	Mean square	F values	Pr>F
STA-1E Cell 5	Year	2	0.3495	0.1747	57.91	<0.0001
STA-1E Cell 7	Year	3	0.2526	0.0843	24.80	<0.0001
STA-3/4 Cell 1A	Year	3	0.0941	0.0314	10.12	<0.0001

1983



1984 **Figure 5-51.** Individual NDVI values for cattail as a function of year in STA-1E, Cell  
 1985 5, during 2005–2008. Each line represents a 1/16 acre quadrat, labeled P1 to P12.  
 1986 Years with different letters were significantly different from each other. Note that  
 1987 cattail was observed in Cell 5 in 2005.

1988


### 1989 **Cattail Coverage and Normalized Difference Vegetation Index** 1990 **Values in STA-1E, Cell 7**

1991 Cattail coverage in STA-1E, Cell 7, increased over the four years following the startup of this  
 1992 STA in 2004. The cattail cover changed only slightly from 2005 to 2006 but subsequently  
 1993 increased to approximately 55 percent in 2007–2008 (**Figure 5-52**).

1994 The NDVI value of cattail among the four years significantly differed in Cell 7 (**Table 5-33**).  
 1995 The average of the NDVI values in the 12 quadrats significantly increased from 0.12 in 2005 to  
 1996 0.31 in 2006 and subsequently decreased to 0.22 in 2007 and to 0.16 in 2008. There was no  
 1997 significant difference in the NDVI value between 2005 and 2008 (**Figure 5-53**).


1998

1999



**Figure 5-52.** Changes in cattail coverage in STA-1E, Cell 7, from 2005–2008.

2000  
2001  
2002  
2003  
2004



**Figure 5-53.** Individual NDVI values for cattail as a function of year in STA-1E, Cell 7, from 2005–2008. Years with different letters were significantly different each other.

2005  
2006  
2007  
  
2008  
2009


2010 **Cattail Coverage and Normalized Difference Vegetation Index**  
 2011 **Values in STA-3/4 Cell 1A**

2012 Cattail coverage in Cell 1A changed slightly in the first two years from 2005 to 2006 but  
 2013 subsequently decreased to approximately 41 percent in 2007 and increased to the previous level  
 2014 in 2008 (**Figure 5-54**).

2015 The NDVI value significantly differed in Cell 1A over the four years (**Table 5-33**). The  
 2016 average NDVI value for eight quadrats significantly increased from 0.20 in 2005 to 0.27 in 2006  
 2017 and subsequently decreased from 0.13 in 2007 to 0.11 in 2008. There was no significant  
 2018 difference in the NDVI value between 2007 and 2008 (**Figure 5-55**).

2019


2020



2021 **Figure 5-54.** Changes in cattail coverage in selected northern  
 2022 one-third area of STA-3/4, Cell 1A, from 2005 to 2008.

2023





2024 **Figure 5-55.** NDVI values of cattail communities in the northern one-third of  
 2025 STA-3/4, Cell 1A, during 2005–2008. Each line in the graph designates a 1/16 acre  
 2026 quadrat, labeled P1, P3, P5, P7, P11, P14, P17, and P18. The letters above the data  
 2027 points indicate significant difference among the years; data points with the same  
 2028 letter are not significantly different.

2029

2030 Results indicate that interpretation of the emergent vegetation condition in a cell should not  
 2031 only take into account the amount of area covered, but also the density, i.e., NDVI values. The  
 2032 coverage assessment includes the aerial extent of vegetation in a cell regardless of vegetation  
 2033 conditions while the NDVI value is indicative of live green vegetation. While cattail coverage  
 2034 generally shows an overall increase or even a minimal decrease over the past four years in  
 2035 STA-1E, Cells 5 and 7, and STA-3/4, Cell 1A, the NDVI value varied.

2036 The pattern of the NDVI values calculated is consistent with field observations in these cells  
 2037 during the study period. The significant decrease in NDVI values from 2006 to 2007 and 2008  
 2038 may reflect the impacts on emergent communities of the severe two-year drought followed by  
 2039 long periods of high water conditions. In general, the results of this study suggest that the NDVI  
 2040 is a promising surrogate for monitoring the dynamics of cattail communities and as a measure of  
 2041 extreme weather events impacts on vegetation.

2042 This study is an initial attempt to apply the NDVI as an indicator of vegetation density in the  
 2043 STAs. Further investigation will attempt to correlate vegetation index values with actual  
 2044 ground-based vegetation density measurements. Ground measurements taken contemporaneously  
 2045 with remotely-sensed imagery can cross-validate each density detection method. Once validated  
 2046 and established, this methodology may be used in future monitoring of vegetation dynamics in  
 2047 the STAs.

2048

---

## STA RESEARCH AND OPTIMIZATION STUDIES

---

2049 This section also reports on the work being completed pursuant to PDE component of  
2050 the Long-Term Plan. The following summarizes the research projects initiated or ongoing in  
2051 WY2009 that have been designed to strengthen understanding about the mechanisms that control  
2052 STA performance. These include vegetation surveys, soil sampling, monitoring of newly  
2053 rehabilitated STA cells, assessment of floc soil biogeochemistry, and several large-scale  
2054 experiments that examined biomass effects on SAV establishment and the influences of  
2055 hydrologic extremes on cattail growth and survival to help identify stress indicators.

2056

### PHYSIOLOGICAL RESPONSE OF CATTAIL TO 2057 DROUGHT CONDITIONS

2058 Wetlands may experience periods of dry conditions when the vegetation within the wetland  
2059 will experience stress. The objective of this experiment was to examine the response of cattails to  
2060 varying water deficient conditions. Cattails are a dominant emergent plant species in the STAs.  
2061 This field study was conducted in outdoor greenhouse enclosures located at the south research  
2062 site at STA-1W. Cattail harvested from the adjacent treatment cell (Cell 1B) was planted in large  
2063 pots constructed from 30-gallon, heavy-duty trash cans (22.5 x 22.75 in.). The experiment had  
2064 three soil moisture treatments (100 percent soil moisture [control], 70 to 85 percent soil moisture,  
2065 and < 70 percent moisture). The plants were subjected to water deficient conditions for three  
2066 months where each pot received only periodical water inflows from rain events because of  
2067 structural problems with the greenhouse enclosures. The greenhouse enclosures were fortified to  
2068 prevent rainfall from getting into the cattail pots and the pots were then subjected to a more  
2069 intense drought condition for four month. After, all pots were rehydrated to saturated water  
2070 conditions (100 percent soil moisture). At each water regime change, some pots were  
2071 destructively harvested and metabolic indicators of plant stress were measured.

2072 The study was completed in April 2009; related data are currently being processed and are  
2073 expected to be presented in future SFERs. Plant stress will be assessed based on plant survival,  
2074 plant biomass by tissue type (leaves, roots, and rhizomes), length of tallest live leaf, shoot-base  
2075 culm width, and rate of plant growth. The following physiological and biochemical parameters –  
2076 soil percent moisture; photosynthesis rate, transpiration rate, and leaf fluorescence – will also be  
2077 evaluated. Preliminary evaluation of these data have shown the following:

- 2078 • Soil moisture of 70 to 100 percent provides optimum conditions for cattail growth.
- 2079 • Rhizomes and roots extend to a depth of at least 25 in.
- 2080 • Soil moisture below 70 percent causes most of the above ground biomass to die back  
2081 (**Figure 5-56**). These plants did not flower. Pots maintained at 70 to 85 percent soil  
2082 moisture flowered earlier than the controls.
- 2083 • Below-ground tissue morphology was different among the treatments, with roots and  
2084 rhizomes growing at the top of the pot for the controls and 70 to 85 percent  
2085 treatments while pots under the most extreme drought conditions had the roots and  
2086 rhizomes extending to the bottom of the pot.
- 2087 • Physiological measurements showed little difference between control and all  
2088 treatment pots when subjected to periodic watering; changes between the treatments  
2089 were found when subjected to four-month, water-deficient conditions.
- 2090 • All plants exhibited regrowth when rehydrated. When rehydrated after four months  
2091 of dry conditions, those plants below 70 percent moisture had the highest amount of  
2092 new shoots (**Figure 5-56**).

2093  
2094



2095  
2096  
2097  
2098  
2099  
2100

**Figure 5-56.** Subjected to low water conditions, much of the above-ground biomass started to die (photo by the SFWMD). Upon rehydration, many new shoots came up after two months of saturated conditions.

2101 **Effects of Deepwater Condition on Growth, Chlorophyll Fluorescence**  
2102 **and Nutrient Composition of Cattail**

2103 Cattail is one of most dominant aquatic plant in the STAs. During the wet season, many  
2104 cattail-dominated cells in the STAs experience extended periods of deepwater conditions. The  
2105 objectives of the study were to examine the response of cattail (specifically *T. domingensis*) to  
2106 deepwater conditions, and investigate the potential of this species to recovery after experiencing  
2107 deepwater stress.

2108 The study consisted of two experimental phases: a six-week period of different flooding  
2109 depth treatments followed by a four-week recovery period. The flooding treatments included  
2110 three water depths: 1.3 ft (control water depth), 3.0 ft (moderate water depth), and 4.5 ft (extreme  
2111 water depth) above the soil surface. Following the flooding depth treatments, half of the plants  
2112 from each treatment were randomly harvested for growth and biomass measurement. The  
2113 remaining plants were used for the four-week recovery study, during which the plants were  
2114 maintained at a water depth of 1.3 ft. Photosynthesis and chlorophyll fluorescence were  
2115 measured weekly throughout the flooding depth treatment and recovery portions of the study.

2116 Moderate and extreme flooding depths significantly reduced the number of new shoots  
2117 (P value < 0.001) and total biomass (P value < 0.001) per plant (**Figures 5-57** and **5-58**).  
2118 Flooding impact in terms of new shoot growth and biomass was 4.5 ft > 3.0 ft > 1.3 ft.


2119 At the end of the four-week recovery period, cattails previously exposed to the different  
2120 flooding depth treatments showed remarkable signs of recovery in terms of the number of new  
2121 shoots and the number of live leaves per plant. However, total biomass was significantly lower  
2122 for plants from at the 4.5 ft depth treatment than for at the 3 ft depth treatment and the control  
2123 plants. There was no significant difference in total biomass between the 3 ft depth and the control  
2124 (**Figure 5-61**).

2125 During the four-week recovery, cattail plants that were stressed by extended flooding at 3.0 ft  
2126 and 4.5 ft water depths showed improved photosynthesis (**Figure 5-62**), but continued to have  
2127 lower chlorophyll fluorescence (**Figure 5-63**). Chlorophyll fluorescence was significantly lower  
2128 at the 4.5 ft depth than in the control. However, there was no difference between moderate  
2129 flooding and the control.

2130 In summary, moderate and extreme flooding depths significantly reduced the number of new  
2131 shoots that emerged from parent plants, total biomass, photosynthesis, and chlorophyll  
2132 fluorescence. When the water level was reduced to 1.3 ft for four weeks (recovery phase), cattail  
2133 that was exposed to moderate flooding depth showed signs of recovery in total biomass,  
2134 photosynthesis, and chlorophyll fluorescence, while plants subjected to extreme flooding depths  
2135 did not recover their total biomass or chlorophyll fluorescence. This study indicates that impacts  
2136 to cattails from extended periods of extreme water depths could be irreversible, while those  
2137 exposed to moderate flooding depths can recover if water depth reduced to a level where  
2138 sprouting of new shoots and regrowth are encouraged. Further studies, including validation of  
2139 these findings by field observation and inclusion of more depth measurements, are needed to  
2140 determine narrower depth-duration thresholds for STA cattail vegetation.

2141

2142



2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150

**Figure 5-57.** Number of new shoots per cattail plant (*T. domingensis*) (mean ± SE) as a function of water depth following six-week duration of flooding. Bars with different letters are significantly different.

2151

2152

2153

2154

2155

2156

2157

2158

2159

2160

2161

2162

2163

2164

2165

2166


2167

2168

2169

2170


2171



**Figure 5-58.** Total biomass (mean ± SE) per cattail plant (*T. domingensis*) as a function of water depth following six-week duration of flooding. Bars with different letters are significantly different.

2172

2173




2174

**Figure 5-59.** Photosynthesis (mean  $\pm$  SE) of cattail (*T. domingensis*) during a six-week duration of flooding. Measurements were made in May and June 2008.

2175


2176

2177




2178  
2179  
2180  
2181

**Figure 5-60.** Chlorophyll fluorescence Fv/Fm (mean ± SE) of cattail (*T. domingensis*) as a function of water depth during six-week duration of flooding. Bars with different letters are significantly different.




2182  
2183  
2184  
2185

**Figure 5-61.** Total biomass of cattail (*T. domingensis*) following four week recovery. Bars with different letters are significantly different.



2186  
2187  
2188  
2189  
2190

**Figure 5-62.** Effects of previous flooding depths and recovery duration on photosynthesis of cattail (*T. domingensis*) during the four-week period of recovery from July to August 2008.



2191  
2192  
2193  
2194  
2195

**Figure 5-63.** Effects of previous flooding depth on chlorophyll fluorescence (Fv/Fm) of cattail (*T. domingensis*) during the four-week period of recovery. Bars with different letters are significantly different.




2196 **Internal Water Quality Transects in STA-1E and STA-1W**

2197 Careful monitoring of both STA-1W and STA-1E is critical, since these wetlands discharge  
 2198 to sensitive receiving waters (WCA-1 and WCA-2A), and because both treatment wetlands  
 2199 contain flow-ways that historically have exhibited markedly different treatment performance.  
 2200 Internal water quality sampling is useful for pinpointing problem areas with respect to excessive  
 2201 external TP loadings, soil phosphorus release, or vegetation community constraints. Internal  
 2202 monitoring also is useful for assessing regions of the cell that are providing exceptional treatment,  
 2203 for example to characterize the most effective vegetation community types responsible for  
 2204 phosphorus removal. For this effort, an internal water quality survey will be conducted in each of  
 2205 the STA-1E and STA-1W flow-ways during the rainy season in 2009 (WY2010).

2206 During a large flow pulse in August 2008, the District performed an internal sampling event  
 2207 to characterize the internal water column TP gradient under short hydraulic retention time  
 2208 conditions. On the day of sample collection (August 21, 2008), average daily flow into the  
 2209 Central Flow-way of STA-1E was 1,137 cfs, and the prior two-week daily inflow averaged 405  
 2210 cfs (**Figure 5-64**). Internal sampling locations are depicted in **Figure 5-65**.


2211 On this sampling date, water column TP concentrations entered STA-1E Cell 3 at 143 ppb  
 2212 and exited at 135 ppb (**Figure 5-66**). The minimal TP reduction in the cell, coupled with the high  
 2213 concentration of readily bioavailable SRP in the cell outflow indicates poor phosphorus removal  
 2214 performance in this “front-end” cattail-dominated wetland. By contrast, along the sampling  
 2215 transects within the downstream Cell 4N, which is dominated by the SAV species hydrilla and  
 2216 Southern naiad, TP concentrations declined from 115 to 29 ppb (**Figure 5-66**). Essentially, all the  
 2217 readily available SRP was removed within Cell 4N. Within the final cell in the flow-way (Cell  
 2218 4S), TP concentrations declined further, exiting the cell at 9 ppb. As noted in previous SFERs, the  
 2219 outflow TP was comprised principally of particulate P and dissolved organic P (**Figure 5-66**).

2220  
 2221  
 2222  
 2223




2224  
 2225  
 2226  
 2227  
 2228

**Figure 5-64.** Water loading into the Central Flow-way of STA-1E during August 2008. Internal samples were collected on 8/21/08.



**Figure 5-65.** Internal sampling locations in the Central Flow-way of STA-1E. Cell 3 is an EAV dominated wetland, and Cells 4N and 4S are dominated by SAV.

2229  
2230  
2231  
2232



**Figure 5-66.** Internal water column phosphorus species concentrations within the Central Flow-way of STA-1E (Cells 3, 4N, and 4S) on August 21, 2008. The inset depicts concentrations in Cell 4S, with a reduced Y-axis scale.

## 2233 **STA-2 Internal Phosphorus Storage and Stability Gradients**

2234 Sediments represent the ultimate storage reservoir for P removed from the water column  
2235 within the STAs. Because internal P loading from the underlying sediment can influence wetland  
2236 treatment efficiency, it is important to quantify the stability of P that accrues in STA sediments.  
2237 Assessments of sediment P stability along the length of the flow path will provide a better  
2238 understanding of factors that influence wetland treatment longevity, and the minimum achievable  
2239 outflow TP concentrations. The three cells of STA-2 are excellent candidates for sediment  
2240 stability characterization: the cells have been subjected to widely different P loadings, and are  
2241 exhibiting markedly different levels of P removal performance. Additionally, STA-2 is one of the  
2242 two best-performing STAs. During past years, the District has performed internal characterization  
2243 of sediments in STA-2, Cells 2 and 3 (**Figure 5-67**). Some comparisons in the chemical  
2244 characteristics of these sediments are provided below.

2245 Cell 3 is dominated by SAV, with a small region of EAV, whereas Cell 2 is dominated by  
2246 EAV (primarily cattail, with some sawgrass), with a small region of SAV. The data presented  
2247 herein address trends in surficial soils (0 to 4 cm), with Cell 3 soils sampled in 2005 and Cell 2  
2248 soils characterized in 2008. Differences noted in sediment characteristics, therefore, may be  
2249 related to differences in vegetation, and/or differences in operations since both cells were  
2250 subjected to initial flow-through conditions in 2001.


2251 Surficial soil (0 to 4 cm) TP concentrations were higher in Cell 2 than in Cell 3, potentially  
2252 due to the longer operational period of the former (seven years for Cell 2 versus four years for  
2253 Cell 3), but also possibly due to differences in plant community type. Maximum soil TP levels for  
2254 Cell 2 were found in the mid-region of the wetland, whereas a gradual decline in soil TP with  
2255 distance from the inflow was noted in Cell 3 (**Figure 5-68**). Outflow region soil TP in Cell 2  
2256 averaged 980 mg/kg, while outflow region soil TP in Cell 3, sampled three years earlier, was  
2257 approximately 580 mg/kg.

2258 Several other soil constituents exhibited little inflow to outflow gradient within the wetlands,  
2259 but differed markedly between cells (**Figure 5-69**). Average nitrogen (N) and total organic carbon  
2260 (TOC) contents were markedly higher in the emergent macrophyte-dominated wetland  
2261 (Cell 2), while bulk density and calcium contents were much higher in the SAV-dominated  
2262 system (Cell 3).

2263 By contrast, surficial soil porewater soluble reactive (SRP) concentrations exhibited a marked  
2264 spatial gradient in both wetlands, declining from 306 to 19 ppb in Cell 2 and 150 to 7 ppb in  
2265 Cell 3 (**Figure 5-70**). Porewater SRP has been used previously as an indicator of internal loading  
2266 in STA wetlands, and the observed low concentrations in outflow region soils suggests that the  
2267 soil in these zones probably are not contributing a substantial phosphorus load to the water  
2268 column. A repeat sampling effort is planned for Cell 3 in late summer 2009, which will provide  
2269 invaluable information on temporal changes in sediment chemistry in STA flow paths.

2270


2271




2272  
 2273  
 2274  
 2275  
 2276  
 2277  
 2278  
 2279

**Figure 5-67.** Surficial soils were collected along transects oriented perpendicular to flow in Cells 2 and 3 of STA 2. Zones not sampled along each transect represent regions containing sub-dominant vegetation (i.e., SAV in Cell 2; emergent vegetation in Cell 3).

2280




2281  
2282  
2283



2284  
2285  
2286  
2287  
2288  
2289

**Figure 5-68.** Surficial (0 to 4 cm depth) soil TP contents for STA-2, Cell 2 (emergent macrophyte-dominated, sampled in 2008) and Cell 3 (SAV dominated, sampled in 2005). Units are in milligrams per kilogram (mg/kg).


2290



2291  
 2292  
 2293  
 2294  
 2295  
 2296  
 2297  
 2298  
 2299  
 2300

**Figure 5-69.** Surficial soil TN, TOC, total Ca, and bulk density for STA-2, Cells 2 (emergent macrophyte-dominated, sampled in 2008) and 3 (SAV dominated, sampled in 2005). Units for TN, TOC, and total Ca are in milligrams per kilogram (mg/kg); units for bulk density are in grams per cubic centimeter (g/cc).

2301



2302  
 2303  
 2304  
 2305  
 2306  
 2307  
 2308  
 2309  
 2310  
 2311

**Figure 5-70.** Surficial soil porewater soluble reactive P contents for STA-2, Cell 2 (emergent macrophyte-dominated, sampled in 2008) and Cell 3 (SAV dominated, sampled in 2005). Units are in parts per billion (ppb), or micrograms per liter (µg/L).

## 2312 Phosphorus Fractions in Floc and Surface Soil Layers in STA-2, Cell 4

2313 One critical aspect in managing the STAs is maximizing the capacity to store phosphorus. A  
 2314 large portion of the runoff P treated by the STAs is stored in the soils via physical, chemical, and  
 2315 biological processes. The characterization of the different P pools stored in the soils is an  
 2316 important step to establish baseline conditions in order to track changes in P storage over time.  
 2317 This soil characterization was conducted to determine the current labile and non-labile pools of P  
 2318 in soils from STA-2, Cell 4. STA-2, Cell 4 (1,902 acres), is the newest of the four cells in this  
 2319 STA and became operational in 2008.

2320 In March 2009, 10 stations were sample in STA-2, Cell 4, for baseline phosphorus-  
 2321 fractionation (**Figure 5-71**). All samples sites were selected from the District's routine soil  
 2322 sampling grid to include locations in a spatial distribution manner from the inflow to the outflow  
 2323 of the cell. Samples were collected by driving a 10 cm diameter, stainless steel corer into the soil  
 2324 profile. Each core was sectioned into the floc layer (when present) and 0-10 cm of the  
 2325 consolidated soil layer. Samples were cleared of vegetation roots, placed in water-proof plastic  
 2326 bags, and placed in an ice cooler for transport to the laboratory. Sediment samples were collected  
 2327 at all ten sites, while floc was present and collected at only eight sites. Samples were processed  
 2328 and analyzed by DB Environmental Laboratories, Inc.

### 2329 *Results and Discussion*

2330 Soil analysis results generally indicated higher concentrations of TP ( $736 \pm 195$  mg kg<sup>-1</sup>) in  
 2331 the floc layer than in the underlying 0-10 cm soil layer ( $514 \pm 129$  mg kg<sup>-1</sup>) (**Table 5-71**). Bulk  
 2332 density of the floc material is nearly half of the consolidated soil's bulk density. Results from the  
 2333 P fractionation analysis indicate that even after only one year of operation, the floc layer shows  
 2334 higher levels of inorganic P than the 0-10 cm soil layer. The largest fraction (approximately 54  
 2335 percent of TP) in the 0-10 cm soil layer was in the form of residual P, a form that is not readily  
 2336 released into the water column or readily available for rooted plant uptake (**Figure 5-72**). The  
 2337 organic P fraction comprised 28 and 23 percent of soil TP in the floc and 0-10 cm layers,  
 2338 respectively.

2339

2340

2341 **Table 5-34.** Soil properties and concentration of the different inorganic (Pi)  
 2342 and organic (Po) phosphorus fractions from floc and 0-10 cm soil layer in STA-2,  
 2343 Cell 4. Values represent mean  $\pm$  one standard deviation. Floc depth sites n=8  
 2344 samples, sediment 0-10 cm layer n=10 samples.

	n	Depth	BD	Labile-Pi	FeAl-Pi	CaMg-Pi	Po	Residue TP	Soil TP
		cm	g/cc	mg kg <sup>-1</sup>	mg kg <sup>-1</sup>	mg kg <sup>-1</sup>	mg kg <sup>-1</sup>	mg kg <sup>-1</sup>	mg kg <sup>-1</sup>
Floc	8	5.7 $\pm$ 3.1	0.1 $\pm$ 0.04	3.7 $\pm$ 3.8	49 $\pm$ 27	212 $\pm$ 38	205 $\pm$ 72	267 $\pm$ 86	736 $\pm$ 195
Soil	10	0-10	0.26 $\pm$ 0.07	1.2 $\pm$ 1.0	26 $\pm$ 9	89 $\pm$ 40	118 $\pm$ 50	269 $\pm$ 77	514 $\pm$ 129

2345

2346



2347  
 2348  
 2349  
 2350  
 2351  
 2352  
 2353  
 2354  
 2355  
 2356  
 2357  
 2358  
 2359  
 2360  
 2361  
 2362  
 2363  
 2364  
 2365  
 2366




Figure 5-71. Soil sampling locations in STA-2, Cell 4.




Figure 5-72. Relative distribution of inorganic (Pi) and organic (Po) phosphorus fractions in soils from STA-2 Cell 4 in the floc layer and the 0-10 cm soil layer. CaMg-Pi = calcium- and magnesium-bound phosphorus; FeAl-Pi = iron and aluminum-bound phosphorus; L-Pi = labile inorganic phosphorus; Po = organic phosphorus.

## 2367 **STA-2 Internal Water Quality**

2368 Internal water quality measurements are being performed in the four flow-ways of STA-2 to  
2369 characterize water column P removal profiles as a function of vegetation type, flow, P loading,  
2370 and season. Monitoring within Cell 3 has been performed since 2003, and monitoring in Cells 1  
2371 and 2 was initiated in 2007. Internal characterization of Cell 4 water column gradients began in  
2372 2008. The data have demonstrated that these internal profiles are useful for identifying regions of  
2373 poor performance, and that they also help define the potential for selected flow-ways to achieve  
2374 target outflow concentrations.

## 2375 **Characterize Hydraulic Resistance of Emergent Macrophytes** 2376 **in STA-2, Cell 2**

2377 Many of the EAV-dominated STA cells contain dense stands of vegetation, consisting of both  
2378 living and dead plant material. Under high flow events, it is thought that the hydraulic resistance  
2379 created by the dense vegetation contributes to the high water depths observed in the front-end of  
2380 many of the STA flow-ways. For this project, the District has deployed pressure transducers at  
2381 various locations along the wetland flow path in STA-2, Cell 2. These instruments are being used  
2382 to characterize water stage changes within the wetland as a function of flow regime. These data  
2383 will help clarify hydraulic resistance for STA emergent communities, and also provide  
2384 background information that may facilitate selected vegetation management practices (i.e.,  
2385 burning to thin dead cattail biomass; conversion of cattail to SAV) in STAs. This project started  
2386 in 2008; the end date has yet to be determined and will depend on the utility of findings.

## 2387 **STA-1W Biomass and Decomposition Study**

2388 In 2006 and 2007, major efforts were conducted to rehabilitate multiple cells in STA-1W in  
2389 order to make the environmental conditions more favorable for vegetation establishment and  
2390 improved P removal performance. SAV serves as the “polishing” or downstream cells in the  
2391 flow-way of the STAs. As part the rehabilitation efforts, agricultural rice (*Oryza sativa*) was  
2392 planted in Cells 1B, 2B, 4, and 5B. Rice was planted as an interim vegetation to help reduce the  
2393 resuspension of sediments into the water column, thereby encouraging SAV establishment.  
2394 Rice was selected because it was readily available, inexpensive, and easily planted using  
2395 standard farming practices. Details of rice planting were provided in the 2008 and 2009 SFERs –  
2396 Volume I, Chapter 5.

2397 With a focus on rice, cattail, barnyard grass (*Enchinocloa walteri*), and common grass  
2398 (*Paspalum distichum*), this study was conducted to (1) evaluate and compare the amount of  
2399 biomass from rice versus other common emergent aquatic vegetation species, and (2) to quantify  
2400 the decomposition rates for each species.

## 2401 **Biomass Estimation**

2402 Biomass was harvested for each species, excluding cattail, using 0.25 m<sup>2</sup> quadrats to evaluate  
2403 the amount of biomass per species present at each sampling point. Key elements are as follows:

- 2404 1. Three 0.25 m<sup>2</sup> plots were randomly selected in STA-1W for each species.
- 2405 2. All materials contained within each plot were harvested, including above-ground  
2406 (leaves and stems) and below-ground (roots and rhizomes) components.
- 2407 3. Above-ground and below-ground were separated, washed, and dried at 60 °C.
- 2408 4. Dry weights were recorded for each plot collected and recorded accordingly.
- 2409 5. Biomass was calculated, where: Biomass/M<sup>2</sup>= Weight of plant material/0.25
- 2410 6. Tukey’s HSD test was used to verify that significant differences in biomass  
2411 estimations between species existed when ANOVAs were significant.

## 2412 **Decomposition**

2413 Plant material obtained through the biomass estimation section of the study was used to  
2414 conduct the decomposition portion of the study. Three separate locations within STA-1W were  
2415 selected for field incubation, i.e., Cells 2B, 4, and 1B. It should be noted that ideally this  
2416 incubation should have been done using air-dried or fresh biomass. Key elements are as follows:

- 2417 1. A total of 10 to 20 grams of dried material from each species was placed into 45  
2418 individually numbered mesh bags for deployment.
- 2419 2. All samples were weighed to obtain a baseline weight prior to deployment.
- 2420 3. Three plots were used as replicate experimental units.
- 2421 4. Within each experimental unit, a total of 15 bags for each species were submerged to  
2422 mimic natural conditions.
- 2423 5. Three bags of each species were collected from each experimental unit (one from  
2424 each plot) at days 31, 61, 186, 295, and 389 after the start of incubation.
- 2425 6. After each sampling event all materials were washed and dried at 60°C for a period of  
2426 two weeks. Each bag of dried material was then weighed.
- 2427 7. Decomposition rates were calculated as percent biomass remaining for each sampling  
2428 event and was calculated, where:  
2429 
$$\text{Percent Remaining} = ((100 - (\text{Initial Weight} - \text{Final Weight})) / \text{Initial Weight}) * 100$$
- 2430 8. Tukey's HSD test was used to verify that significant differences in biomass  
2431 estimations between species existed when ANOVAs were significant.

## 2432 **Results**

2433 Results show that rice produced the least amount of total plant biomass when compared to  
2434 both barnyard grass and common grass (**Figure 5-73**). No significant differences were observed  
2435 between the three species in terms of below ground biomass. Biomass in leaf material was  
2436 significantly higher in the *Paspalum* species compared to both rice and *Echinochloa*. A  
2437 significant portion of the rice and the *Echinochloa* plants are made up of stem material, while the  
2438 *Paspalum* was completely made up of leafy material. Overall biomass per square meter was  
2439 significant different amongst all three species with *Paspalum* having the highest total biomass  
2440 followed by the *Echinochloa* species. Rice contained the least amount of biomass in this study.

2441 The results from decomposition study indicated that rice decomposes in a much shorter  
2442 timeframe than *Echinochloa*, *Paspalum*, and *Typha*. Approximately 70 percent of the rice  
2443 biomass decomposed in 30 days, 95 percent by six months, and fully decomposed by 210 days  
2444 (**Figure 5-73**). Barnyard grass and common grass biomass decomposed at virtually the same  
2445 rate with approximately 50 percent of the biomass remaining after 30 days and less than  
2446 20 percent remaining after 295 days. Cattail decomposition rates were significantly lower  
2447 (P value  $\leq 0.0001$ ) than the other species; this finding is in line with other decomposition studies  
2448 conducted on this species (Pietro and Chimney, 2006). Approximately 70 percent of cattail  
2449 biomass remained after 30 days and about 30 percent remained after 289 days. After 186 days,  
2450 the decomposition rates for cattail and the two grass species are not significantly different.

## 2451 **Discussion**

2452 In this study it was found that (1) rice contained less biomass in a per unit area than the other  
2453 two grass species tested in this study, and (2) the decomposition rate of the rice plant is  
2454 significantly faster than that of *E. walteri*, *P. distichum*, and *T. domingensis*. These findings are  
2455 expected to be useful when planning future rehabilitation efforts in the STAs where the SAV  
2456 community may be struggling to survive due to sediment resuspension into the water column.  
2457 Previous studies, as described in 2008 and 2009 SFERs – Volume I, Chapter 5, have proven that  
2458 *O. saptiva* is an optimal tool used to reduce problems with the resuspension of sediments into the

2459 water column in SAV cells. Other common emergent species may provide a similar function as  
 2460 rice; however, it is not desired for such species to persist for long periods of time throughout the  
 2461 SAV cells. Therefore, the fact that rice is an annual plant, has a relatively low amount of biomass,  
 2462 and decomposes in a relatively short period of time, makes this species optimal for use in future  
 2463 rehabilitation efforts in SAV cells within the STAs.

2464  
 2465

2466

2467

2468

2469

2470


2471

2472

2473

2474

2475



2476  
 2477

**Figure 5-73.** Above-ground and below-ground biomass estimations per square meter of area planted with rice.


2478

2479

2480

2481

2482



**Figure 5-74.** Percent of biomass remaining for each species for rice, barnyard grass and common grass, and cattail over time under submerged conditions.

2483 **Effects of Water Column Calcium Concentrations on Phosphorus**  
2484 **Removal by a Mesocosm-Scale STA Flow-way**

2485 In this study, the District is evaluating whether the approximately twofold higher calcium  
2486 (Ca) levels found in Everglades Agricultural Area (EAA) farm runoff, in comparison to Lake  
2487 Okeechobee waters, can lead to lower outflow TP concentrations from a sequence of cattail,  
2488 SAV, and calcareous periphyton mesocosms operated at a low P loading rate. To date, Ca levels  
2489 appear to exert a slight influence on the minimum attainable outflow TP levels in the system, with  
2490 low [about 35 milligrams per liter (mg/L)] and high (70 mg/L) Ca systems achieving outflow TP  
2491 concentrations of 20 and 16 ppb, respectively. As part of this effort, internal profiles in water  
2492 column Ca concentrations are being measured in several full-scale STA flow-ways, as a function  
2493 of vegetation community type and hydraulic loading rate.

2494 **Vegetation Conversion Status Updates**

2495 ***STA-3/4, Cell 1B, Conversion***

2496 Per revision to the Long-Term Plan, conversion of STA-3/4, Cell 1B, from an emergent to an  
2497 SAV marsh is intended to occur incrementally while keeping the cell online. The ongoing  
2498 conversion requires elimination of the cattail and willow (*Salix caroliniana*) that cover most of  
2499 the cell, and subsequent establishment of one or more of the desirable SAV species (i.e., southern  
2500 naiad, muskgrass, or pondweed) for the STAs. Initial conversion measures were taken in  
2501 November 2005 when an herbicide was applied aerially to 650 acres of cattail and willow in the  
2502 southernmost portion of the cell. The second phase of the incremental conversion was initiated on  
2503 December 6, 2007, when an aerial herbicide treatment was applied to an additional 800 acres of  
2504 cattail immediately north of the first treatment area. In October and November 2008, another 400  
2505 acres of cattail were treated. These three increments have cumulatively treated EAV cover on  
2506 53 percent of the effective treatment area of Cell 1B.

2507 Due to limited natural colonization of SAV following the initial herbicide treatment, in July  
2508 2007 SAV was inoculated (via helicopter) at 11 sites in the southernmost section of the cell. As a  
2509 result of these founder site inoculations and subsequent natural colonization, SAV has been  
2510 established and presently covers approximately 35 percent of Cell 1B based on a qualitative  
2511 survey in July 2009. This increase from the previous year (i.e., based on the 2008 survey,  
2512 SAV was covering an estimated 15 percent of the cell) indicates that the incremental conversion  
2513 strategy has been successful and will continue to proceed with an iterative adaptive  
2514 implementation process.

2515 **VEGETATION MANAGEMENT RESEARCH**

2516 **Submerged Aquatic Vegetation Establishment Research**

2517 Several studies have been initiated to facilitate SAV establishment and conversion efforts and  
2518 to investigate alternative vegetation management strategies for sustaining STA performance.  
2519 Effects of dead and decomposing cattail litter on rates of “natural” (i.e., unassisted) colonization  
2520 of SAV and periphyton are being evaluated in experimental 480 m<sup>2</sup> (12 m x 20 m) plots that  
2521 were established in a dense cattail stand within two of the emergent vegetation strips in STA-3/4,  
2522 Cell 2B, in spring 2007. Bimonthly random standing-crop biomass sampling has indicated no  
2523 natural colonization of SAV has occurred in the two-year period following the herbicide  
2524 treatments. These results suggest that the dense untreated cattail above the treated plots (i.e., the  
2525 emergent vegetation strip) may be impeding influx of SAV propagules from established beds  
2526 upstream and thereby precluding establishment of SAV. Although periphyton colonization of  
2527 dead (treated) cattail during the summer of 2007 likely provided an interim P uptake pathway

2528 following the treatments, very little periphyton was found in treated plots after the decomposing  
2529 cattail litter sank in the water column (i.e., during sampling periods after February 2008).

2530 Preliminary conclusions from the vegetation strip study in Cell 2B appear to be supported by  
2531 a complementary study in the southern section of STA-3/4, Cell 1B, where the incremental  
2532 conversion of emergent vegetation to SAV has been ongoing since November 2007. Sample data  
2533 from study plots (36 m<sup>2</sup>) in Cell 1B indicates that SAV propagules from established beds  
2534 upstream of the 1,850 acres of treated cattail has led to comparable average ( $\pm$  standard error)  
2535 SAV cover in uninoculated study plots ( $46 \pm 9$  percent) and in plots that had been inoculated  
2536 with muskgrass and Southern naiad ( $49 \pm 5$  percent).

2537 Results of these two studies are expected to clarify the time frame required for SAV  
2538 conversions and associated need for SAV inoculations and/or measures to remove dead emergent  
2539 plant biomass (through harvesting, tilling, fire etc.). These and other associated planned studies  
2540 may have implications for alternative vegetation management strategies such as the potential  
2541 value of rotation of emergent and SAV cover to maintain sustainability of STA cells.

### 2542 **Bulrush Planting**

2543 An investigation was undertaken to evaluate the potential for establishing giant bulrush  
2544 (*Schoenoplectus californicus*) in the front ends of STAs where water depths during high inflow  
2545 periods have resulted in conditions that have not been conducive to sustained vegetative growth.  
2546 To evaluate this potential vegetation management option for the STAs, giant bulrush was planted  
2547 in unvegetated areas immediately downstream of inflow structures in STA-1E, Cell 7; STA-2,  
2548 Cell 3; and STA-3/4, Cell 1A.


2549 In May 2007, approximately 1,100 giant bulrush culms were planted in 20 x 20 m plots at  
2550 each of these three locations, which provided an initial density of 2.8 bulrush culms m<sup>2</sup>. Water  
2551 depths on planting dates were 11-12 cm in the plot in STA-3/4, Cell 1A; 30-31 cm in STA-1E,  
2552 Cell 7; and 37-38 cm in STA-2, Cell 3. Post planting monitoring was conducted in  
2553 July, September, October, and November 2007, and in January, March, May and July 2008  
2554 (**Figure 5-75**). During each of these sampling dates, the number of bulrush culms was counted in  
2555 10 randomly selected 1 m<sup>2</sup> quadrats in each plot. July 2007 sampling indicates initial post-  
2556 planting mortality was 29 percent in STA-1E, Cell 7, 57 percent in STA-2, Cell 3, and 64 percent  
2557 in STA-3/4, Cell 1A. Culm densities remained constant during August and September; by  
2558 January 2008, vegetative reproduction by surviving plants increased mean ( $\pm$  standard error)  
2559 densities to  $5.7 \pm 2.8$  culms in STA-3/4, Cell 1A, and  $13.9 \pm 4.5$  culms in STA-1E, Cell 7. Rates  
2560 of bulrush expansion in these cells increased through subsequent sampling dates and mean  
2561 densities reached  $28.5 \pm 9.7$  culms m<sup>2</sup> in STA-3/4, Cell 1A, and  $117.7 \pm 14.8$  culms m<sup>2</sup> in  
2562 STA-1E, Cell 7, in July 2008. Establishment of bulrush was least successful in STA-2, Cell 3,  
2563 where survival from initial planting provided patchily distributed culms that attained a mean  
2564 density of  $11.6 \pm 8.4$  culms m<sup>2</sup> during the last sampling date in 2008.

2565 Water depth regimes at these locations were determined by mean plot elevations and daily  
2566 tailwater stage data at the nearest gauging station (i.e., S-373B for STA-1E, Cell 7; G-333C for  
2567 STA-2, Cell 3; and G-374E for STA-3/4, Cell 1A). Mean plot elevations were derived by  
2568 subtracting the mean of 20 random depth measurements, which were taken from each plot on  
2569 June 8 and 17, 2007, from the tailwater stage at the reference gauge on these dates. Based on  
2570 these plot elevations and stage hydrographs from these gauging stations, four flow events during  
2571 the period from the date of planting through the last sampling date in July 2008 resulted in depths  
2572 at planted bulrush plots (**Figure 5-76**) that were substantially higher than target depths for these  
2573 STAs. These events resulted in depths  $> 90$  cm for 54 days in the bulrush plot in STA-2, Cell 3,  
2574 37 days in the plot in STA-3/4, Cell 1A, and 20 days in the plot in STA-1E, Cell 7 (**Figure 5-77**).

2575       The relative success of bulrush plantings at these sites, as indicated by relative culm densities  
2576 one year after planting, appeared to be correlated with differences in depth regimes at the three  
2577 plot locations. Highest culm densities, for example, were attained in STA-1E, Cell 7, where high  
2578 water depths occurred for only a brief time period, while STA-2, Cell 3, had deep water for the  
2579 longest period of time and the lowest densities of bulrush culms during the last sampling date.  
2580 However, there were differences in soil characteristics at the three plot locations that also could  
2581 have led to the differences in the rate in which planted bulrush established and spread. Soils at the  
2582 bulrush planting site in STA-2, Cell 3, where bulrush plantings were least successful, were very  
2583 dense and compact (almost peat-like), and were unlike soils in the bulrush plot in STA-3/4, Cell  
2584 1A, which consisted of soft muck. The most successful planting site, STA-1E, Cell 7, had a sandy  
2585 muck soil, which visibly had a higher mineral content than soils at the other two sites.


2586       While it could not be determined if differences in depth regimes and/or soil characteristics (or  
2587 neither of these conditions) led to the differences in establishment success and subsequent  
2588 expansion rates of planted bulrush, bulrush did become established at all three sites and thereafter  
2589 showed a capability of withstanding high depth periods. These preliminary results provide  
2590 support for continued evaluation of more extensive plantings of bulrush in portions of STA cells  
2591 where periodic deep water regimes inhibit establishment and/or sustained growth of other EAV  
2592 species (e.g., cattail). Any future planting efforts should account for the likelihood of high initial  
2593 (planting) mortality, as indicated by results of this study, but should exploit the potential for high  
2594 rates of vegetative expansion by established culms. Plantings consisting of numerous, small  
2595 dispersed clumps with about 50 bulrush culms/150 m<sup>2</sup>, for example, could be used to potentially  
2596 establish bulrush over large areas of open water, which could include sufficient topographic  
2597 variability to simultaneously provide for a more rigorous evaluation of the influence of water  
2598 depth regimes on the establishment, expansion, and persistence of this species in the STAs.

2599



2600


2601 **Figure 5-75.** Post-planting monitoring measurements used to determine the success  
 2602 of the establishing giant bulrush (*Schoenoplectus californicus*) planting effort.



2603 **Figure 5-76.** Water depth regimes measured as part of the bulrush planting study.



2604



2605  
2606  
2607

**Figure 5-77.** Water depth duration curves measured to evaluate the success of the bulrush planting study.

## 2608 Submerged Aquatic Vegetation Surveys

2609 Submerged aquatic vegetation (SAV), the dominant community in downstream STA cells,  
2610 are subject to various disturbances, including herbivory, tropical cyclone winds, and excessive  
2611 loadings of nutrient or particle-laden waters. Reductions in SAV areal coverage can lead to  
2612 impaired STA performance. Because the coverage and species composition of SAV communities  
2613 can be detected only sporadically with aerial or satellite images (i.e., when the plants “top out” in  
2614 the water column), efficient ground-level survey methods must be implemented to assess  
2615 temporal changes in the spatial distribution of SAV coverage. For this effort, the District annually  
2616 performs at least one airboat survey in each of the 13 SAV-dominated STA cells. This  
2617 information will be used to develop relationships between SAV coverage, species type, and cell  
2618 treatment performance. Additionally, it will help define potential impacts of external  
2619 perturbations on SAV community health.


2620 As an example, **Figure 5-78** depicts changes in SAV coverage and speciation from  
2621 2003–2008 in STA-2, Cell 3, a well-performing STA cell. In 2003, pondweed and Southern naiad  
2622 were the dominant SAV species, with beds of hydrilla and coontail (*Ceratophyllum demersum*)  
2623 occurring in the inflow region coverage. Muskgrass was not present in the wetland at this time.  
2624 Hydrilla began to increase in spatial distribution over time, but the inflow region cover of this  
2625 plant, along with that of other SAV species, was sharply reduced by Hurricane Wilma in late  
2626 2005 (see the May 2006 survey, **Figure 5-78**). With respect to long-term fluctuations in SAV  
2627 coverage, the dominant changes that have occurred are the gradual decline in pondweed in the  
2628 cell, and increase in coverage by the non-vascular species, muskgrass. The decline in pondweed  
2629 is probably related to the gradual soil enrichment of the inflow and mid- regions of the cell, since  
2630 this species appears to prefer low water column nutrient conditions. Reasons for the gradual  
2631 expansion of muskgrass are unknown; however, in many South Florida ecosystems, *Chara* acts as  
2632 a colonizing species, rather than a component of mature SAV stands.

2633 This same monitoring approach has been utilized to characterize temporal changes in SAV  
2634 coverage in the downstream end SAV cells of STA-1E, one of the newer STAs. A total of 30, 31,  
2635 and 53 observation sites have been established within Cells 4N, 4S, and 6, respectively  
2636 (**Figure 5-79**). In March 2006, Southern naiad was the dominant SAV species in Cells 6 and 4N,  
2637 while hydrilla dominated Cell 4S. Maximum density and coverage for Southern naiad in these  
2638 cells occurred in August 2006, after which time this species exhibited a gradual decline. By  
2639 contrast, hydrilla has become the dominant SAV species in all three downstream cells. Coontail is  
2640 now the second most prominent SAV species in STA-1E, exhibiting fairly widespread coverage  
2641 in Cell 6.

2642

2643

2644




2645

2646

**Figure 5-78.** Changes in STA-2, Cell 3, areal SAV coverage from May 2003 to October 2008. Darker colors represent higher vegetation densities. SAV measurement locations are depicted by the black dots.

2647



2648

2649


2650

2651

2652

2653

Figure 5-78. Continued.



2654

2655

2656

2657

2658

2659

**Figure 5-79.** Changes in SAV cover in STA-1E from March 2006 through February 2009. These schematics depict the downstream cells of the Western (Cell 6) and Central (Cells 4N and 4S) Flow-ways.

## 2660 **Vegetation Management Strategies**

2661 The vegetation management activities in the STAs during WY2009 focused on treating  
2662 cattails and willow in STA-3/4, Cell 1B (700 acres); grasses and willow in STA-5, Cell 1A;  
2663 cattails in STA-1W, Cell 1B (100 acres) and Cell 3 (300 acres) and STA-3/4, Cell 2B (200 acres);  
2664 and willow in STA-5 Cell 1A (343 acres) and STA-6 Cell 3 (74 acres). As part of the vegetation  
2665 conversion from EAV to SAV, 300 acres of cattails were treated in STA-2, Cell 2. Appendix 5-13  
2666 presents the type and amount of herbicide used in WY2009.

## 2667 **Effects of Vegetation Management Strategies on the Establishment of** 2668 **SAV in STA-1W**

2669 A monitoring study was conducted in STA-1W Cell 5B to evaluate efficacy of four  
2670 vegetation management strategies on the reestablishment of SAV at different sites with rice,  
2671 sprangletop grass (*Leptochloa fascicularis*), barnyard grass, or miscellaneous dominant plant  
2672 species (Chen et al., 2009). This treatment cell underwent rehabilitation to mitigate damage done  
2673 to the vegetation communities after Hurricane Wilma in 2005. As part of the vegetation  
2674 reestablishment efforts, rice was planted to aid in SAV growth. The vegetation management  
2675 strategies evaluated in this study include (1) grass detritus left undisturbed, (2) grass detritus  
2676 removed to allow reestablishment of SAV from the sediment seed bank, (3) grass detritus left  
2677 undisturbed and healthy SAV transplanted directly on top of the detritus, and (4) grass detritus  
2678 removed and healthy SAV transplanted directly into the empty water column. The study was  
2679 conducted from November 2006 to December 2007. It should be noted that during this time  
2680 period the STAs, including this cell, experienced a two-year drought period which may have  
2681 affected the outcome of this experiment.

2682 Primary findings from this study are:

- 2683 • Hydrilla and coontail showed increased coverage from April to December in 2007. In  
2684 contrast, *Chara* coverage did not significantly change.
- 2685 • Vegetation management strategies significantly affected coontail areal coverage in  
2686 stations with different vegetation types. Coontail coverage in harvested stations was  
2687 higher than in stations with transplanting SAV alone. In sites with miscellaneous  
2688 dominant plant species, coontail coverage was higher in stations with grass detritus  
2689 removed and healthy SAV transplanted than in stations with other three types of  
2690 vegetation.
- 2691 • Vegetation management strategies did not influence Southern naiad or hydrilla coverage  
2692 but significantly affected *Chara* coverage. The combination of harvesting and  
2693 transplanting SAV improved *Chara* establishment.
- 2694 • Rice-dominated stations generally had higher coontail coverage than sprangletop and  
2695 barnyard grass-dominated stations.

## 2696 **Sawgrass Mesocosm Assessment**

2697 During 2006–2007, the District continued monitoring two mesocosm experiments related to  
2698 the sustainability of STA communities. The purpose of this study is to evaluate the P removal  
2699 performance of sawgrass cultured in mesocosms. In natural stands, sawgrass has been able to  
2700 achieve outflow concentrations of 10 ppb and has proven resistant to hurricane winds. To date,  
2701 the mean outflow TP concentrations from sawgrass experiment systems have averaged 23 ppb.  
2702 When the experiment is terminated, accrued soils in the sawgrass and PSTA mesocosms will be  
2703 characterized with respect to P content, and stability of the associated P. This project started in

2704 2006 and is expected to end in 2010. Further studies may be needed to validate the results of the  
2705 mesocosm study at a field-scale.

### 2706 **Effects of SAV Species on Soil Accrual Rate and Soil** 2707 **Phosphorus Stability**

2708 In a mesocosm experiment, the soil accrual rate and soil P stability of *Chara*, pondweed, and  
2709 Southern naiad (three common SAV species) are being characterized. The mesocosms have been  
2710 in operation since July 2006, and have received waters with an average inflow TP concentration  
2711 of 36 ppb, at a mean P loading rate of 0.6 g P/m<sup>2</sup>/yr. Through May 2009, average outflow TP  
2712 levels for the *Chara*, Southern naiad, and pondweed mesocosms has been 13, 15 and 18 ppb,  
2713 respectively. Later in 2009, the accrued soils within the three vegetated systems will be collected  
2714 and compared with respect to stability of their associated P content. The project started in 2006  
2715 and is anticipated to end in late 2009.

### 2716 **Impacts of Previously Enriched Soils on Outflow Phosphorus** 2717 **Concentrations in a Submerged Aquatic Vegetation Wetland**

2718 This mesocosm assessment, which began in 2005, was conducted to determine the effects of  
2719 previously enriched soils on outflow P quality within SAV-dominated STA flow-ways. The term  
2720 “previously enriched” refers to soil that was farmed prior to the land being converted to an STA.  
2721 To date, the SAV communities cultured on native muck and Cell 4 outflow soils have provided  
2722 the lowest outflow TP concentrations, whereas SAV on previously-enriched Cell 4 inflow soils  
2723 have provided only a slight reduction from inflow TP levels. At the beginning of the study,  
2724 porewater SRP levels in Cell 4 inflow sediments were high, but have gradually declined,  
2725 presumably due to the gradual flux of SRP from the sediments into the water column. This  
2726 project started in 2005 and is scheduled for completion in late 2009.

### 2727 **Low-Level Phosphorus Loading Rate Mesocosm Assessment**

2728 Several mesocosm assessments are being conducted to characterize and optimize STA  
2729 phosphorus removal performance. The Low-Level Phosphorus Loading Rate Mesocosm  
2730 Assessment has been in operation since spring 2004, with the objective of determining if  
2731 substantial improvements in outflow quality can be achieved by operating STAs at extremely low  
2732 loading rates. Each treatment consists of a treatment train of two SAV tanks in series, followed by  
2733 a calcareous periphyton system cultured on limerock. To date, only marginal improvements in  
2734 outflow TP concentrations (13 versus 12 ppb) have been achieved by providing a 50 percent  
2735 reduction in loading rates (from 0.51 to 0.25 g P/m<sup>2</sup>/yr).

### 2736 **Assessing the Ability of STA Outflows to Support Pristine** 2737 **Everglades Flora**

2738 The goal of this study is to determine whether pristine species (e.g., calcareous periphyton  
2739 and *Utricularia* spp.) can thrive downstream of the STAs at water column phosphorus  
2740 concentrations in excess of 10 ppb (the TP criterion value for the EPA). Much of the TP in waters  
2741 discharged from well performing STAs consists of particulate P and dissolved organic P (some of  
2742 which is not readily bioavailable), and this appears to facilitate growth of the pristine species in  
2743 STA outflows that do not achieve TP levels as low as 10 ppb. While the best performing STA,  
2744 STA-3/4, has produced annual outflow TP concentrations ranging from 13 ppb to 23 ppb, some  
2745 flow paths have achieved short term outflow TP concentrations of 10-12 ppb. This project started  
2746 in 2004; the end data has yet to be determined and will depend on the utility of findings.

2747

2748 **Potential Water Quality Benefits of a Floating Aquatic Vegetation**  
2749 **Inflow Region**

2750 FAV commonly occurs in the inflow regions of STA flow-ways and is typically controlled by  
2751 the District with herbicides. However, because many FAV species exhibit explosive growth as  
2752 well as rapid assimilation of nutrients, it is hypothesized that FAV communities may actually  
2753 enhance STA inflow region P removal effectiveness. FAV species are unaffected by the  
2754 deepwater conditions that can occur in the inflow regions of STA cells during high-flow events.  
2755 For this project, which started in 2007, test cells at STA-1W are being used to document the P  
2756 removal effectiveness of FAV versus cattail, and sequential combinations of FAV-cattail, as  
2757 inflow region communities for STAs. The project started in 2007; the end date has yet to be  
2758 determined and depends on the utility of findings.

2759 **Optimization of Submerged Aquatic Vegetation Communities**

2760 Sequenced communities of EAV followed by SAV, as specified in the Long-Term Plan, have  
2761 provided effective P removal in many of the STAs. However, SAV communities are susceptible  
2762 to damage from hurricane winds. The superior P removal performance of SAV communities,  
2763 however, provides a compelling reason to encourage and maintain SAV beds in the outflow  
2764 regions of STA flow-ways.

2765 Steps that have been taken in the past three years to increase SAV sustainability include the  
2766 incorporation of EAV strips perpendicular to flow, and the encouragement of discrete EAV  
2767 stands within large SAV beds. The District and DB Environmental Laboratories, Inc. are  
2768 performing a series of investigations to characterize the impacts of EAV presence, and EAV  
2769 management techniques on water quality and sustainability of SAV beds.

2770 **STA-1W, Cell 5B, Vegetation Strip Status Update**

2771 After a series of hurricanes and storms in 2004 and 2005, visual observations showed  
2772 physical impacts to the SAV communities in most of the STA cells. Hurricane Wilma caused  
2773 extensive damage to the SAV communities causing them to be uprooted and pushed or “rolled”  
2774 up onto the surrounding levees (**Figure 5-80**). Damage was typically excessive in the larger cells  
2775 where wide-open areas exist. Since that time, emergent vegetation strips were planted or allowed  
2776 to establish in higher grounds, e.g., old farm roads, to serve as buffer against wind effects during  
2777 storms. This report is an assessment of the condition and performance of these vegetation strips in  
2778 STA-1W, Cell 5B. Actual performance, as far as wind protection, is difficult to quantify in the  
2779 field and is beyond the scope of this evaluation. In Cell 5B, four north-south vegetation strips  
2780 were planted utilizing five common plant species. In STA-1W, SAV cells are dominated by  
2781 Southern naiad and pondweed, and hydrilla. These species are either non-rooted or weakly  
2782 rooted, leaving them susceptible to high wind events.

2783 Visual observations in the initial two years from time of planting indicate that all species  
2784 successfully established and withstood the variable water depths in the cell. After three years, it is  
2785 evident that fire flag (*Thalia geniculata*) and bulrush appear to be the most successfully  
2786 established, based on density of establishment and plant condition in the dry and wet seasons.  
2787 Both species formed very thick vegetation strips ranging from 10 to 50 feet in width and up to 10  
2788 feet in height. These two species seem to be the best suited for the creation of vegetation strips.

2789 The three remaining species established only in areas where water depths did not exceed  
2790 water depths of two feet or more (**Figure 5-83**). Pickerelweed (*Pontederia cordata*) and spikerush  
2791 (*Eleocharis interstincta*) formed thick vegetation strips in some of the areas but they were limited  
2792 in stature and therefore probably would not provide the desired performance during high wind



2793 events. Duck potato (*Sagittaria lancifolia*) appeared to be in very poor condition and sparse  
 2794 coverage and is therefore considered unsuitable for future vegetation strip creation.

2795

2796

2797

2798

2799

2800

2801

2802

2803

2804



**Figure 5-80:** Photographs of SAV "roll-up" in (A) STA-2, Cell 3, and (B) STA-1W, Cell 5B, following Hurricane Wilma in 2005 (photos by the SFWMD).

2805

2806

2807

2808

2809

2810

2811


2812

2813

2814

2815

2816



**Figure 5-81:** STA-1W, Cell 5B, 2006 vegetation strip planting map illustrating planting locations for each of the five species used in the creation of the vegetation strips.

2817 In summary, establishment of vegetation strips in STA-1W Cell 5B along the old farm roads  
 2818 was generally successful. Utilizing higher ground, such as old farm roads in establishment of  
 2819 vegetation strips is recommended, especially for duck potato. The species that thrive best in  
 2820 variable water depths were pickerelweed, bulrush, and fire flag form continuous strips through  
 2821 the planted areas. Fire flag and bulrush were able to tolerate variable water depths and persisted  
 2822 even in areas where water depth exceeded two feet for extended periods. Planting of spikerush in  
 2823 areas with variable water depths is not recommended. Due to their limited stature or plant height  
 2824 and therefore less performance during high wind events, planting of duck potato and  
 2825 pickerelweed is also less desirable.

2826

2827

2828

2829

2830

2831

2832

2833

2834



2835 **Figure 5-82:** Photographs of established vegetation strips containing (A) bulrush  
 2836 (*Scirpus californicus*) and (B) fire flag (*Thalia geniculata*) (photos by the SFWMD).

2837

2838

2839

2840

2841

2842

2843

2844

2845



2843 **Figure 5-83:** Photographs of (A) pickerelweed (*Pontederia cordata*),  
 2844 (B) spikerush (*Eleocharis lancifolia*), and (C) duck potato (*Sagittaria  
 lancifolia*) three years after planting (photos by the SFWMD).

2845

## 2846 PERIPHYTON-BASED STORMWATER TREATMENT AREA 2847 IMPLEMENTATION PROJECT

2848 The Periphyton-dominated Stormwater Treatment Area (PSTA) Implementation Project  
2849 comprises a 400-acre portion of STA-3/4, Cell 2B, that was isolated by the construction of levees  
2850 to form an upstream 200-acre cell (Upper SAV Cell) and two adjacent downstream 100 acre cells  
2851 (Lower SAV and PSTA cells) (**Figure 5-84**). All cells have been managed to promote an SAV  
2852 community and its associated periphyton through repeated herbicide applications to suppress  
2853 emergent aquatic plants. The primary difference in the construction of the PSTA versus the SAV  
2854 cells is that the peat substrate in the PSTA Cell was removed down to caprock level, while the  
2855 soil in the Upper and Lower SAV cells was not disturbed. Consequently, the floor elevation of the  
2856 PSTA Cell is approximately 1.8 feet (54 cm) lower than the adjacent SAV cells. Peat was  
2857 removed from the PSTA Cell because it provided a rooting medium for emergent plants and was  
2858 a potential source of phosphorus that would flux back into the water column and reduce treatment  
2859 efficiency. The two 100 cfs (244,658 m<sup>3</sup>/d) pumps in the project's outflow pump station (G-388)  
2860 are activated by a float switch and maintain the PSTA Cell at a depth of approximately 1.9 ± 0.25  
2861 foot (58 ± 8 cm). Surface inflow to the PSTA Cell through its two inflow gates (G-390A and B)  
2862 was adjusted to operate this cell at a nominal hydraulic retention time (HRT) of approximately 5  
2863 days. The function of the Upper SAV Cell was to provide the SAV component of an emergent  
2864 aquatic vegetation (Cell 2A) SAV treatment train and deliver low TP concentration water to the  
2865 Lower SAV and PSTA cells. The original objective of this project was to compare treatment  
2866 performance, i.e., TP removal, of the PSTA Cell versus the Lower SAV Cell; however,  
2867 comparison between the two cells is not technically appropriate, as described below. Therefore,  
2868 the treatment performance of Cell 2B was added to this year's report to provide another point of  
2869 reference to compare against the PSTA Cell. The history of the PSTA Project, design  
2870 considerations, project layout, and the project's Operating Plan are discussed in previous SFERs.

2871 Water quality was monitored at all seven water control structures in the PSTA Project during  
2872 WY2009 (**Figure 5-84**). Water temperature, dissolved oxygen, conductivity, and pH were  
2873 measured in situ in conjunction with the collection of water samples. SRP, TP, and total dissolved  
2874 phosphorus (TDP) were monitored weekly; nitrite + nitrate-nitrogen, ammonium-nitrogen, TKN,  
2875 calcium, chloride, and TSS were monitored monthly; and sodium, potassium, magnesium, sulfate,  
2876 hardness, and alkalinity were monitored quarterly. Samples were collected at the upstream side of  
2877 each structure. TP was collected with both grab and auto-sampler samples; all other parameters  
2878 were collected only with grab samples. A quarterly sampling program was initiated in October  
2879 2008 to document the pattern of downstream changes in TP, TDP, and SRP concentrations within  
2880 the PSTA Cell; grab samples were collected at paired locations along two longitudinal transects  
2881 in the cell.

2882 The SAV community in the PSTA Project was surveyed on two dates during WY2009  
2883 (August 2008 and February 2009) using a geo-referenced grid of regularly spaced sampling  
2884 stations in each cell: 104 sites in the Upper SAV Cell and 48 sites in both the Lower SAV and  
2885 PSTA cells. The areal coverage of all SAV taxa combined and each SAV taxon individually at all  
2886 sites was categorized as low (up to one-third coverage), medium (one-third to two-thirds  
2887 coverage), or high (> two-thirds coverage).

### 2888 Operations and Performance

2889 South Florida experienced drought conditions during the last three water years, which  
2890 reduced stormwater runoff into STA-3/4, especially during each year's dry season (winter and  
2891 spring). The need to maintain minimum water levels in the STA necessitated that all outflow  
2892 structures be closed for much of each dry season. These conservation efforts, in turn, curtailed  
2893 operation of the PSTA Project. The dates when there was sufficient water in the STA to operate

2894 the PSTA Cell define the PSTA Project’s “operational period” for that water year. The  
2895 operational period was from June–October (115 d) in WY2007, July–December (161 d) in  
2896 WY2008, and July–December (168 d) in WY2009 (see **Figure 5-85A**). G-388 was shut down at  
2897 the end of each operational period to help conserve water in the STA. The discussion of PSTA  
2898 Project operation and data analyses presented below are limited to the operational period in each  
2899 water year unless noted otherwise.

2900 The PSTA Cell inflow gates (G-390A and B; **Figure 5-84**) were not operable during  
2901 WY2007, therefore no surface water entered the cell. Water discharged from G-388 during this  
2902 year was primarily groundwater seepage from the adjacent Upper and Lower SAV cells  
2903 (**Figure 5-85**, Panel A). The G-390A and B gates were operated in WY2008 and WY2009; G-  
2904 388 discharge in these years included surface water inflow plus seepage. Monthly PSTA Cell  
2905 outflow during WY2008 and WY2009 was 17 to 115 percent greater than the corresponding  
2906 inflow. This relationship (outflow > inflow) is reflected in the monthly inflow-outflow regression  
2907 line, which had a slope greater than one (slope = 1.48) (**Figure 5-85**, Panel B). Mean  
2908 monthly outflow exceeded inflow during WY2008 and WY2009 by 56 percent and 57 percent,  
2909 respectively.

2910 The original intent of this study was to operate the PSTA and Lower SAV cells such that each  
2911 cell received half of the inflow to the Upper SAV Cell (i.e., equal hydraulic loading to each cell)  
2912 to facilitate a comparison of the treatment efficiency of the PSTA versus SAV technologies.  
2913 Unfortunately, this plan proved unworkable and the two cells have been operated very differently.  
2914 Inflow to the PSTA Cell was regulated to achieve a target HRT, while inflow to the Upper and  
2915 Lower SAV cells was dependent upon storm events that delivered water to STA-3/4. The PSTA  
2916 Cell had surface-water hydraulic loading rates (HLRs) during the last two years (2.5 and 2.8 in/d)  
2917 substantially lower than HLRs in the Lower SAV Cell (5.1 and 8.5 in/d) but higher than those for  
2918 the Cell 2B (0.4 and 1.6 in/d). Nominal HRTs calculated for the PSTA Cell in WY2008 and  
2919 WY2009 (5.9 and 5.2 d, respectively) were very close to the target of 5 d (**Table 5-35**).


2920 Transect sampling has revealed the existence of well-defined downstream P gradients in the  
2921 STA treatment cells (e.g., see Figure 5-27 in the 2009 SFER). However, similar gradients were  
2922 not evident in the PSTA Cell for TP or SRP (**Figure 5-86**). A small gradient was observed for  
2923 TDP. Note that most of the SRP samples were at the method detection limit of 2 ppb.

2924 Summary statistics for water quality parameters monitored at all PSTA Project sampling  
2925 stations throughout WY2009 and during the WY2009 operational period are presented in  
2926 Appendix 5-11. Based on comparison of flow-weighted mean (FWM) outflow TP concentrations,  
2927 the PSTA Cell exhibited better treatment performance than either the Lower SAV Cell or Cell 2B  
2928 in each water year (**Table 5-35**). The PSTA Cell had a FMW outflow TP concentration of 8 ppb  
2929 in WY2009; all monthly outflow FWM TP concentrations during the year were less than 10 ppb  
2930 (**Figure 5-85**, Panel C). This performance was achieved at a surface-water TP loading rate of  
2931 0.368 g/m<sup>2</sup>/yr. In contrast, the PSTA Cell outflow FWM TP concentration and surface-water TP  
2932 loading rate in WY2008 were 12 ppb and 0.630 g/m<sup>2</sup>/yr, respectively. Monthly outflow FMW TP  
2933 concentrations exhibited a moderate linear relationship ( $r^2 = 0.50$ ) with monthly inflow  
2934 concentrations (**Figure 5-85**, Panel D).

2935 SAV was widespread throughout the PSTA Project in WY2009 (**Figure 5-87**). Six SAV taxa  
2936 were observed over the two sampling dates: hydrilla, muskgrass, pondweed, red ludwigia  
2937 (*Ludwigia repens*), Southern naiad, and spiny naiad (*Najas marinas*) (Appendix 5-12) compared  
2938 to 11 taxa found in WY2007 and 10 taxa in WY2008. The most frequently encountered taxa in  
2939 WY2009 were muskgrass and southern naiad as in previous years. It is thought to be of no  
2940 particular importance that fewer uncommon taxa were recorded in WY2009 compared  
2941 to previous years. The distribution of hydrilla continued to be restricted primarily to the Upper  
2942 SAV Cell.


2943       The PSTA Project monitoring program will continue for the remainder of FY2009, and a  
2944 report summarizing operations and performance since inception is planned to be prepared in  
2945 FY2010. This report will include a summary of any findings of the tracer project conducted in the  
2946 PSTA Cell in FY2009 as well as updated costs and design considerations associated with the  
2947 construction and operation of PSTA treatment cells. It is anticipated that the information in the  
2948 report will assist in decision-making about further implementation of PSTA treatment technology  
2949 features.  
2950

2951




**Figure 5-84.** Map of the Periphyton-based Stormwater Treatment Area (PSTA) Implementation Project showing the location of water control structures, the Upper SAV Cell, the Lower SAV Cell, and the PSTA Cell. The adjacent Cell 2B and its water control structures are also shown.

2952  
2953  
2954  
2955  
2956  
2957  
2958  
2959  
2960  
2961  
2962  
2963



2981



**Figure 5-87.** Distribution of SAV in the Upper SAV, Lower SAV, and PSTA cells during August 2008 and February 2009. [Note: each closed circle represents the total areal coverage level of all SAV taxa at that site. Dots indicate sites without SAV. The depiction of cell boundaries is based on the PSTA Project’s Geographic Information Systems shapefile.]



**Table 5-35.** Hydraulic characteristics and treatment performance of the PSTA Cell, the Lower SAV Cell, and STA-3/4, Cell 2B, during the WY2007, WY2008, and WY2009 PSTA Project operational periods.

	WY2007 <sup>1</sup>			WY2008 <sup>2</sup>			WY2009 <sup>3</sup>		
	PSTA	Lower SAV <sup>4</sup>	Cell 2B	PSTA	Lower SAV <sup>5</sup>	Cell 2B <sup>5</sup>	PSTA	Lower SAV <sup>5</sup>	Cell 2B <sup>5</sup>
Surface-water hydraulic loading (in/d)	0	--	4.1	2.5	5.1	0.4	2.8	8.5	1.6
Nominal hydraulic retention time (d)	10.1	--	4.7	5.9	8.7	33.8	5.2	1.3	10.3
Mean surface-water inflow (cfs)	0	--	431	10	23	46	12	38	166
Mean surface-water outflow (cfs)	9	--	530	16	7	63	18	54	243
Total surface-water inflow (ac-ft)	0	--	90714	3326	7388	14767	3953	12828	55245
Total surface-water outflow (ac-ft)	2162	--	111365	5201	2096	20103	6102	18106	80871
Surface inflow flow-weighted mean TP (ppb) <sup>6</sup>	--	--	33 (8)	28 (4)	22 (1)	26 (5)	14 (1)	21 (9)	15 (1)
Surface outflow flow-weighted mean TP (ppb) <sup>6</sup>	16 (3)	--	20 (1)	12 (2)	32 (6)	20 (3)	8 (<1)	13 (1)	12 (1)
Surface-water areal TP loading (g/m <sup>2</sup> /yr)	0	--	1.270	0.630	1.030	0.109	0.368	1.674	0.219
TP removal coefficient - k (m/yr) <sup>7</sup>	--	--	22.0	24.2	-11.5	0.9	18.8	50.1	4.7

Notes: 1 cm ≈ 0.39 in; 1 cfs ≈ 2,447 m<sup>3</sup>/d or 1.98 ac-ft/d; 1 ac-ft ≈ 1,233.5 m<sup>3</sup>; 1 ppb = 1 mg/L

<sup>1</sup> WY2007 operational period from June 17 to October 9, 2006 = 115 days

<sup>2</sup> WY2008 operational period from July 5 to December 12, 2007 = 161 days

<sup>3</sup> WY2009 operational period from July 9 to December 23, 2008 = 168 days

<sup>4</sup> The Lower SAV Cell was not operated in WY2007

<sup>5</sup> Calculations based only positive flow through the water control structures

<sup>6</sup> Values reported as mean (standard error)

<sup>7</sup>  $k = \ln(TP_{in}/TP_{out}) \times [(Vol_{in} + Vol_{out})/2] / \text{Wetland Surface Area} \times (365.25/d)$ ; calculation based only on surface flows

2982

2983

**2984 WILDLIFE AND AVIAN PROTECTION**

2985 The Avian Protection Plan (APP) for Black-necked Stilts and Burrowing Owls nesting in the  
2986 Everglades Agricultural Area Stormwater Treatment Areas discussed in the 2008 SFER –  
2987 Volume I, Chapter 5, has been finalized and accepted by the U.S. Fish and Wildlife Service  
2988 (USFWS). This plan was implemented during WY2009, and protective measures underlined in  
2989 the plan were taken during this season.

2990 This APP is unconventional in that it has been developed to help manage the operation of  
2991 constructed treatment wetlands, i.e., the STAs that already provide important benefits to  
2992 migratory birds compared to the previous land use (agriculture). This plan outlines actions  
2993 intended to minimize harmful impacts to migratory birds and nests due to operation of the STAs.  
2994 Results of this year's STAs bird surveys are presented in this section.

2995 During WY2009, the District also continued a study to evaluate and quantify the  
2996 environmental lift of the STAs on avifauna community. This study, which is being conducted  
2997 jointly by Florida Atlantic University and the University of Florida, Institute of Food and  
2998 Agricultural Services (UF-IFAS) under contract to the District and Everglades Agricultural Area  
2999 Environmental Protection District (EAA EPD), involves scientific evaluation of the bird  
3000 population, their prey, and habitat among three different habitat categories: agricultural, cropland,  
3001 natural marsh, and the STAs. Initial results indicate that the STAs create significant  
3002 environmental lift.

3003 The District in cooperation with the USFWS developed the APP for the existing STAs and  
3004 their expansions focusing on black-necked stilts (*Himantopus mexicanus*) and burrowing owls  
3005 (*Athene cunicularia floridana*). The APP characterizes the risk to these species from STA  
3006 construction, operation start-up, drought conditions operations, routine maintenance, and  
3007 enhancement activities.

**3008 Burrowing Owls**

3009 No burrowing owl nests were found in the STAs during this survey season.

**3010 Black-necked Stilts**

3011 Through implementation of the APP guidelines and proactive field operations, a majority of  
3012 observable nesting birds exhibited a successful breeding season. Standardized survey and  
3013 information-sharing methods were utilized, and operational procedures related to levee and canal  
3014 maintenance were implemented to reduce impacts to ground-nesting birds within the STAs.

3015 Increased nesting of black-necked stilts in WY2009 occurred due to an extended drought that  
3016 resulted in low water levels and exposed bottom sediments in the STAs, which increased  
3017 available nesting habitat. During WY2008, a total of 191 nests were observed compared to a total  
3018 of 873 during WY2009 (Appendix 5-14, Table 1). During the heavy rains beginning mid-May,  
3019 the District was able to manage water levels and minimize flooding of locations where the  
3020 greatest numbers of nests were present. It is assumed that some nests were flooded as a result of  
3021 the rain events and the need to provide upstream flood protection based on the lower number of  
3022 nests recorded during the spot check surveys after the storms.

3023 On March 24 and 25, 2009, preliminary levee surveys were conducted to record the status of  
3024 nesting of black-necked stilts in the STAs. At this time, field staff noted increased activity of the  
3025 birds flying and foraging in STA-1E cells 4N, 4S; a few birds were spotted in STA-2, while the  
3026 remaining STAs did not have any black-necked stilts that were visible from the levees.

3027 In mid-April, surveys determined the onset of the black-necked stilt breeding season. Per the  
3028 APP, black-necked stilts were the focus of the surveys as they are an abundant and conservative

3029 indicator species for ground-nesting birds in the STAs. Additionally, black-necked stilts nest  
3030 directly on the ground, often close to the water's edge. Nest sites are vulnerable to any increase in  
3031 water level, more so than other ground-nesting species that select sites farther upslope or in  
3032 standing vegetation, and STA operating strategies are designed to minimize impacts to the sites.

3033 Internal black-necked stilt nest surveys of treatment cells were performed from the levee  
3034 (levee surveys) by field personnel from BEM Systems, Inc. Levee surveys represent a resourceful  
3035 way to observe a large area to obtain useful information regarding the potential number of nests  
3036 within a treatment cell. Two different types of levee surveys were executed based on the type of  
3037 information needed to make operational decisions:

- 3038 • **Monthly.** This survey was performed every 30 days from the start of the breeding  
3039 season; all treatment cells were surveyed to provide baseline nesting information and  
3040 the basis for operational decisions throughout the season.
- 3041 • **Spot-check.** This survey was performed on an as-needed basis depending on water  
3042 conditions. Inspections were done on specific nest locations previously recorded,  
3043 and/or treatment cells of operational interest; nest numbers in cells not surveyed are  
3044 assumed to remain as previously observed.

3045 Black-necked stilt survey information was obtained using binoculars [10 x 50 millimeter  
3046 (mm)] or a spotting scope (20-60 x 80 mm). A hand-held Global Positioning System unit  
3047 provided latitude and longitude of observer location on the levee where nests were detected inside  
3048 of a treatment cell. Distance was measured with a rangefinder (6 x 216.0°). Information including  
3049 coordinates of observer, number and distance of nests, observations, and observer initials were  
3050 recorded in the field using an Access database (Appendix 5-14, Figure 1). Once the survey was  
3051 completed, data were sent to the District via electronic mail for analysis and report generation.  
3052 Standardized reports were used to inform District staff of the location of black-necked stilt nests  
3053 and the number of nests by flow-way and treatment cell (Appendix 5-14, Figure 2). Reports  
3054 regarding black-necked stilt nest activity and the resulting activity restrictions within the STAs  
3055 were distributed by email internally and to the USFWS, and by installing signage in the field at  
3056 nesting areas.

### 3057 ***Modification of Operational Procedures and Levee and Canal Maintenance***

3058 Adjustments to operational and mechanical procedures were developed in accordance with  
3059 the APP to reduce impacts to ground-nesting birds within the STAs. Operational adjustments  
3060 were typically implemented on a case-by-case basis and were based on stilt nesting activity and  
3061 available flow alternatives. Mowing and grading schedules, as part of levee and canal  
3062 maintenance, were adapted to occur annually before April or after July, which is outside of the  
3063 black-necked stilt breeding season. The mowing schedule is based on the species observed  
3064 nesting in the STAs.

3065 WY2009 surveys indicated that there were only two identified species of ground nesters, i.e.  
3066 the black-necked stilt and the killdeer (*Charadrius vociferous*), that nest on the levee roads and  
3067 slopes in the STAs. While the mowing schedule within the STAs is modified based on the  
3068 black-necked stilt's breeding season, it also includes the killdeer's breeding season. Both species  
3069 start nesting on levee roads between the months of April and May and have a similar gestation  
3070 period of 20 to 30 days. Modifications to operations and maintenance within the STAs are  
3071 presented in **Table 5-36**.

3072

3073

3074

3075

3076

**Table 5-36.** Modified operational and levee and canal maintenance activities implemented during the 2008 black-necked stilt breeding season.

STA	Type of Action	Date Implemented	Impact Reduction of Ground Nesters Description of Action
All	Operational	12/9/08 – held throughout the season when possible	Increased the water depth in SAV cells by 0.5 ft from the normal target stage (typically 1.25 ft) in response to predicted drought impacts.
All	Operational	Throughout breeding season	Utilized flow-ways to avoid and/or minimize nest impacts in accordance with the Avian Protection Plan.
All	Maintenance	Throughout breeding season	Modified mowing and grading schedule to reduce impacts to ground nesters and young on levee roads and embankments.
Operation Changes to Individual STAs			
1W	Operational	Throughout breeding season	Closed levee road to vehicular traffic between Cells 2A and 2B due to high number of stilt nests.

3077

3078

3079

***Status of the 2009 Black-Necked Stilt Breeding Season***

3080

3081

3082

3083

3084

3085

3086

3087

3088

3089

The 2009 breeding season surveys began in mid-April, with the earliest nests observed on April 15-17, 2009, in STA-1E, Cells 3, 4N, and 4S; STA-1W, Cell 2B; and STA-3/4, Cell 1B. Monthly surveys were implemented from May 11-15, 2009, and were again performed from June 15-19, 2009. Spot check surveys were performed when needed depending on the water conditions. Most nests were inactive by the June monthly survey, with the exception of STA-5 Cell 1A, where 7 nests were found during the June survey. The nesting season was finished in July 9, 2009. Previous nesting surveys done in 2006–2008 also indicated that peak-breeding season began in early May and extended into late June or early July. This suggests that the black-necked stilt-nesting season remained relatively consistent despite changes in environmental conditions.

3090

3091

3092

3093

3094

3095

3096

3097

There were 873 black-necked stilt nests observed via levee surveys during the 2009 breeding season, compared to 191 during the 2008 season (Appendix 5-14, Table 1), with the highest number found in STA-1W (360 nests), followed by STA-2 (237 nests) (Appendix 5-14, Table 2). The District was able to manage water levels and prevent flooding of next locations in the flow-ways with the most nests, however, it is assumed that some nests were flooded in STA-2, Cell 4, and STA-1W, Cell 2B, due to heavy rains in mid-May, which was evident in the lower count of nests recorded during the spot check surveys in these areas after the rain events (Appendix 5-14, Table 2).

3098

## 3099 RECREATIONAL FACILITIES AND ACTIVITIES

3100 Over this past year, one additional public access site was opened in the STAs, and one  
3101 boardwalk designed specifically to enhance recreation opportunities for disabled people was  
3102 constructed. The public access site has several “green” elements and is located at the southeast  
3103 corner of STA-3/4. The boardwalk is located in STA-5 and is accessible to hunters and  
3104 participants of bird-watching tours.

3105 The STA-3/4 southeast recreational facility opened in February 2009. This facility includes a  
3106 four-mile trail provided for hiking, biking, and enjoying wildlife. The trail goes past the different  
3107 types of vegetation cells in the STA. Fishing from the bank is allowed in the waters outside the  
3108 treatment footprint of the STA. The recreational site incorporates “green technology” because it  
3109 includes the use of a dry vault composting toilet instead of a septic field that has the potential to  
3110 seep nutrients into the marsh. In addition, a solar-powered fan is used in the bathroom to circulate  
3111 air, and the automated gates at the front entrances are solar-powered. The parking area has a  
3112 shade shelter with interpretive signs explaining the functions of the STA and animals that can be  
3113 seen in the area.

3114 In STA-5, a customized boardwalk was constructed to enhance recreation opportunities for  
3115 the public including the disabled (see **Figure 5-88**). The boardwalk which was built 100 yards  
3116 into the STA has cutouts in the railing that allow people in wheelchairs to see the marsh in a less  
3117 obstructed manner. The end of the boardwalk is closer to the water and has a 10 foot by 10 foot  
3118 platform with lowered railings to accommodate a person in a wheelchair or in a seated position  
3119 while shooting a firearm during waterfowl hunting. The boardwalk is accessible to participants in  
3120 the bird-watching tours conducted by the Hendry-Glades Audubon Society and the duck hunting  
3121 conducted by the Florida Fish and Game Conservation Commission (FWC).

3122

3123

3124

3125

3126

3127

3128

3129

3130

3131

3132

3133

3134

3135

3136

3137

3138

3139

3140

3141

3142

3143

3144



**Figure 5-88.** Bird watching on the STA-5 boardwalk (photo by the SFWMD).

**3145 Hunting**

3146 The STA hunting program is coordinated through the FWC, and hunts are closely  
3147 coordinated with STA staff. The STAs host alligator and waterfowl hunting quota hunts. Many  
3148 precautions have been put in place for the STA hunting program and these have become part of  
3149 the FWC rules as the program has evolved. Hunting is limited to weekend days to coordinate with  
3150 the ongoing management of the STAs. The high quality of the hunts and the limited opportunities  
3151 through the permit process encourage high compliance with the additional rules. Unlike  
3152 traditional alligator (*Alligator mississippiensis*) hunting, motorized boats are not allowed in the  
3153 STAs however canoes are allowed to be used by the hunters.

3154 Alligator hunting took place in STA-1W and STA-5 in 2008. Alligator hunts in the STAs are  
3155 managed by the FWC, and the season traditionally runs from mid-August to November 1<sup>st</sup>. The  
3156 alligator hunt permit numbers are determined by FWC to be sustainable harvest quantities. There  
3157 were 100 and 50 permits issued for STA-1W and STA-5, respectively, and each permit allowed  
3158 two alligators to be harvested. There were 133 alligators harvested from STA-1W and 61 from  
3159 STA-5.

3160 The STAs contain areas of open water and SAV, which provide ideal habitat for waterfowl.  
3161 The FWC also coordinates the waterfowl hunting program. STA-5 opened for duck hunting as an  
3162 experiment in 2002, with 25 permits issued per hunt day. Because of its popularity and no  
3163 apparent impact to the functioning of the treatment areas, the hunting program was expanded to  
3164 include the other STAs. STA-1W, STA-2, STA-3/4, and STA-5 were open for hunting in the  
3165 2008–2009 season. The waterfowl season involves migratory birds, and the bag limits are  
3166 determined by the FWC with the federal government. Hunting was permitted on one weekend  
3167 day per STA during the 2008–2009 waterfowl hunting season, for a total of 11 hunt days  
3168 (including one hunt for youths) from mid-November to the first week of February. The hunting  
3169 program brought 5,712 hunters who bagged 22,714 waterfowl.

**3170 Bird-watching Program**

3171 The public access sites at the STAs offer substantial bird-watching opportunities. Organized  
3172 bird-watching tours are conducted by Hendry-Glades Audubon Society at STA-5. Birding tours  
3173 have been extremely popular in the birding community with participants commonly spending the  
3174 night at local hotels to facilitate the tour. The diversity of birds has made STA-5 a destination for  
3175 Lifetime sightings. In addition to the diversity, birders are drawn to abundance of a number of  
3176 species. The Audubon Society conducts regularly scheduled bird counts at STA-5 and also STA-  
3177 1W.

**3178 Other Activities**

3179 STA-1E, STA-1W, and STA-3/4 are open to the public Friday through Monday. These sites are  
3180 open daylight hours and the areas open to the public start at the public access site. Each site has a  
3181 dry vault toilet and a shade shelter with information about the wildlife and the project. The STAs  
3182 provide excellent opportunities for wildlife viewing, whether hiking, or biking. Fishing is allowed  
3183 in the external canals of the STAs. STA-3/4 has a motor boat ramp that leads to 27 miles of  
3184 canals with trophy-size bass. STA-1E allows catch and release fishing in the internal cells of the  
3185 STA. The guided bird-watching tour at STA-1E has been discontinued as birding enthusiasts can  
3186 now access the area on their own. However, the guided bird-watching tour at STA-5 will continue  
3187 to be conducted by volunteer members of Hendry-Glades Audubon Society.

3188

3189

---

## STATUS OF OTHER LONG-TERM PLAN PROJECTS

---

3190

### COMPARTMENT B AND COMPARTMENT C BUILD-OUT STATUS

3191

3192 The Compartment B Build-out Project is located in Palm Beach County, west and south of  
3193 the existing boundaries of STA-2 (**Figure 5-1**). This project will enhance the performance of  
3194 STA-2 by creating additional wetland treatment area. Construction of Compartment B Build-out  
3195 started in FY2009. The project is expected to be flow-capable by the end of 2010 and all  
3196 construction will be completed by the end of 2011. The EFA permit for the project requires  
3197 modifying the existing STA-2 discharge locations. These modifications are currently in design.

3198 The Compartment C Build-out Project, located in Hendry County between the existing  
3199 boundaries of STA-5 and STA-6, will expand the size and enhance the performance of these  
3200 STAs by creating additional wetland treatment area. Construction of Compartment C Build-out,  
3201 started in FY2009 (**Figure 5-1**). The project is expected to be flow-capable by the end of 2010  
3202 and all construction will be completed by end of 2011.

### HYDROLOGIC AND HYDRAULIC ASSESSMENT AND INTERNAL MEASUREMENTS

3203

3204

3205 No activities were completed for this project in FY2009.

### ECP OPERATIONS MONITORING PROJECT

3206

3207 The objective of the ECP Operations Monitoring Project is to collect water quality samples  
3208 and monitor flow at inflow and outflow locations of all treatment cells within the STAs that are  
3209 not specified as compliance sampling locations by the STA operating permits. Flow is monitored  
3210 on a continuous basis. Water quality samples analyzed for flow-proportional TP concentrations  
3211 are collected weekly; all other water quality parameters are monitored biweekly. The TP data are  
3212 routinely used to assess the performance of each treatment cell and contribute to the development  
3213 of strategies for improving the efficiency of the TP load retained in the STAs as a whole.

### STA SITE MANAGEMENT

3214

3215 The operation of the STAs involves extensive coordinated efforts by multidisciplinary teams  
3216 and the use of innovative technologies and integrative diagnostic tools. The primary function of  
3217 STA site management is to coordinate among various departments, divisions, and external  
3218 stakeholders to facilitate resolution of day-to-day STA management and operational issues. Site  
3219 managers maintain an on-site presence at STAs to ensure the program's objectives are met.

3220 Site managers routinely report observations of changing environmental and site conditions,  
3221 maintenance concerns, or infrastructure problems to appropriate SFWMD staff. Significant  
3222 additional coordination by the site managers has been and will continue to be required during the  
3223 build-out of the Long-Term Plan components. Additionally, site managers coordinate monthly  
3224 vegetation management surveys to identify priorities and strategies to meet the overall vegetation  
3225 goals of the STA program. Site managers also monitor daily stormwater operations and confirm  
3226 that these operations are consistent with the established STA Operation Plans.

3227 Research and optimization studies provide data used to guide operations. For example,  
3228 guidance regarding water deliveries to the individual treatment flow-ways is based on information  
3229 such as cumulative average annual inflow volumes and TP loads, treatment cell outflow TP  
3230 concentrations, or the status of vegetation establishment within the treatment cells. Vegetation  
3231 management activities are coordinated with multidisciplinary teams, and staff meets weekly to  
3232 discuss operations related to performance and sustainability issues.

**3233 ACQUISITION OF SURVEY DATA**

3234 The Acquisition of Survey Data Project as described in the October 27, 2003, the Long-Term  
3235 Plan was completed in FY2005. As new STA facilities and structures are completed, or as new  
3236 survey information is needed in support of optimization or rehabilitation efforts, acquisition of the  
3237 survey data is collected at that time.

**3238 ADDITIONAL FLOW AND WATER QUALITY MONITORING  
3239 STATIONS**

3240 The Additional Flow and Water Quality Monitoring Project as described in the October 27,  
3241 2003, Long-Term Plan is complete. As new flow and water quality monitoring stations are  
3242 needed, for example, for facilities associated with the Compartment B and C STA Build-out  
3243 projects, they are included in the design and construction contracts for the overall STA facilities.

**3244 REVIEW AND CORRECTION OF FLOW  
3245 MEASUREMENT ANOMALIES**

3246 The goal of this project is to address flow estimate uncertainties and to provide good quality  
3247 flow data at all major flow stations in the STAs. Stream-gauging data are collected in the field for  
3248 use in calibrating flow equations, and flow rating analysis is conducted to improve computed  
3249 flows, detect and correct anomalous data, and estimate missing data.

3250 Improved flow equations have been completed and implemented at 100 percent in STA-1E,  
3251 STA-1W, STA-2, STA-3/4, STA-5, and STA-6. Theoretical flow equations for flow computation  
3252 have been implemented at 100 percent for structures in the STAs expansion project.

3253 Quality analysis was performed for following stations in STAs: G-251, G-255, G-259, G-302,  
3254 G-303, G-304A-J, G-306A-J, G-308, G-309, G-310, G-311, G-328, G-329A-D, G-330A-E,  
3255 G-331A-G, G-332, G-333A-E, G-334, G-335, G-337, G-342A-D, G-343, G-344A-D, G-349A  
3256 and B, G-350A and B, G-354, G-357, G-370, G-371, G-372, G-373, G-374A-F, G-375A-E,  
3257 G-376B, G-377A-E, G-379A-D, G-380A-F, G-381A-C and E, G-388, and G-393.

3258 Water balance analysis was conducted for STA-1E, STA-1W, STA-2, STA-3/4, STA-5, and  
3259 STA-6 on as-needed basis, e.g., STA-2 inflow/outflow canal water budget analysis.

3260 The dimensional analysis rating approach has been used to perform culvert ratings and  
3261 stream-gauging planning, the case studies including STA-3/4: G-374B, G-374E, G-375D,  
3262 G-376B, G-376E, G-377B, G-377D, G-378C, G-379B, G-379D, G-380B, G-380E, G-381B,  
3263 G-381E; STA-1E: S-370A, S-366D, S-369C, S-368C; STA-5: G-342, G-344, G-406; STA-2:  
3264 G-368C, G-333A-E, G-331A-F, G-329A-C, and G-328I.

3265 Improved flow rating equations have been developed for: G-368A-E, S-5AE, S-5AW,  
3266 G-344C-D, G-330A-E, G-393A-E, S-392, G-328I, G-337A, G-354A-C, S-371A-C, S-374A-C,  
3267 G-378A-E, G-328I, G-200B, G-250G, G-349B, G-350B, G-349A, G-388, and G-50.

3268 A total of 368 field measured datasets have undergone the quality assurance process. They  
3269 include: S-370A, S-367C, S-371B, S-374B, S-368C, G-378C, G-337A, G-378C, G-384C,  
3270 G-381B, G-381E, G-379D, G-380B, G-328I, G-377D, G-304I, G-375D, G-376B, G-376E,  
3271 G-379B, G-331A-F, G-379B, G-379D, G-329A-C, G-333B-E, G-354C, G-344A, G-344D,  
3272 G-378C, G-393B, G-380B, and G-380E.

3273 About 139 additional stream-flow measurements in the same were completed until July. The  
3274 stream-gauging plan was completed for STA-1E.



**3275 UPDATE AND MAINTENANCE OF HYDRAULIC MODELS**

3276 A major effort that was completed in FY2008 and early FY2009 in support of the STA  
3277 hydraulic models was the development of nearly one hundred new "preferred" datasets for flow  
3278 monitoring stations located at interior STA sites. A "preferred" dataset is defined as the "best  
3279 available data," and consists of data that has undergone post-processing quality assurance. In  
3280 FY2009, the focus was on the use of the STA Operational Envelopes for operational decision-  
3281 making in lieu of the use of the hydraulic models, therefore the new "preferred" data were used to  
3282 improve the information contained in the Operational Envelope weekly summary sheets. Future  
3283 improvements to the STA hydraulic models will be performed using the improved flow data.

3284

---

**LITERATURE CITED**

---

3285

- 3286 Allen, W.C., P.B. Hook, J.A. Biederman and O.R. Stein. 2002. Temperature and Wetland Plant  
3287 Species Effects on Wastewater Treatment and Root Zone Oxidation. *J. Environ. Qual.*, 31:  
3288 1010-1016.
- 3289 Brix, H. 1997. Do Macrophytes Play a Role in Constructed Treatment Wetlands? *Water Sci.*  
3290 *Technol.*, 35: 11-17.
- 3291 Brueske, C.C. and G.W. Barrett. 1994. Effects of Vegetation and Hydrologic Load on  
3292 Sedimentation Patterns in Experimental Wetland Ecosystems. *Ecol. Eng.*, 3: 429-447.
- 3293 Chen, H., C. Coghlan and E. Fogarty-Kellis. 2009. Effects of Vegetation Management Strategies  
3294 on the Establishment of Submersed Aquatic Vegetation in Cell 5B of Stormwater Treatment  
3295 Area 1 West (STA-1W). SFWMD Technical Publication, WMD 09-1001, April 2009. South  
3296 Florida Water Management District, West Palm Beach, FL.
- 3297 Chimney, M.J. and K.C. Pietro. 2006. Decomposition of Macrophyte Litter in a Subtropical  
3298 Constructed Wetland in South Florida (USA), *Ecological Engineering*, 27(2006): 301-321.
- 3299 Chimney, M. J., M. Nungesser, J. Newman, K. Pietro, G. Germain, T. Lynch, G. Goforth and  
3300 M.Z. Moustafa. 2000. Chapter 6: Stormwater Treatment Areas – Status of Research and  
3301 Morning to Optimize Effectiveness of Nutrient Removal and Annual Report on Operational  
3302 Compliance. In: *2000 Everglades Consolidation Report*, South Florida Water Management  
3303 District, West Palm Beach, FL.
- 3304 Coleman, J., K. Hench, K. Garbutt, A. Sexstone, G. Bissonnette and J. Skousen. 2001. Treatment  
3305 of Domestic Wastewater by Three Plant Species in Constructed Wetlands. *Water Air Soil*  
3306 *Pollution*, 128: 283-295.
- 3307 FLEPPC. 2007. List of Florida's Invasive Plant Species. Florida Exotic Pest Plant Council  
3308 *Wildland Weeds*, 10(4): Fall 2007.
- 3309 Garrett, B. and D. Ivanoff, 2008. Hydropattern Restoration in Water Conservation Area-2A.  
3310 Report submitted to the Florida Department of Environmental Protection, in fulfillment of  
3311 Permit # 0126704-001-GL (STA-2). South Florida Water Management District, West Palm  
3312 Beach, FL.
- 3313 Jensen, J.R. 2004. *Introductory Digital Image Processing*, 3<sup>rd</sup> Edition. Prentice Hall,  
3314 New York, NY.
- 3315 Koch, M.S. and K.R. Reddy, 1992. Distribution of Soil and Plant Nutrients Along a Trophic  
3316 Gradient in the Florida Everglades. *Soil Scientist Society of America Journal*, 56: 1492-1499.
- 3317 Kadlec, R.H. 2006. Free Surface Wetlands for Phosphorus Removal: The Position of the  
3318 Everglades Nutrient Removal Project. *Ecological Engineering*, 27: 361-379.
- 3319 Luckeydoo, L.M., N.R. Fausey, L.C. Brown and C.B. Davis. 2002. Early Development of  
3320 Vascular Vegetation of Constructed Wetlands in Northwest Ohio Receiving Agricultural  
3321 Waters. *Agric. Ecosyst. Environ.*, 88: 89-94.
- 3322 Nick Miller, Inc. 2003. Vegetation Map Report (Stormwater Treatment Areas 2, 5 & 6). Prepared  
3323 for the South Florida Water Management District, West Palm Beach, FL.

- 3324 Nick Miller, Inc. 2005. Vegetation Map Report (Stormwater Treatment Areas 1E, 1W, 2, 3/4, 5 &  
3325 6). Prepared for South Florida Water Management District, West Palm Beach, FL.
- 3326 Pietro, K., R. Bearzotti, G. Germain and N. Iricanin, 2009. Chapter 5: STA Performance,  
3327 Compliance and Optimization South Florida Water Management District, West Palm Beach,  
3328 FL. In: *2005 South Florida Environmental Report – Volume I*, South Florida Water  
3329 Management District, West Palm Beach, FL.
- 3330 Pickett Surveying & Photogrammetry. 2006 Vegetation Map Report (Stormwater Treatment  
3331 Areas 1E, 1W, 2, 3/4, 5 & 6). Prepared for the South Florida Water Management District,  
3332 West Palm Beach, FL.
- 3333 Ray, A.M. and R.S. Inouye. 2007. Development of Vegetation in a Constructed Wetland  
3334 Receiving Irrigation Return Flows. *Agriculture, Ecosystem and Environment*, 121: 401-406.
- 3335 Reddy, K.R. and W.F. DeBusk. 1985. Nutrient Removal Potential of Selected Aquatic  
3336 Macrophytes. *J. Environ. Qual.*, 14: 459-462.
- 3337 Richardson, C.J. and S.S. Qian. 1999. Long-term Phosphorus Assimilative Capacity in  
3338 Freshwater Wetlands: A New Paradigm for Sustaining Ecosystem Structure and Function.  
3339 *Environmental Science & Technology*, 33: 1545-1551.
- 3340 SFWMD. 2004. Operation Plan, Rotenberger Wildlife Management Area. South Florida Water  
3341 Management District, West Palm Beach, FL. January 2004.
- 3342 SFWMD. 2007a. Operation Plan, Stormwater Treatment Area 1 West. South Florida Water  
3343 Management District, West Palm Beach, FL. April 2007.
- 3344 SFWMD. 2007b. Operation Plan, Stormwater Treatment Area 3/4. South Florida Water  
3345 Management District, West Palm Beach, FL. August 2007.
- 3346 SFWMD. 2007c. Integrated Operation Plan, Stormwater Treatment Areas 5 and 6. South Florida  
3347 Water Management District, West Palm Beach, FL. August 2007.
- 3348 SFWMD. 2007d. Operation Plan, Stormwater Treatment Area 2. South Florida Water  
3349 Management District, West Palm Beach, FL. December 2007.
- 3350 SFWMD. 2007e. STA Drought Contingency Strategy Document. South Florida Water  
3351 Management District, West Palm Beach, FL.
- 3352 SFWMD. 2009a. Interim Operation Plan, Stormwater Treatment Area 1 East. South Florida  
3353 Water Management District, West Palm Beach, FL. May 2009.
- 3354 SFWMD. 2009b. Chemistry Laboratory Quality Manual. SFWMD-LAB-QM-2009-001,  
3355 Effective June 16, 2009. South Florida Water Management District, West Palm Beach, FL.
- 3356 SFWMD. 2009c. Field Sampling Quality Manual. SFWMD-FIELD-QM-001-05, Effective  
3357 February 6, 2009. South Florida Water Management District, West Palm Beach, FL.
- 3358 Weaver, K. 2004. Everglades Marsh Dissolved Oxygen Site-Specific Alternative Criterion  
3359 Technical Support Document. Florida Department of Environmental Protection,  
3360 Tallahassee, FL.
- 3361 Wetzel, R.G. 1990. Land-Water Interfaces: Metabolic and Limnological Regulators (Edgardo  
3362 Baldi Memorial Lecture). *Ver. Int. Ver. Limnol.*, 24: 6-24.